Sterling Drilling Company, Rig #4

Box 1006, Pratt, Kansas 67124-1006 Office Phone (316) 672-9508, Fax 672-9509

SAMPLE LOG

Fair 'B' 1-10

LOCATION:

70'N of Ne Se Ne

Section 10 T 21s

R 11w

API:

15-185-230870000

Stafford County, Kansas

OWNER: F.G. Holl Company, L.L.C.

COMMENCED:

15-Jun-99

CONTRACTOR: Sterling Drilling Company, Rig #4

COMPLETED:

24-Jun-99

TOTAL DEPTH:

DRILLER 3475

Ground Elevation:

1751

LOGGER

3475 FEET 3475 FEET

KB Elevation:

1760

<u>LOG</u>

172 FEET

Top Soil and Sand

0 -172 -

462 FEET

Shale

462 -

486 FEET

Anhydrite

486 -

3475 FEET

Limestone, Shale and Dolomite

Cored: 240' to 258' (18') Full Recovery.
302' to 321' (19') Full Recovery.
321' to 340' (19') Recovered 16'.

(Cored 74' Total)

347' to 365' (18') Recovered 16'.

CASING RECORDS

Surface Casing:

Spud @ 9:30 am on 06-15-99. Drilled 12-1/4" hole to 225'. Ran 5 joints of new 24# 8-5/8" surface casing 210.89' set at 222' KB. Cemented with 225 sacks 60/40 Poz, 2% Gel, 3% CC. Plug down at 2:15 pm on 06-15-99 by Acid Services. Good returns. Ticket # 01415.

Production Casing:

Ran 83 jts of New 5-1/2" 14# casing. Tallied 3473.99', set at 3473' KB.

Cemented with 75 sacks lite and 175 sacks 50/50 Poz, 2% Gel, 5# Gil, 10% Salt, .5% Fla, 1/4# Flocele. Plug down at 11:45 am on 06-24-99 by Acid Services, ticket # 01421. Plugged rathole with 15 sacks, mousehole with 10 sacks.

DEVIATION SURVEYS

1/2	degree(s) at	225	feet
3/4	degree(s) at	2709	feet
1	degree(s) at	3135	feet