

Lease :	schendel	
Owner:	Bobcat Oilfield Services Inc.	
OPR #:	3895	
Contractor:	DALE JACKSON PRODUCTION CO.	
OPR #:	4339	
Surface:	Cemented:	Hole Size:
20FT, 6IN	5 SACKS	8 3/4
Longstring	Cemented:	Hole Size:
713' 2 7/8	90	5 5/8

hydrill

Dale Jackson Production Co.
 Box 266, Mound City, Ks 66056
 Cell # 620-363-2683
 Office # 913-795-2991

Well #: 5-10
Location: SE NE NW S24 T16 R21
County: Miami
FSL: 4200
FEL: 2980
API#: 15-121-28793-00-00
Started: 8-13-2010
Completed: 8-17-2010
TD: 722

SN:	Packer:
NONE	
Plugged:	Bottom Plug:

Well Log

TKN	BTM Depth	Formation	TKN	BTM Depth	Formation
1	1	Top soil	22	669	Shale
11	12	Clay	.3	672	Oil sand (very shaley)(fair bleed)
8	16	Lime	2.5	674.5	Oil sand (some shale)(good bleed)
5	21	Black shale	1	675.5	Shale (fracture)(water)(some oil sand0
14	35	Lime	4.5	680	Oil sand (fair bleed)(some shale)
7	42	Sand (dry)	1	681	Sandy shale(oil sand str.)
3	45	Shale	3	684	Oil sand (shaley)(fair bleed)
16	61	Lime	4	688	Shale (oil sand str.)
10	71	Shale	7	695	Sandy shale
2	73	Red bed	TD	722	shale
15	88	Shale			
17	105	Lime			
27	132	Sandy shale			
63	195	Shale			
20	215	Lime			
11	276	Shale			
7	232	Sand (dry)			
12	244	Shale			
8	252	Lime			
21	273	Shale			
12	285	Sand (dry)			
8	293	Lime			
22	315	Shale			
27	342	Lime			
7	349	Black shale			
22	371	Lime			
4	375	Black shale			
12	387	Lime			
26	413	Shale			
3	417	Sand (dry0			
71	487	Shale			
14	501	Sandy shale (oil show)			
55	556	Shale			
6	562	Lime			
20	582	Shale			
4	586	Coal			
5	591	Shale			
8	599	Lime (shaley)			
1	600	Shale			
2	602	Oil sand (shaley) (poor bleed)			
13	615	Shale			
4	619	Lime			
1	620	Coal			
6	626	Shale			
5	631	Lime			
11	642	Shale (limey)			
5	647	lime			