

|          |                    |       |           |      |        |                   |          |       |    |
|----------|--------------------|-------|-----------|------|--------|-------------------|----------|-------|----|
| Customer | White Explorations |       | Lease No. |      |        | Date              | 2-24-12  |       |    |
| Lease    | Carr               |       | Well #    | 2-34 |        | Service Receipt   |          |       |    |
| Casing   | 4 5/8              | Depth | 1613 RTD  |      | County | Stanton           |          | State | KS |
| Job Type | Surface            |       | Formation |      |        | Legal Description | 34-29-41 |       |    |

| Pipe Data       |         | Perforating Data |          | Cement Data |
|-----------------|---------|------------------|----------|-------------|
| Casing size     | 4 5/8   | Tubing Size      | Shots/Ft |             |
| Depth           | 1612.62 | Depth            | From     | To          |
| Volume          | 99.85   | Volume           | From     | To          |
| Max Press       | 1500    | Max Press        | From     | To          |
| Well Connection | P.C.    | Annulus Vol.     | From     | To          |
| Plug Depth      |         | Packer Depth     | From     | To          |

Lead 405 SX A1-6m.  
@ 11.4# 380 CaCl  
1/4# Pdl. 240 WCA-1  
2.95 u 18.10 gal  
Tail in 150 SX "C"  
@ 14.8# 280 CaCl  
1/4# Pdl  
1.34 u 6.33 gal

| Time  | Casing Pressure | Tubing Pressure | Bbls. Pumped | Rate | Service Log                           |
|-------|-----------------|-----------------|--------------|------|---------------------------------------|
| 06:00 |                 |                 |              |      | on loc, spot trucks, RU, surface, etc |
| 10:47 | 2400            |                 |              |      | psi test                              |
| 10:50 | 110             |                 | 0            | 5    | start mixing @ 11.4#                  |
| 11:45 | 50              |                 | 213          | 5    | on tail @ 14.8#                       |
| 12:00 | 0               |                 | 36           | -    | shut down, prop plug                  |
| 12:02 | 0               |                 | 0            | 5    | start disp, washup                    |
| 12:25 | 330             |                 | 80           | 2    | slow rate                             |
| 12:30 | 350             |                 | 90           | 1    | slow rate                             |
| 12:36 | 400-1050        |                 | 100          | -    | plug down                             |
| 12:38 | 1050-0          |                 |              |      | release psi, float held               |
|       |                 |                 |              |      | job complete                          |
|       |                 |                 |              |      | thank you                             |
|       |                 |                 |              |      | chad & crew                           |

|               |        |            |              |              |  |
|---------------|--------|------------|--------------|--------------|--|
| Service Units | 194806 | 2822337772 | 11354 194806 | 33021 194806 |  |
| Driver Names  | CHINE  | R. Olds    | J. Grijalva  | S. Swafford  |  |

Kelly Wilson Customer Representative     
 Serry Bennett Station Manager     
 Chad Hine Cementer