

Citation Oil & Gas Corp

Schmitt # 8-7

CASING & CEMENTING RECORD

No	Jts. Run	Size	Weight #/ft.	Grade	Thread	Footage (ft.)
84		5 1/2"	15.5	J 55	8 rnd	3428
TOTALS						

6 Shoe Depth 3428.45 Float Collar Depth 3346.59 Top of Liner NONE  
 Cemented Bottom w/ 200 sxs Common 1090 Salt, 290 gel, 1/4# flo seal/sx  
500 gal pre mud flush  
 Cement Plug Down At 7:45 pm w/ 1500 psi Date 2-15-2012  
 CMT.D. D V or Top w/ \_\_\_\_\_ Plug CMT. Down @ \_\_\_\_\_ w/ \_\_\_\_\_ p.s.i. Date \_\_\_\_\_

SQUEEZES

7 No. \_\_\_\_\_ Tool @ \_\_\_\_\_ Broke Down Perf. \_\_\_\_\_ to \_\_\_\_\_ w/ \_\_\_\_\_ # Pump off \_\_\_\_\_ # Mixed \_\_\_\_\_  
 \_\_\_\_\_ sxs \_\_\_\_\_ CMT Sqzd. \_\_\_\_\_ sxs. into perf. left \_\_\_\_\_  
 \_\_\_\_\_ sxs. in CSG Final and Max. Press. \_\_\_\_\_ # Reversed \_\_\_\_\_ sxs. Job Comp. @ \_\_\_\_\_ Date \_\_\_\_\_  
 8 No. \_\_\_\_\_ Tool @ \_\_\_\_\_ Broke Down Perf. \_\_\_\_\_ to \_\_\_\_\_ w/ \_\_\_\_\_ # Pump off \_\_\_\_\_ # Mixed \_\_\_\_\_  
 \_\_\_\_\_ sxs. \_\_\_\_\_ CMT Sqzd. \_\_\_\_\_ sxs. into perf. left \_\_\_\_\_  
 \_\_\_\_\_ sxs. in CSG Final and Max. Press. \_\_\_\_\_ # Reversed \_\_\_\_\_ sxs. Job Comp. @ \_\_\_\_\_ Date \_\_\_\_\_

PRODUCTION TEST

9 No. \_\_\_\_\_ Perf \_\_\_\_\_ To \_\_\_\_\_ PKR @ \_\_\_\_\_ Water Cushion \_\_\_\_\_ BTM CHK \_\_\_\_\_ TOP CHK \_\_\_\_\_  
 Tool Open \_\_\_\_\_ Hrs. Fluid To Surf \_\_\_\_\_ Min w/ \_\_\_\_\_ # Tool Closed \_\_\_\_\_ Hrs. Shut In \_\_\_\_\_

Hrs. Time	Ck. Size	Tbg. Press.	Gas MCF	Oil bpd	Water bpd	% H <sub>2</sub> O	% BS & W	GOR	Corr. Grav.

30

