

Citation Oil & Gas Corp
 Wieland Unit
 Schmitt # 8-11

CASING & CEMENTING RECORD

No Jts. Run	Size	Weight #/ft.	Grade	Thread	Footage (ft.)
87	5.5"	15.5	J55 LT&C	8rnd	3443.30
TOTALS					

6 Shoe Depth 3451.10 Float Collar Depth 3373.62 Top of Liner None
 Cemented Bottom w/ 200 sxs 10% soft 2% gel 1/4" flo seal
 Cement Plug Down At 9:15 pm w/ 1300 psi Date 2-28-2012
 CMTD. D. V. or Top w/ _____
 Plug CMT. Down @ _____ w/ _____ p.s.i. Date _____

SQUEEZES

17 No. _____ Tool @ _____ Broke Down Perf. _____ to _____ w/ _____ Pump off _____ # Mixed
 _____ sxs. _____ CMT Sgzd. _____ sxs into perf. left _____
 _____ sxs in CSG Final and Max. Press. _____ # Reversed _____ sxs Job Comp. @ _____ Date _____
 18 No. _____ Tool @ _____ Broke Down Perf. _____ to _____ w/ _____ Pump off _____ # Mixed
 _____ sxs. _____ CMT Sgzd. _____ sxs into perf. left _____
 _____ sxs in CSG Final and Max. Press. _____ # Reversed _____ sxs Job Comp. @ _____ Date _____

PRODUCTION TEST

19 No. _____ Perf _____ To _____ PKR @ _____ Water Cushion _____ BTM CHK _____ TOP CHK _____
 Tool Open _____ Hrs. Fluid To Surf _____ Min w/ _____ Tool Closed _____ Hrs. Shut In _____

Hrs Time	Ck. Size	Tbg. Press.	Gas MCF	Oil bpd	Water bpd	% H ₂ O	% BS & W	GOR	Corr. Grav

30