

DAILY DRILLING REPORT

PROSPECT Tuttle A YEAR 1980
Byron WELL NO. 1 WELL LOCATION C SE/4 COUNTY Kiowa STATE KS
 WELL SITE LEASE DESCRIPTION Sec. 6-27S-16W CODE _____
 OPERATOR Beren Corporation ELEVATION: GR 2101
 CONTRACTOR Sterling Drilling DF _____
 GEOLOGIST Bob Lewellyn KB 2111
 DEVELOPMENT WELL _____ PROSPECT TEST WELL X NOTIFY Lexicon Resources Corporation
 OWNERSHIP 1980 Beren Program 633 17th Street
First of Denver Plaza, Suite 2110
Denver, Colorado 80202
 IDENTIFICATION Test Well
Farm-out from Lexicon

Susan (303) 623-1760

TOPS:	
Base Wellington	2313 (- 202) Brn Lime 4063 (-1952) Ms Ch 4593 (-2482)
Herington	2335 (- 224) Lansing 4079 (-1968) KK Sh 4641 (-2530)
Council Grove	2692 (- 581) BKC 4386 (-2275) KK Sd 4664 (-2553)
Indian Cave Zone	3130 (-1019) Marmaton 4424 (-2313) RTD 4684
Penn	3145 (-1034) Pawnee 4474 (-2363)
Bern	3417 (-1306) FS 4544 (-2433)
Topeka	3585 (-1474) Ch Shale 4556 (-2445)
Heebner	3904 (-1793) +2 Ch Sd 4562 (-2451)

MOVING IN & RIGGING UP December 23, 1980 SPUD 10:00 am on 12/28/80

SET 8 5/8" @ 457' w/ 300 sx 60-40 pozmix, 2% gel, 3% CC. P.D. 6:15 PM 12-28-80.

DATE	DEPTH	DST
12/30/80	2496'	#1 4534 - 4575 (Cher Sd) 30/45/30/90 Strong blow, GTS 2 minutes Gauge on 2" choke: 9010 MCF, 10 min 8600 MCF, 20 min 8600 MCF, 30 min 9010 MCF, 40 min 9400 MCF, 50 min & stable
12/31/80	3100'	
1/1/81	3735'	
1/2/81	4245'	
1/3/81	4575'	
1/4/81	4613'	Rec: No fluid 1561/1561 1086/1199 1076/1199
1/5/81	4633'	#2 4596 - 4613 (Miss) 30/45/120/90 Strong blow throughout Rec: 90' mud 1168/1117 21/42 31/73
1/6/81	4684'	Running Petro-Logs & will run 5 1/2" production casing this PM @ 4683', one foot off bottom. #3 4613 - 4633 (Miss) 30/45/120/90 Weak blow throughout Rec: 60' mud 931/787 31/31 31/52
LOG TOPS:		
Heebner	3910 (-1799)	Cher A Sd 4553 (-2442)-4
BL	4057 (-1946)	Cher B Sd 4562 (-2451)-10
Lansing	4074 (-1963)	Miss 4595 (-2484)-42
BKC	4373 (-2262)	KK Sh 4654 (-2543)
Pawnee	4471 (-2360)	KK Sd 4660 (-2549)
FS	4538 (-2427)	LTD 4683 (-2572)
Cher Sh	4548 (-2437)	#4 4666 - 4684 (Kind Sd) Mis-run, tool wouldn't open.
1/7/81	Ran 155 joints 5 1/2" production casing (4690'). Set at 4683'. Cemented with 250 sx 60-40 pozmix, 10% salt, 3/4 of 1% CFR-2, 10# gil/sx. P.D. 3:45 AM 1-7-81.	#5 4668 - 4684 (Kind Sd) 30/45/30/45 Weak blow 30 minutes Rec: 10' mud 1261/1034 31/31 31/31