

Sky Drilling, L.L.C.
Park Place – Becker Building
11551 Ash Street, Suite # 205
Leawood, Kansas 66211
Office (913) 499-8373
Fax (913) 766-1310

August 31, 2012

Company: Haas Petroleum, LLC
11551 Ash Street, # 205
Leawood, Kansas 66211

Lease: Massey – Well # 6 I HP
County: Woodson
Spot: E2 SW Sec 35, Twp 23, SR 14 E
Spud Date: August 10, 2012
API: 15-207-28214-00-00
TD: 1724'

8/10/12: Build location, dig pits. Move in Rig #2 and rig up. Spud 12 ¼ surface hole. Drill from 0' to 40' TD. At TD 40' cir hole clean. Trip out 12 ¼ bit. Rig and ran 40' of 8 5/8 casing. Cement with 25 sacks cement. Shut down from weekend.

8/13/12: Start up. Trip in hole with 6 ¾ PDC bit. Drill out cement. Drill from 40' to 1043'.

8/14/12: Drill from 1043' to 1724' TD. Mud up @ 1196, rig up gas sniffer. CFS @ 1649. At TD 1724' cir hole clean. Trip out hole to collars. Shut down.

8/16/12: Start up. Trip back to bottom. Cir hole 45 minutes. Rig and lay down drill pipe and collars. Rig and ran 1711' of 4 ½ casing. Rig up cementers and cement. Cir cement to top.



 ENTERED

TICKET NUMBER 37795

LOCATION Eureka

FOREMAN Steve Head

FIELD TICKET & TREATMENT REPORT

CEMENT APT 15-207-28214

DATE	CUSTOMER #	WELL NAME & NUMBER	SECTION	TOWNSHIP	RANGE	COUNTY
8-16-12	3451	Massey 6T-HP	35	23S	14E	Woodson
CUSTOMER						
Haas Petroleum, LLC						
MAILING ADDRESS						
11551 Ash ST, Suite 205						
CITY	STATE	ZIP CODE	TRUCK #	DRIVER	TRUCK #	DRIVER
Leawood	KS	66311	485	Alan m		
			611	Joey		
			479	merle		

JOB TYPE <u>Long string</u>	HOLE SIZE <u>6 3/4</u>	HOLE DEPTH <u>1724</u>	CASING SIZE & WEIGHT <u>4 1/2 1260</u>
CASING DEPTH <u>17</u>	DRILL PIPE _____	TUBING _____	OTHER _____
SLURRY WEIGHT _____	SLURRY VOL _____	WATER gal/sk _____	CEMENT LEFT in CASING _____
DISPLACEMENT <u>27 3/4 bbls</u>	DISPLACEMENT PSI <u>500</u>	<u>Bump</u> Mud pump <u>1100</u>	RATE _____

REMARKS: SAFETY Meeting. Rig up to 4½ casing. Break circulation w/ 10 bbls Fresh water. Mix 145 sks 60/40 pozmix Cement w/ 8% Gel. ½" phenoseal pack AT 13.5" perf. Tail in with 50 sks Thick Set Cement w/ 5" Kol seal per/sk AT 13.4" gel. Wash out pump & lines. Shut down. Release Plug. Displace with 27½ bbls Fresh water. Final pumping Pressure 500". Bump Plug 1100". Wait 2 min. Release Pressure. Plug held. Gravel Cement Returns to Surface 12 bbls to PIT. Job Complete Rig down.

Thank you

[illegible]

Ravin 3737

I acknowledge that the payment terms, unless specifically amended in writing on the front of the form or in the customer's account records, at our office, and conditions of service on the back of this form are in effect for services identified on this form.