

SCANNED

Well Refined Drilling Company, Inc.
 4230 Douglas Road Thayer, Kansas 66776
 Contractor License # 33072 - FEIN # 48-1248553
 620-839-5581/Office; 620-432-6170/Jeff; 620-839-5582/FAX

HAVE RIG
 Rig # 5
 WILL DIG

Rig #:	5	Lic # 5150	S31	T32S	R18E			
API #:	15-099-24583-0000		Location:	NW,SE,SE,SW				
Operator:	Colt Energy Inc.		County:	Labette				
Address:	P.O Box 388							
	Iola, Ks 66749		Gas Tests					
Well #:	14-31	Lease Name: Parks Revocable Trust	Depth	Oz.	Office	flow - MCF		
Location:	415	FSL Line						
	2040	FWL Line	See Page 3					
Spud Date:	5/20/2010							
Date Completed:	5/24/2010	TD: 1055						
Driller:	Josiah Kephart							
Casing Record	Surface	Production						
Hole Size	12 1/4"	7 7/8"						
Casing Size	8 5/8"							
Weight								
Setting Depth	20' 6"							
Cement Type	Portland							
Sacks	5							
Geologist:	Jim Stegeman							
10LE-052410-R5-011-Parks Revocable Trust 14-31-Colt Energy Inc.								
Well Log								
Top	Bottom	Formation	Top	Bottom	Formation	Top	Bottom	Formation
0	2	overburden	221	231	lime	452	455	sand
2	3.5	clay	231	237	sand			oil odor
3.5	5	lime	237	244	shale	455	480	1st Oswego lime
5	44	shale	244	245	coal	480	482	shale
44	46	lime	245	246	lime	482	484	Summit blk shale
46	113	shale	246	263	shale	484	509	2nd Oswego lime
113	115	slime	263	267	sandy shale	509	510	shale
115	125	shale	267	274	sand	510	515	Excello blk shale
125	127	lime	274	283	sandy shale	515	516.5	Mulky coal
127	174	shale	283	352	shale	516.5	520	Breezy Hill lime
174	176	blk shale	352	374	lime	520	523	shale
176	177	shale	374	375	shale	523	526	lime
177	178	coalk	375	378	blk shale	526	547	shale
178	181	shale	378	379.5	coal	547	549	coal
181	215	lime	379.5	444	shale	549	560	shale
215	217	shale	405		stopped for day	560	561	coal
217	219	blk shale	444	449	sand	561	572	shale
219	221	shale	449	452	sandy shale	572	573	lime

Top	Bottom	Formation	Top	Bottom	Formation	Top	Bottom	Formation
573	577	shale						
577	578.5	blk shale						
578.5	581	shale						
581	582.5	coalk						
582.5	628.5	shale						
628.5	629	lime - hard						
629	630	coalk						
630	670	shale						
670	672	blk shale						
672	673	coalk						
673	710	shale						
710	713	blk shale						
713	725	shale						
725	727	sand						
727	741	shale						
741	742	coalk						
742	767	shale						
767	772	sand						
772	776	shale						
776	777	coalk						
777	870	shale						
870	871.5	AW coal						
871.5	877	shale						
877	878	BW coal						
878	932	shale						
932	934	coalk						
934	939	shale						
939	967	chat						
945		oil odor						
967	1055	lime						
1055		Total Depth						

Notes:

5/20/2010
Set surface - 20' 6" - 5 Portland - waited 1 1/2 hours on dozer

5/21/2010
Drilled to 405'

5/24/2010
TD'd well at 1055'