

Well Report



Company : Dorado E&P Partners
 Well : Preisser 25-9-6 1H
 Location : Reno County Kansas
 Reference: Grid North

Page: 1
 Date : 9/11/2012
 File : OK 12129

Vertical Section Calculated Along Azimuth 0.00°

	KB Elevation = 1733.00ft				GR. Elevation = 1721.00ft					
	MD ft	Inc deg	Azi deg	TVD ft	North ft	East ft	V'Sect ft	D'Leg %/100	Build %/100	Turn %/100
0	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
1	1619.00	0.40	69.50	1618.99	1.98	5.29	1.98	0.02	0.02	4.29
2	2155.00	0.30	49.90	2154.98	3.54	8.12	3.54	0.03	-0.02	-3.66
3	2559.00	0.30	126.50	2558.97	3.59	9.78	3.59	0.09	0.00	18.96
4	3149.00	0.50	154.00	3148.96	0.36	12.15	0.36	0.05	0.03	4.66
5	3166.00	0.70	124.20	3165.96	0.23	12.27	0.23	2.14	1.18	-175.29
6	3197.00	0.50	111.10	3196.96	0.08	12.55	0.08	0.78	-0.65	-42.26
7	3228.00	1.60	3.40	3227.95	0.46	12.70	0.46	5.86	3.55	-347.42
8	3259.00	5.30	358.50	3258.89	2.32	12.69	2.32	11.96	11.94	-15.81
9	3290.00	9.00	1.30	3289.64	6.18	12.71	6.18	11.98	11.94	9.03
10	3321.00	11.60	3.40	3320.14	11.72	12.95	11.72	8.47	8.39	6.77
11	3352.00	14.20	2.30	3350.36	18.63	13.28	18.63	8.42	8.39	-3.55
12	3383.00	16.20	358.90	3380.27	26.75	13.35	26.75	7.06	6.45	-10.97
13	3414.00	18.50	356.90	3409.86	35.99	13.01	35.99	7.66	7.42	-6.45
14	3445.00	21.50	356.90	3438.99	46.58	12.43	46.58	9.68	9.68	0.00
15	3476.00	24.40	358.00	3467.53	58.65	11.90	58.65	9.46	9.35	3.55
16	3507.00	27.50	359.10	3495.40	72.21	11.57	72.21	10.12	10.00	3.55
17	3538.00	30.70	359.40	3522.48	87.28	11.37	87.28	10.33	10.32	0.97
18	3569.00	33.20	359.80	3548.79	103.68	11.26	103.68	8.09	8.06	1.29
19	3600.00	35.90	359.60	3574.32	121.26	11.16	121.26	8.72	8.71	-0.65
20	3631.00	38.70	359.20	3598.97	140.05	10.97	140.05	9.07	9.03	-1.29
21	3663.00	41.30	359.10	3623.49	160.61	10.66	160.61	8.13	8.13	-0.31
22	3694.00	43.80	359.30	3646.32	181.57	10.37	181.57	8.08	8.06	0.65
23	3725.00	45.90	359.60	3668.30	203.43	10.16	203.43	6.81	6.77	0.97
24	3756.00	47.70	359.40	3689.52	226.03	9.96	226.03	5.83	5.81	-0.65
25	3787.00	49.60	359.40	3710.00	249.30	9.72	249.30	6.13	6.13	0.00
26	3818.00	52.10	359.00	3729.57	273.33	9.38	273.33	8.13	8.06	-1.29
27	3849.00	54.50	359.20	3748.09	298.18	8.99	298.18	7.76	7.74	0.65
28	3879.00	56.20	358.50	3765.15	322.86	8.49	322.86	5.98	5.67	-2.33
29	3910.00	58.60	358.80	3781.85	348.96	7.88	348.96	7.78	7.74	0.97
30	3941.00	62.00	359.00	3797.21	375.88	7.36	375.88	10.98	10.97	0.65
31	3972.00	64.70	358.50	3811.11	403.58	6.76	403.58	8.83	8.71	-1.61
32	4003.00	67.30	359.00	3823.72	431.89	6.14	431.89	8.52	8.39	1.61
33	4034.00	69.50	359.80	3835.13	460.71	5.84	460.71	7.49	7.10	2.58
34	4065.00	70.50	359.70	3845.73	489.84	5.71	489.84	3.24	3.23	-0.32
35	4096.00	71.20	359.40	3855.90	519.12	5.48	519.12	2.44	2.26	-0.97

Well Report



Company : Dorado E&P Partners
 Well : Preisser 25-9-6 1H
 Location : Reno County Kansas
 Reference: Grid North

Page: 2
 Date : 9/11/2012
 File : OK 12129

Vertical Section Calculated Along Azimuth 0.00°

	KB Elevation = 1733.00ft				GR. Elevation = 1721.00ft					
	MD	Inc	Azi	TVD	North	East	V'Sect	D'Leg	Build	Turn
	ft	deg	deg	ft	ft	ft	ft	%/100	%/100	%/100
36	4127.00	71.60	359.00	3865.79	548.50	5.07	548.50	1.78	1.29	-1.29
37	4158.00	72.20	359.10	3875.42	577.96	4.59	577.96	1.96	1.94	0.32
38	4189.00	73.40	358.90	3884.59	607.57	4.07	607.57	3.92	3.87	-0.65
39	4220.00	76.40	359.00	3892.66	637.49	3.52	637.49	9.68	9.68	0.32
40	4251.00	78.30	359.20	3899.45	667.73	3.05	667.73	6.16	6.13	0.65
41	4282.00	81.00	359.60	3905.02	698.22	2.73	698.22	8.80	8.71	1.29
42	4313.00	84.00	0.20	3909.06	728.96	2.67	728.96	9.87	9.68	1.94
43	4344.00	85.50	0.40	3911.90	759.82	2.83	759.82	4.88	4.84	0.65
44	4375.00	87.00	1.10	3913.93	790.75	3.24	790.75	5.34	4.84	2.26
45	4429.00	89.10	359.90	3915.77	844.72	3.71	844.72	4.48	3.89	-2.22
46	4460.00	89.60	0.20	3916.12	875.71	3.74	875.71	1.88	1.61	0.97
47	4491.00	89.90	0.30	3916.25	906.71	3.87	906.71	1.02	0.97	0.32
48	4522.00	89.30	359.80	3916.47	937.71	3.90	937.71	2.52	-1.94	-1.61
49	4553.00	89.20	0.00	3916.87	968.71	3.85	968.71	0.72	-0.32	0.65
50	4584.00	89.00	0.30	3917.36	999.71	3.93	999.71	1.16	-0.65	0.97
51	4615.00	87.90	0.20	3918.20	1030.69	4.06	1030.69	3.56	-3.55	-0.32
52	4646.00	86.90	359.90	3919.61	1061.66	4.09	1061.66	3.37	-3.23	-0.97
53	4677.00	86.80	359.40	3921.31	1092.61	3.90	1092.61	1.64	-0.32	-1.61
54	4708.00	86.90	359.10	3923.01	1123.56	3.49	1123.56	1.02	0.32	-0.97
55	4739.00	87.10	358.90	3924.64	1154.52	2.95	1154.52	0.91	0.65	-0.65
56	4770.00	86.40	358.90	3926.39	1185.46	2.36	1185.46	2.26	-2.26	0.00
57	4801.00	86.10	359.10	3928.42	1216.39	1.82	1216.39	1.16	-0.97	0.65
58	4832.00	85.40	358.60	3930.72	1247.30	1.20	1247.30	2.77	-2.26	-1.61
59	4863.00	84.20	358.60	3933.53	1278.16	0.45	1278.16	3.87	-3.87	0.00
60	4894.00	84.20	358.70	3936.66	1308.99	-0.28	1308.99	0.32	0.00	0.32
61	4925.00	84.70	358.70	3939.66	1339.84	-0.98	1339.84	1.61	1.61	0.00
62	4956.00	85.20	358.30	3942.39	1370.71	-1.79	1370.71	2.06	1.61	-1.29
63	4987.00	85.80	358.60	3944.82	1401.60	-2.62	1401.60	2.16	1.94	0.97
64	5018.00	86.30	358.60	3946.96	1432.52	-3.38	1432.52	1.61	1.61	0.00
65	5049.00	86.80	358.70	3948.82	1463.45	-4.11	1463.45	1.64	1.61	0.32
66	5080.00	87.20	358.50	3950.44	1494.40	-4.87	1494.40	1.44	1.29	-0.65
67	5111.00	88.30	358.30	3951.66	1525.37	-5.73	1525.37	3.61	3.55	-0.65
68	5142.00	89.50	358.40	3952.26	1556.35	-6.62	1556.35	3.88	3.87	0.32
69	5173.00	90.30	358.70	3952.31	1587.34	-7.41	1587.34	2.76	2.58	0.97
70	5204.00	91.40	358.90	3951.85	1618.33	-8.06	1618.33	3.61	3.55	0.65
71	5235.00	92.20	358.90	3950.88	1649.31	-8.65	1649.31	2.58	2.58	0.00

Well Report



Company : Dorado E&P Partners
 Well : Preisser 25-9-6 1H
 Location : Reno County Kansas
 Reference: Grid North

Page: 3
 Date : 9/11/2012
 File : OK 12129

Vertical Section Calculated Along Azimuth 0.00°

	KB Elevation = 1733.00ft				GR. Elevation = 1721.00ft						
	MD	Inc	Azi	TVD	North	East	V'Sect	D'Leg	Build	Turn	
	ft	deg	deg	ft	ft	ft	ft	%/100	%/100	%/100	
72	5266.00	93.00	358.90	3949.47	1680.27	-9.25	1680.27	2.58	2.58	0.00	
73	5297.00	93.40	359.20	3947.74	1711.21	-9.76	1711.21	1.61	1.29	0.97	
74	5327.00	94.70	359.20	3945.62	1741.14	-10.18	1741.14	4.33	4.33	0.00	
75	5358.00	95.50	359.30	3942.86	1772.01	-10.58	1772.01	2.60	2.58	0.32	
76	5389.00	95.60	359.60	3939.87	1802.86	-10.88	1802.86	1.02	0.32	0.97	
77	5420.00	94.70	0.10	3937.08	1833.74	-10.96	1833.74	3.32	-2.90	1.61	
78	5451.00	94.60	359.90	3934.57	1864.64	-10.96	1864.64	0.72	-0.32	-0.65	
79	5482.00	95.20	0.10	3931.92	1895.52	-10.96	1895.52	2.04	1.94	0.65	
80	5513.00	94.20	359.40	3929.38	1926.42	-11.09	1926.42	3.93	-3.23	-2.26	
81	5544.00	92.60	359.60	3927.54	1957.36	-11.36	1957.36	5.20	-5.16	0.65	
82	5575.00	91.40	359.70	3926.46	1988.34	-11.55	1988.34	3.88	-3.87	0.32	
83	5606.00	91.20	359.90	3925.76	2019.33	-11.66	2019.33	0.91	-0.65	0.65	
84	5636.00	91.40	0.00	3925.08	2049.32	-11.69	2049.32	0.75	0.67	0.33	
85	5667.00	91.80	359.80	3924.21	2080.31	-11.74	2080.31	1.44	1.29	-0.65	
86	5698.00	92.20	359.70	3923.13	2111.29	-11.88	2111.29	1.33	1.29	-0.32	
87	5729.00	92.30	359.60	3921.91	2142.27	-12.07	2142.27	0.46	0.32	-0.32	
88	5760.00	91.10	359.30	3920.99	2173.25	-12.36	2173.25	3.99	-3.87	-0.97	
89	5791.00	90.90	359.20	3920.45	2204.25	-12.77	2204.25	0.72	-0.65	-0.32	
90	5822.00	90.50	359.50	3920.07	2235.24	-13.12	2235.24	1.61	-1.29	0.97	
91	5853.00	90.30	359.90	3919.86	2266.24	-13.28	2266.24	1.44	-0.65	1.29	
92	5884.00	90.10	359.70	3919.75	2297.24	-13.39	2297.24	0.91	-0.65	-0.65	
93	5915.00	90.20	359.60	3919.67	2328.24	-13.58	2328.24	0.46	0.32	-0.32	
94	5946.00	90.50	359.30	3919.48	2359.24	-13.88	2359.24	1.37	0.97	-0.97	
95	5977.00	90.70	359.40	3919.15	2390.23	-14.23	2390.23	0.72	0.65	0.32	
96	6008.00	90.90	359.50	3918.72	2421.23	-14.53	2421.23	0.72	0.65	0.32	
97	6039.00	91.60	359.80	3918.05	2452.22	-14.72	2452.22	2.46	2.26	0.97	
98	6070.00	92.00	359.60	3917.07	2483.20	-14.88	2483.20	1.44	1.29	-0.65	
99	6101.00	91.10	359.80	3916.23	2514.19	-15.04	2514.19	2.97	-2.90	0.65	
100	6131.00	90.80	359.70	3915.74	2544.19	-15.17	2544.19	1.05	-1.00	-0.33	
101	6162.00	90.40	359.80	3915.41	2575.19	-15.31	2575.19	1.33	-1.29	0.32	
102	6193.00	90.40	0.10	3915.19	2606.19	-15.33	2606.19	0.97	0.00	0.97	
103	6224.00	90.80	359.90	3914.87	2637.18	-15.33	2637.18	1.44	1.29	-0.65	
104	6255.00	91.20	359.70	3914.33	2668.18	-15.44	2668.18	1.44	1.29	-0.65	
105	6286.00	91.40	0.00	3913.63	2699.17	-15.52	2699.17	1.16	0.65	0.97	
106	6316.00	90.80	0.50	3913.05	2729.16	-15.39	2729.16	2.60	-2.00	1.67	
107	6347.00	90.80	0.30	3912.62	2760.16	-15.18	2760.16	0.65	0.00	-0.65	

Well Report



Company : Dorado E&P Partners
 Well : Preisser 25-9-6 1H
 Location : Reno County Kansas
 Reference: Grid North

Page: 4
 Date : 9/11/2012
 File : OK 12129

Vertical Section Calculated Along Azimuth 0.00°
KB Elevation = 1733.00ft GR. Elevation = 1721.00ft

	MD ft	Inc deg	Azi deg	TVD ft	North ft	East ft	V'Sect ft	D'Leg %/100	Build %/100	Turn %/100
108	6378.00	91.20	0.40	3912.08	2791.16	-14.99	2791.16	1.33	1.29	0.32
109	6408.00	91.40	0.50	3911.40	2821.15	-14.75	2821.15	0.75	0.67	0.33
110	6439.00	90.40	0.70	3910.91	2852.14	-14.43	2852.14	3.29	-3.23	0.65
111	6470.00	90.10	1.00	3910.77	2883.14	-13.97	2883.14	1.37	-0.97	0.97
112	6501.00	89.10	1.00	3910.99	2914.13	-13.43	2914.13	3.23	-3.23	0.00
113	6532.00	89.10	1.20	3911.48	2945.12	-12.83	2945.12	0.65	0.00	0.65
114	6563.00	89.30	1.00	3911.91	2976.11	-12.24	2976.11	0.91	0.65	-0.65
115	6594.00	89.10	0.80	3912.34	3007.11	-11.75	3007.11	0.91	-0.65	-0.65
116	6625.00	89.10	0.70	3912.83	3038.10	-11.34	3038.10	0.32	0.00	-0.32
117	6656.00	89.10	1.00	3913.32	3069.09	-10.88	3069.09	0.97	0.00	0.97
118	6687.00	89.40	1.30	3913.72	3100.08	-10.26	3100.08	1.37	0.97	0.97
119	6718.00	90.20	1.00	3913.83	3131.08	-9.64	3131.08	2.76	2.58	-0.97
120	6749.00	90.60	1.00	3913.61	3162.07	-9.10	3162.07	1.29	1.29	0.00
121	6780.00	90.90	0.50	3913.21	3193.07	-8.69	3193.07	1.88	0.97	-1.61
122	6811.00	90.90	0.30	3912.72	3224.06	-8.48	3224.06	0.65	0.00	-0.65
123	6842.00	91.30	0.20	3912.13	3255.05	-8.34	3255.05	1.33	1.29	-0.32
124	6873.00	91.50	0.20	3911.37	3286.05	-8.23	3286.05	0.65	0.65	0.00
125	6904.00	91.50	0.40	3910.56	3317.03	-8.07	3317.03	0.64	0.00	0.65
126	6935.00	91.60	0.30	3909.72	3348.02	-7.88	3348.02	0.46	0.32	-0.32
127	6966.00	91.90	0.70	3908.77	3379.01	-7.61	3379.01	1.61	0.97	1.29
128	6997.00	91.20	0.90	3907.93	3409.99	-7.18	3409.99	2.35	-2.26	0.65
129	7028.00	90.90	1.30	3907.37	3440.98	-6.58	3440.98	1.61	-0.97	1.29
130	7058.00	91.20	1.40	3906.82	3470.97	-5.88	3470.97	1.05	1.00	0.33
131	7089.00	91.30	1.30	3906.14	3501.95	-5.15	3501.95	0.46	0.32	-0.32
132	7120.00	91.60	1.60	3905.35	3532.93	-4.36	3532.93	1.37	0.97	0.97
133	7151.00	92.00	1.50	3904.38	3563.90	-3.52	3563.90	1.33	1.29	-0.32
134	7182.00	91.50	1.90	3903.43	3594.88	-2.60	3594.88	2.07	-1.61	1.29
135	7213.00	90.80	1.60	3902.81	3625.86	-1.66	3625.86	2.46	-2.26	-0.97
136	7244.00	91.00	1.90	3902.33	3656.84	-0.71	3656.84	1.16	0.65	0.97
137	7275.00	91.00	2.50	3901.78	3687.81	0.48	3687.81	1.94	0.00	1.94
138	7306.00	91.10	1.90	3901.22	3718.78	1.67	3718.78	1.96	0.32	-1.94
139	7337.00	91.20	1.90	3900.59	3749.76	2.70	3749.76	0.32	0.32	0.00
140	7368.00	90.80	2.00	3900.05	3780.74	3.75	3780.74	1.33	-1.29	0.32
141	7399.00	90.90	2.10	3899.59	3811.71	4.86	3811.71	0.46	0.32	0.32
142	7430.00	90.10	2.10	3899.32	3842.69	6.00	3842.69	2.58	-2.58	0.00
143	7461.00	90.40	1.90	3899.19	3873.67	7.08	3873.67	1.16	0.97	-0.65

Well Report



Company : Dorado E&P Partners
 Well : Preisser 25-9-6 1H
 Location : Reno County Kansas
 Reference: Grid North

Page: 5
 Date : 9/11/2012
 File : OK 12129

Vertical Section Calculated Along Azimuth 0.00°

	MD	Inc	Azi	TVD	North	East	V'Sect	D'Leg	Build	Turn
	ft	deg	deg	ft	ft	ft	ft	%100	%100	%100
144	7492.00	90.60	1.40	3898.92	3904.66	7.97	3904.66	1.74	0.65	-1.61
145	7523.00	90.60	1.40	3898.59	3935.65	8.73	3935.65	0.00	0.00	0.00
146	7554.00	91.00	1.20	3898.16	3966.63	9.43	3966.63	1.44	1.29	-0.65
147	7585.00	90.90	1.00	3897.65	3997.62	10.03	3997.62	0.72	-0.32	-0.65
148	7616.00	90.70	1.30	3897.21	4028.62	10.65	4028.62	1.16	-0.65	0.97
149	7647.00	90.20	1.90	3896.97	4059.60	11.51	4059.60	2.52	-1.61	1.94
150	7678.00	90.60	1.80	3896.75	4090.58	12.51	4090.58	1.33	1.29	-0.32
151	7709.00	89.90	1.70	3896.62	4121.57	13.46	4121.57	2.28	-2.26	-0.32
152	7740.00	89.70	1.40	3896.73	4152.56	14.30	4152.56	1.16	-0.65	-0.97
153	7770.00	88.70	1.50	3897.14	4182.55	15.06	4182.55	3.35	-3.33	0.33
154	7801.00	88.50	1.40	3897.90	4213.53	15.84	4213.53	0.72	-0.65	-0.32
155	7832.00	88.80	1.30	3898.63	4244.51	16.57	4244.51	1.02	0.97	-0.32
156	7863.00	89.10	0.80	3899.20	4275.50	17.14	4275.50	1.88	0.97	-1.61
157	7894.00	88.90	0.40	3899.74	4306.49	17.47	4306.49	1.44	-0.65	-1.29
158	7925.00	88.60	0.10	3900.42	4337.48	17.60	4337.48	1.37	-0.97	-0.97
159	7956.00	88.70	359.70	3901.15	4368.48	17.55	4368.48	1.33	0.32	-1.29
160	7987.00	88.90	0.10	3901.80	4399.47	17.49	4399.47	1.44	0.65	1.29
161	8018.00	89.10	359.90	3902.34	4430.46	17.49	4430.46	0.91	0.65	-0.65
162	8049.00	89.70	0.30	3902.66	4461.46	17.55	4461.46	2.33	1.94	1.29
163	8080.00	89.80	359.80	3902.80	4492.46	17.57	4492.46	1.64	0.32	-1.61
164	8111.00	90.00	0.10	3902.85	4523.46	17.55	4523.46	1.16	0.65	0.97
165	8142.00	90.20	359.40	3902.80	4554.46	17.41	4554.46	2.35	0.65	-2.26
166	8173.00	90.20	359.20	3902.69	4585.46	17.03	4585.46	0.65	0.00	-0.65
167	8204.00	90.40	358.90	3902.53	4616.45	16.52	4616.45	1.16	0.65	-0.97
168	8235.00	90.50	359.00	3902.28	4647.45	15.95	4647.45	0.46	0.32	0.32
169	8266.00	90.70	358.70	3901.96	4678.44	15.33	4678.44	1.16	0.65	-0.97
170	8297.00	90.80	358.80	3901.55	4709.43	14.65	4709.43	0.46	0.32	0.32
EXT	8350.00	90.80	358.80	3900.81	4762.41	13.54	4762.41	0.00	0.00	0.00

Bottom Hole Closure 4762.43ft Along Azimuth 0.16°