



**EVANS
ENERGY
DEVELOPMENT
INC.**

11 Lewis Drive

Paola, KS 66071

**Oil & Gas Well Drilling
Water Wells
Geo-Loop Installation**

Phone: 913-557-9083

Fax: 913-557-9084

WELL LOG

Tailwater, Inc.

Simons Bros. Farms #8-IW

API#15-003-25,592

December 4 - December 6, 2012

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
6	soil & clay	6
3	clay & gravel	9
71	shale	80
31	lime	111
61	shale	172
10	lime	182
5	shale	187
37	lime	224
5	shale	229
21	lime	250
3	shale	253
24	lime	277 base of the Kansas City
170	shale	447
3	lime	450
14	shale	464
6	lime	470 oil show
8	shale	478
10	oil sand	488 green, good bleeding
1	coal	489
11	shale	500
19	silty shale	519
1	coal	520
7	shale	527
6	lime	533
15	shale	548
8	lime	556
33	shale	589
7	lime	596
27	shale	623
6	broken sand	629 brown & green, good bleeding
34	shale	663
1	lime & shells	664
6	oil sand	670 brown, good bleeding
4	shale	674
3	sand	677 black, no oil
35	shale	712
2	broken sand	714 brown & grey, light bleeding

8	shale	722
2	broken sand	724 brown & grey, light bleeding
45	silty shale	769
8	oil sand	777 black, no oil show, oil odor
20	shale	797
14	oil sand	811
49	shale	860 TD

Drilled a 9 7/8" hole to 22.5'

Drilled a 5 5/8" hole to 860'

Set 22.5' of 7" surface casing cemented with 6 sacks of cement.

Set 850' of 2 7/8" threaded and coupled 8 round upset tubing with 3 centralizers, 1 float shoe and 1 clamp.



CONSOLIDATED
Oil Well Services, LLC

PO Box 884, Chanute, KS 66720
620-431-9210 or 800-467-8676

TICKET NUMBER 38954

LOCATION Ottawa

FOREMAN Alan Mader

FIELD TICKET & TREATMENT REPORT

CEMENT

DATE	CUSTOMER #	WELL NAME & NUMBER	SECTION	TOWNSHIP	RANGE	COUNTY
12-6-1d	7806	Simon Bras 8E-W	NW 27	20	20	AN
CUSTOMER <u>Tail water</u>			TRUCK # DRIVER TRUCK # DRIVER			
MAILING ADDRESS <u>6421 Avondale Dr</u>			<u>516</u>	<u>Ala Mad</u>	<u>Safety</u>	<u>Meat</u>
CITY STATE ZIP CODE <u>Oklahoma City OK 73116</u>			<u>368</u>	<u>Al Mad</u>	<u>ABU</u>	
			<u>369</u>	<u>Den Mas</u>	<u>D M</u>	
			<u>510</u>	<u>Set Pul</u>	<u>ST</u>	

JOB TYPE long string HOLE SIZE 5 5/8 HOLE DEPTH 860 CASING SIZE & WEIGHT 2 7/8
 CASING DEPTH 850 DRILL PIPE _____ TUBING _____ OTHER _____
 SLURRY WEIGHT _____ SLURRY VOL _____ WATER gal/sk _____ CEMENT LEFT in CASING yes
 DISPLACEMENT 5 DISPLACEMENT PSI 800 MIX PSI 200 RATE 46pm

REMARKS: Held meetings. Established rate. Mixed & pumped 100# gel followed by 113 sk 50/50 cement plus 2 7/8 gel. Circulated cement. Flushed pump. Pumped plug to casing TD. Well held 800 PSI for 30 min. M.I.T. Set float. Closed valve.

Evans Travis

Alan Mader

ACCOUNT CODE	QUANTITY or UNITS	DESCRIPTION of SERVICES or PRODUCT	UNIT PRICE	TOTAL
5401	1	PUMP CHARGE	368	1030.00
5406	25	MILEAGE	368	100.00
5402	850	casing footage	368	-
5407	1/2 mtn	ton miles	510	175.00
5502C	1 1/2	8D vac	368	135.00
1124	113	50/50 cement		1237.35
1118B	290	gel		60.90
h1402	1	2 1/2 plug		28.00
				SALES TAX
				ESTIMATED
				TOTAL

Completed!

SALES TAX
ESTIMATED
TOTAL 2869.69

Revin 3737

AUTHORIZATION [Signature]

TITLE _____

DATE _____

I acknowledge that the payment terms, unless specifically amended in writing on the front of the form or in the customer's account records, at our office, and conditions of service on the back of this form are in effect for services identified on this form

255191