

Skyy Drilling, L.L.C.
Park Place – Becker Building
11551 Ash Street, Suite # 205
Leawood, Kansas 66211
Office (913) 499-8373
Fax (913) 766-1310

December 5, 2012

Company: Haas Petroleum, LLC
11551 Ash Street, # 205
Leawood, Kansas 66211

Lease: Massey – Well # 4 I HP
County: Woodson
Spot: SE NE SW SE Sec 35, Twp 23, R 14 E
API: 15-207-28379-00-00
TD: 1720'

Total Footage 1720'
Total Rig Time 16 Hours
40' of 8 5/8 Casing
25 Sacks Cement
Total Dozer Work 6 Hours



ENTERED

TICKET NUMBER 38287
LOCATION Eureka
FOREMAN Steve Mead

FIELD TICKET & TREATMENT REPORT

CEMENT AP# 15-207-28313

DATE	CUSTOMER #	WELL NAME & NUMBER	SECTION	TOWNSHIP	RANGE	COUNTY
12-4-12	3451	Massay 41-HP	25	23S	14E	Woodson
CUSTOMER						
Haas Petroleum LLC						
MAILING ADDRESS						
11551 Ash ST. Ste 305						
CITY	STATE	ZIP CODE				
Lawton	OK					

22.4 bbls	27.4 bbls	800'	1300'
JOB TYPE <u>Long String O</u>	HOLE SIZE <u>6 3/4</u>	HOLE DEPTH <u>1720'</u>	CASING SIZE & WEIGHT <u>4 1/2 106*</u>
CASING DEPTH <u>1722'</u>	DRILL PIPE	TUBING	OTHER
SLURRY WEIGHT	SLURRY VOL	WATER gal/sk	CEMENT LEFT In CASING
DISPLACEMENT <u>27.4 bbls</u>	DISPLACEMENT PSI <u>800*</u>	<u>Bump</u> MIX PSI <u>plug 1300*</u>	RATE
REMARKS: <u>Safety Meeting: Rig up to 4 1/2 casing. Break circulation with Freshwater. 1 bump 6 bbls ahead. Mix 155 sks 60/40 poz mix cement w/ 8% Gel & 1# phenased perisk. Tail in with 3 sks Thick set cement. Washout pump & lines. Shut down Release plug. Displace with 27.4 bbls Fresh water. Final pumping Pressure 800#. Bump plug to 1300#. Wait 2 min Release pressure plug held. Good cement Return to surface 8 bbls slurry to pit.</u>			
<u>Job Complete Rig down</u>			

Thank you

[illegible]

Bayin 3737

AUTHORIZATION Ben Hamer TITLE Toolmaster DATE _____

I acknowledge that the payment terms, unless specifically amended in writing on the front of the form or in the customer's account records, at our office, and conditions of service on the back of this form are in effect for services identified on this form.