

Confidentiality Requested:

Yes No

Kansas Corporation Commission Oil & Gas Conservation Division

1113556

Form ACO-1 August 2013 Form must be Typed Form must be Signed All blanks must be Filled

WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

OPERATOR: License #	API No. 15					
Name:	Spot Description:					
Address 1:						
Address 2:	Feet from North / South Line of Section					
City: State: Zip:+	Feet from East / West Line of Section					
Contact Person:	Footages Calculated from Nearest Outside Section Corner:					
Phone: ()	□NE □NW □SE □SW					
CONTRACTOR: License #	GPS Location: Lat:, Long:					
Name:	(e.g. xx.xxxxxx) (e.gxxx.xxxxxx)					
Wellsite Geologist:	Datum: NAD27 NAD83 WGS84					
Purchaser:	County:					
Designate Type of Completion:	Lease Name: Well #:					
New Well Re-Entry Workover	Field Name:					
□ Oil □ WSW □ SIOW □ Gas □ D&A □ ENHR □ SIGW □ OG □ GSW □ Temp. Abd. □ CM (Coal Bed Methane) □ Cathodic □ Other (Core, Expl., etc.): □ If Workover/Re-entry: Old Well Info as follows: Operator: □ Well Name: □ Well Name:	Producing Formation: Elevation: Ground: Kelly Bushing: Feet Total Vertical Depth: Plug Back Total Depth: Feet Multiple Stage Cementing Collar Used? Yes No If yes, show depth set: Feet If Alternate II completion, cement circulated from: sx cmt.					
Original Comp. Date: Original Total Depth: Deepening Re-perf. Conv. to ENHR Conv. to SWD Plug Back Conv. to GSW Conv. to Producer	Drilling Fluid Management Plan (Data must be collected from the Reserve Pit)					
Commingled Permit #:	Chloride content: ppm Fluid volume: bbls Dewatering method used: Location of fluid disposal if hauled offsite: Operator Name:					
GSW Permit #:	Lease Name: License #:					
Spud Date or Date Reached TD Completion Date or Recompletion Date	QuarterSec. TwpS. R East West County: Permit #:					

AFFIDAVIT

I am the affiant and I hereby certify that all requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Submitted Electronically

KCC Office Use ONLY						
Confidentiality Requested						
Date:						
Confidential Release Date:						
Wireline Log Received						
Geologist Report Received						
UIC Distribution						
ALT 🔲 I 🔲 II 📗 III Approved by: Date:						

Page Two



Operator Name:				_ Lease l	Name: _			Well #:		
Sec Twp	S. R	East \	West	County	:					
INSTRUCTIONS: Shopen and closed, flow and flow rates if gas to	ring and shut-in pres o surface test, along	sures, whether s with final chart(shut-in pre s). Attach	ssure reac extra shee	hed stati t if more	c level, hydrosta space is neede	tic pressures, bot d.	tom hole temp	erature, flui	d recovery,
Final Radioactivity Lo- files must be submitte						ogs must be ema	iled to kcc-well-lo	gs@kcc.ks.go	v. Digital el	ectronic log
Drill Stem Tests Taker (Attach Additional S		Yes	☐ No		_		on (Top), Depth ar			mple
Samples Sent to Geo	logical Survey	Yes	No		Nam	е		Тор	Da	tum
Cores Taken Electric Log Run	☐ No ☐ No									
List All E. Logs Run:										
			CASING		☐ Ne					
		1				ermediate, product		T	_	
Purpose of String	Size Hole Drilled	Size Cas Set (In O		Weig Lbs./		Setting Depth	Type of Cement	# Sacks Used		d Percent itives
		AD	DITIONAL	CEMENTIN	NG / SQL	JEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Ce	ement	# Sacks	Used		Type and P	ercent Additives		
Perforate Protect Casing	100 20111111									
Plug Back TD Plug Off Zone										
1 lug 0 li 20110										
Did you perform a hydrau	ulic fracturing treatment	on this well?				Yes	No (If No, ski	p questions 2 ar	nd 3)	
Does the volume of the to								p question 3)		
Was the hydraulic fractur	ing treatment information	on submitted to the	e chemical c	disclosure re	gistry?	Yes	No (If No, fill	out Page Three	of the ACO-1)
Shots Per Foot		ION RECORD - I					cture, Shot, Cement		d	Depth
						,		,		
TUBING RECORD:	Size:	Set At:		Packer A	t:	Liner Run:				
							Yes No			
Date of First, Resumed	Production, SWD or Ef		ducing Meth Flowing	od:	g 🗌	Gas Lift (Other (Explain)			
Estimated Production Per 24 Hours	Oil	Bbls.	Gas	Mcf	Wate	er B	bls. 0	as-Oil Ratio		Gravity
DISPOSITIO	ON OF GAS:		N/	1ETHOD OF	COMPLE	TION:		PRODUCTION)N INTER\/^	1.
Vented Sold		Open I	_	Perf.	Dually	Comp. Cor	mmingled	THODOCTIC	ZIN IIN I ERVA	L.
	bmit ACO-18.)	Other	(Specific)		(Submit)		mit ACO-4)			

Form	ACO1 - Well Completion
Operator	O'Brien Energy Resources Corp.
Well Name	Utz 2-17
Doc ID	1113556

Tops

Name	Тор	Datum
Heebner	4472	-1775
Toronto	4499	-1802
Lansing	4619	-1922
Marmaton	5278	-2581
Cherokee	5454	-2757
Atoka	5718	-3021
Morrow	5768	-3071
Mississippi Chester	5898	-3201
Ste. Genevieve	6124	-3427

Conservation Division Finney State Office Building 130 S. Market, Rm. 2078 Wichita, KS 67202-3802



Phone: 316-337-6200 Fax: 316-337-6211 http://kcc.ks.gov/

Sam Brownback, Governor

Mark Sievers, Chairman Thomas E. Wright, Commissioner Shari Feist Albrecht, Commissioner

February 05, 2013

Joseph Forma O'Brien Energy Resources Corp. 18 CONGRESS ST, STE 207 PORTSMOUTH, NH 03801-4091

Re: ACO1 API 15-119-21327-00-00 Utz 2-17 NE/4 Sec.17-33S-29W Meade County, Kansas

Dear Production Department:

We are herewith requesting that the Well Completion Form ACO-1 and attached information for the subject well be held confidential for a period of two years.

Should you have any questions or need additional information regarding subject well, please contact our office.

Respectfully,

Joseph Forma Vice President O'Brien Energy Resources Corp.

O'Brien Energy Resources, Inc. Utz No. 2-17, Angell South Field Section 17, T33S, R29W

Meade County, Kansas December, 2012

Well Summary

The O'Brien Energy Resources, Corporation, Utz No. 2-17 was drilled to a total depth of 6210' in the Mississippi Ste. Genevieve Formation. Sever lost circulation problems occurred starting in the lower Lansing at 5060'(120 bbls) and 5114'(100 bbls) and necessitated running a high LCM mud system and at times drilling with slow or partial returns and with partial pump pressure. Total lost circulation occurred at 6110' and was called TD. 38 stands were tripped out and over 1000 barrels of 26+ Lbs/bbl LCM mud was mixed and lost down hole without gaining any returns. The decision was made to run 4 ½" production casing to complete the Morrow "B" Sandstone. Casing became stuck at 5100' and at the same place lost circulation was first noted. Two attempts were made to free the casing by blowing Nitrogen to no avail. Attempts will be made to run a liner through the 4 ½" for completion.

The Utz No. 2-17 was drill approximately 1400' south/southwest of the Rickers Ranch No. 7-17. Formation tops ran consistently high relative to this offset. The Heebner, Toronto and Lansing ran 9' to 11' high. The Marmaton, Cherokee and Atoka ran 11', 14' and 11' high respectively. The Morrow and Morrow "B" Sandstone came in 12' high. The Mississippi Chester 12' high and the Ste. Genevieve, 20' high.

Numerous hydrocarbon shows were documented. The Morrow "B" Sandstone (5802'-5836') consists of A Sandstone in up to 20% of the samples. The upper "B" Sandstone interval(app. 5802'-5820'): White, translucent, speckled green and salt and pepper, hard to friable, fine lower to fine upper, well sorted subround to round grains, siliceous cement, calcareous, clean to argillaceous in part, tight to good intergranular porosity, light mottled blue hydrocarbon fluorescence, occasionally light yellow fluorescence, slow streaming to bleeding cut, no stain, gas bubbles when crushed, show dissipates when dried. 70 to 90 Units of gas was documented on the hotwire.

The lower section of the "B" Sandstone(app. 5820'-5836') contained an oil show consistent with the Rickers Ranch North 7-17: Light brown, salt and pepper, speckled green, very light brown to clear and translucent, very friable to hard in part, fine lower, well sorted subround to round grains, siliceous cement, calcareous, clean, glauconitic in part, occasionally excellent intergranular porosity, trace course vuggy porosity, bright light yellow to blue green hydrocarbon fluorescence(most the Sandstone) and pale mottled blue fluorescence, excellent fast streaming cut, light brown oil stain and live oil and gas bubbles when crushed, good oil odor. A gas increase of 110 Units was noted.

A very upper Morrow Sandstone was documented from 5784' to 5788' and contained a similar fine grained Sandstone as documented as in the "B" and contained a light yellow hydrocarbon fluorescence in 1% of the samples and with a good streaming cut and trace light oil stain. No gas increase was noted.

A very lower Morrow Sandstone was documented from 5882' to 5890' and with an associated 50 Unit gas increase and associated oil show. Samples were somewhat confusing do to slower returns and might actually be sands documented in 'B".

Additional minor shows occurred in the lower Lansing, Marmaton, Cherokee, Atoka and lower Chester(attached mudlog).

The Upper Chester consists of a Limestone: light mottled orange to brown, biomicrite, microcrystalline, subchalky, microsucrosic in part, brittle, clean, very fossiliferous with good interpartical porosity, trace intercrystalline porosity, mottled yellow blue hydrocarbon fluorescence in 15% of the samples, fair to good streaming cut, light oil stain, no visible live oil. No gas increase was documented. The abundance of LCM in the mud system greatly reduces gas readings.

Respectfully Submitted,

Peter Debenham

WELL DATA

Operator: O'Brien Energy Resources, Inc., John Forma – Portsmouth, NH

Geologist: Paul Wiemann – Denver, CO

Prospect Geologist: Ed Schuett, David Ward, Denver

Well: Utz No. 2-17, Angell South Field

API: 15-119-21327

Field: Angell South Field

Location: 1980' FNL & 1980' FEL, Section 17, T33S, R29W, Meade County, Kansas –

15 miles SE of Meade.

Elevation: Ground Level 2685', Kelly Bushing 2697'

Contractor: Duke Drilling Rig No. 6, Type: Double jacknife, triple stand, Toolpusher Rick

Schollenbarger, Drillers: Juan Garcia, DannyWhite, Brett

Company Man: Roger Pearson – Liberal, Kansas

Spud Date: 12/1/2012

Total Depth: 12/8/2012, Driller 6210', Logger – no logs, Mississippi Ste. Genevieve

Casing Program: 35 joints of 8 5/8", J55, 24Lbs/ft, set at 1500'.

Mud Program: Winter Mud, Engineer Theran Hegwood, Chemical gel/LCM. Displaced at

2590'.

Wellsite Consultant: Peter Debenham with mudlogging trailer, Call depth 4000', Box 350, Drake,

CO 80515, 720/220-4860.

Samples: 30' to 4700', 20' to TD. Zones of interest saved.

Electric Logs: Lost circulation – no logs run.

Status: Waiting on slim hole tools and liner to attempt completion.

WELL CHRONOLOGY

6 AM DATE DEPTH FOOTAGE RIG ACTIVITY

11/29 Finish laying down drill pipe and collars on the Singley West 5-29. Rig up casing crew and run and cement $4\frac{1}{2}$ " production casing. Plug down 10:15 am. Rig released 2:15 pm.

11/30 Move to location and rig up rotary tools. Mix spud mud and drill rat hole and mouse hole.

12/1 1200' 1200' Spud in 12 1/4" surface hole to 1200'. Repair chain.

12/2 1667' 479' To 1500' and circulate and trip out. Rig up casing crew and run and cement 8 5/8" to 1500'. Nipple up. Go in hole and fix rotoary table lock. Drill cement and plug and new hole to 1679'.

12/3 2960' 1281' Wait on mechanic and fix low jack. Repair and change out right chain. Survey $(1 - \frac{1}{2} \text{ deg.})$ and service rig. Clean suction.

12/4 4400' 1440'

12/5 5125' 725' To 5021' and run survey(3/4 deg.). Circulate and condition mud and wiper trip and clean suction. Drill to 5060' and lost circulation(120 bbls). To 5114' and lost circulation(100 bbls). Trip out 5 stands and mix mud and LCM and circulate. Trip in and drill to 5125' with slow returns and with 8 Lbs/bbl LCM mud.

12/6 6110' 995'

12/7 6210' 110' To 6210' and lost circulation. Mix mud and LCM – no returns. Trip out 38 stands and mix mud and LCM to 26 bbls/bbl with no returns. Pump 200 bbls through bit and mix mud – no returns. Pumped and lost approxamitley 1000 bbls mud. Trip in and wash down 4 stands and mix mud – no returns. Trip out laying down drill pipe.

12/8 TD Lay down drill pipe and rig up casing crew and run casing. Work stuck casing at 5100'. Wait on nitrogen and blow down same – no go. Rig down nitrogen truck and wait on orders. Wait on nitrogen and blow down. No go, still stuck. Release rig. Will attempt to run in with slim hole bit and clean hole and run and cement liner through 4 1/2" casing with a pulling unit.

BIT RECORD

<u>NO.</u>	MAKE	TYPE	<u>SIZE</u>	<u>OUT</u>	FOOTAGE	<u>HOURS</u>
1 3	HTC Milo	RR PDC	12 ¹ / ₄ " 7 7/8"	1500' 6210'	1500' 4710'	20 3/4 84
				Total Rotatin Avera	•	104 3/4 59.28 Ft/hr

DEVIATION RECORD - degree

612' $\frac{1}{4}$, 1500' 1 $\frac{3}{4}$, 2024' 1, 2500' $\frac{1}{2}$, 5021' $\frac{3}{4}$

MUD PROPERTIES

DATE	DEPTH	$\overline{\mathbf{WT}}$	<u>VIS</u>	<u>PV</u>	<u>YP</u>	<u>pH</u>	$\underline{\mathbf{WL}}$	<u>CL</u>	LCM-LBS/BBL
11/30	Spud mud								
12/2	1550'	8.3	27	0	0	8.0	nc	2000	0
12/3	2150'	8.3	27	3	1	8.0	nc	2200	0
12/4	3800'	9.1	38	10	6	9.0	15.0	4000	8
12/5	5000'	9.1	45	13	7	9.5	8.4	3000	8
12/7	6210'	8.6	38	10	6	9.5	8.8	2100	26

SAMPLE FORMATION TOPS- KB Elev. 2697'

			*Rickers Rai	nch North No. 7-17
FORMATION	DEPTH	DATUM	DATUM	POSITION
Casing	1500'			
Heebner	4472'	-1775'	-1783'	+9'
Toronto	4499'	-1802'	-1813'	+11'
Lansing	4619'	-1922'	-1933'	+11'
Marmaton	5278'	-2581'	-2595'	+14'
Cherokee	5454'	-2757'	-2779'	+22'
Atoka	5718'	-3021'	-3035'	+14'
Morrow	5768'	-3071'	-3083'	+12'
Morrow "B" SS	5802'	-3105'	-3117'	+12'
Base Morrow "B" SS	5836'	-3139'	-3147'	+8'
Mississippi Chester	5898'	-3201'	-3213'	+12'
Ste. Genevieve	6124'	-3427'	-3447'	+20'
TD	6210'	-3513		

^{*}O'Brien Energy Resources, Rickers Ranch North No. 7-17, 660'FNL & 1650'FEL, Sec. 17, app. 1400' to the N/NE, K.B. Elev. 2697'.

JASIC"

Customer Representative

Cement Report NERGY SERVICE Liberal, Kansas Lease No. Date Customer Service Receipt Well # Lease State Depth County Casing Morde Legal Description Job Type **Perforating Data Cement Data Pipe Data** Lead 400 SK **Tubing Size** Shots/Ft Casing size A-Con From Depth Depth To Volume From Volume Tail in 150 sk From Max Press Max Press To Class C Annulus Vol. From Well Connection To Packer Depth Plug Depth Tubing Pressure Casing Service Log Bbls. Pumbed Rate Time Pressure <u> 200</u> 100 400 Service Units **Driver Names**

Taylor Printing, Inc.

Ut Driel Ub#2

1/4/B H5545

100 GREI	Plains Ready Mi "ALL TYPES CONCRETE WORK ENSBORO PLAINS, KANSAS 67869		E: 620-56	3-938
ORDER NO	D DATE	12-1-	3-12	
SOLD TO	MODEL PROISON			2-vi
ADDRESS DELIVER T	5> E onto location	MIE-	7 47	nai
CASH		Time OUT	ing the law.	
QUANTITY	DESCRIPTION	PRICE	AMOL	INT
3	CUBIC YARDS CONCRETE	80×	241	50
See 1	% CALCIUM CHLORIDE			
c=12.47	WATER REDUCER	74. 44.		10
	OZ. AIR ENTRAINING		us Taka	1
-	HOT WATER	Company of the Compan		. 0.3
E Paristic	FIBER			-
	ROCK	4		
10	MILEAGE @PER CUBIC YD MILE HAUL			
	HOURS WAITING TIME		41	.00
	GALLONS WATER ADDED ON JOB		Actions.	
	SERVICE CHARGE - FOR UNDER 3 YARDS		. Twi	
			281	70
Unloading to This concre Any water a	IMPORTANT sible for any damage done by truck after leaving street NO CREDIT for returned concrete. Ime allowed (1) hour. RECEIPT AND RELEASE Inte designed in accordance to A.C.I. Standards, Idded to this design will be at purchaser's risk. THE ABOVE MATERIAL IN GOOD CONDITION.	MECO 13% TAX	20	55
		TOTAL	200	h

Cont to plug RHE



Lease County Co		Libera	i, Kansas						C	ement Report
Casing Depth County Madd State Casing Depth De	Customer	- OB	CYPBA		Lease No.			Da	ite 12-	20-17
Casing Depth Pipe Data Permation Legal Description Pipe Data Perforating Data Cement Data Casing size Dubing Size 76 Shots/Ft Lead (00 SK Depth Volume Volume 25.3 Min From To Tall in 200 SK Annulus Vol. From To Tall in 200 SK Pressure Pressure Bbls. Pumbed Rate Service Log Depth Pressure Pressure Bbls. Pumbed Rate Service Log Depth Size Pressure Bbls. Pumbed Rate Service Log Depth Pressure Pressure Bbls. Pumbed Rate Service Log Depth Size Pressure Bbls. Pumbed Rate Service Log Depth Prom To Tall in 200 SK AAA Depth Pressure Service Log Depth Pressure Bbls. Pumbed Rate Service Log Depth Size Depth Prom To Tall in 200 SK AAA Depth Depth Service Log Depth Pressure Bbls. Pumbed Rate Service Log Depth Depth Depth Depth Pressure Service Log Depth Depth Depth Depth Depth Depth Depth Depth Prom To Tall in 200 SK AAA Depth D	Lease (10	-00/		Well # 2-1	*2-17 Service Receipt				
Service Units 1980 Service Units Servi	Casing		Depth		County	load	e	State K	3	
Pipe Data	Job Type L	47-4	3 like	Formation			Legal Descripti	on		
Depth Dept			Pipe D	ata	7		Perforatin	g Data		Cement Data
Depth Depth Cally From To From To From To Tall in 200 st From To Tall in 200 st From To To Tall in 200 st From To To To To To To To	Casing size			Tubing Size	5"		Shots	/Ft		Lead 100 SK
Volume	Depth			Depth (ally		From		To		A.San
Time Pressure Pressure Bbls. Pumbed Rate Service Log 1/30 1/45 2/100	Volume			Volume 35	3 6510	From		То		
Time Pressure Pressure Bbls. Pumbed Rate Service Log 1/30 1/45 2/100	i .			Max Press	300#	From		То		Tail in 300 st
Time Pressure Pressure Bbls. Pumbed Rate Service Log 1/30 1/45 2/100	Well Connec	tion		Annulus Vol.		From		To		AAZ
130 Pressure Pressure Bbls. Pumbed Rate Service Log 130 Out Or - Sirle Assessment 145 Soot And -	Plug Depth			Packer Depth		From		То		r/ / ()
Soot tark-No up 3100 3200 3	Time			Bbis. Pumbed	Rate			Se	rvice Log	
\$00	1:30					01	oc -s	He C	isses	mont
200 5 3 hump 642 420 smer 3:02 200 5 3 hump 643 420 smer 3:07 200 5 3 hump 5 451 HD spacer 3:10 200 35 3 hump 5 451 HD spacer 3:10 200 35 3 hump 5 451 HD spacer 3:10 200 54 3 sunted to tail 200 sh HH2 e 14.8# 1.07 A35k 3:40 0 0 4 doop due disp csg 4:00 500 36 i slow rate 4:00 12 200 35 0 land plus floot hold Service Units 1990 27462 (4389-4575)						500	f th	Joks-	1	UD.
200 5 3 hump 642 420 smer 3:02 200 5 3 hump 643 420 smer 3:07 200 5 3 hump 5 451 HD spacer 3:10 200 35 3 hump 5 451 HD spacer 3:10 200 35 3 hump 5 451 HD spacer 3:10 200 54 3 sunted to tail 200 sh HH2 e 14.8# 1.07 A35k 3:40 0 0 4 doop due disp csg 4:00 500 36 i slow rate 4:00 12 200 35 0 land plus floot hold Service Units 1990 27462 (4389-4575)	200					Sal	tes in	cetil	2 %	rsa
3:07 200 5 3 pump 12 161 mud Hush 3:07 200 5 3 pump 5 161 HD spacer 3:10 200 35 3 mix pump 100 st A Sen Ute e (2,7 # - 1,97 A3/sk 3:20 200 54 3 switch to tail 200 sto AH2 e 14.8# - 1.57 A3/sk 3:40 0 0 4 doop due disp csg 4:00 500 36 1 slow talk 4:00 12 1200 35 0 land plus flood hold	2260					DNOS	ssure	dest	U 30	00#
3:07 200 5 3 pump 12 161 mud Hush 3:07 200 5 3 pump 5 161 HD spacer 3:10 200 35 3 mix pump 100 st A Sen Ute e (2,7 # - 1,97 A3/sk 3:20 200 54 3 switch to tail 200 sto AH2 e 14.8# - 1.57 A3/sk 3:40 0 0 4 doop due disp csg 4:00 500 36 1 slow talk 4:00 12 1200 35 0 land plus flood hold	3:00		200	5		Din	NO 56	61 ju	208	nur
3107 200 5 3 Dunp 5 161 HD spacer 3100 200 35 3 Mix + Dunp 100 st A Sen Ute (2.7 # - 1,97 A3/st 3120 200 54 3 switch to tail 200 st HAZ e (4.8 # - 1,51 A3/st 2150 0 0 4 drop due disp (sg. 4100 500 36 1 slow Bate 4100 12 1200 35 0 land plus floort hold Service Units 19902 27412 (4358-4575)	3:02		200	12	3	Duras	6121	100	nuo	Stush
3120 200 54 3 switch to tail 200 sto AA2 e 14.8# 1.51 A35k 3145 0 0 4 doop due disp esq. 4100 12 1200 35 0 land plus floot hold Service Units 19902 27462 143594578			200	5	3 -	DUN	05	10	140	Spacer
3120 200 54 3 swatch to tail 200 sb HAZ e (4.8# - 1.07 H 75k 3140 0 0 4 dop dus disp csg: 4100 500 36 i slow rete 4100 12 1200 35 0 land plus float hold Service Units 19902 27462 14358	3110		200	35	3	MIX	+ PL	MA	100	sk A. Serlite
3145 0 0 4 dop due disp csg 4100 500 36 i slow telle 4014 hold 4100 12 1200 35 0 land plus floor hold Service Units 19702 27462 14357-14578						0	(2.7 #	-10	171	13/sk
3150 0 0 4 dop due disp csg: 4100 500 36 i slow tell 4100 12 1200 35 0 land plus floor hold Service Units 19902 27462 14359-14578	3120		200	54	3	SUR		tail	<i>20</i> 0	sb AA2 e
310 0 0 4 dop due disp csg 400 12 1200 35 0 land plus floort hold Service Units 19702 27462 14359-14578					N.	14		1.51	143	sk
400 500 36 Slow Felte 400 12 1200 35 O land plus float hold Service Units 19702 27462 (4359-145)8	3145					LUAS	in the	0.8		
4100 12 1200 35 0 and plus floor hold Service Units 19902 27462 14359-14578	3:50		0	. 0	4	do	2 du	9,6	OSIK	CSG:
4100 12 1200 35 0 and plus floor hold Service Units 19902 27462 14359-14578	460		500	36	ĺ	حام		Elle	0	0
Service Units 19702 27462 14359-14578	4,00	10	(200	_35	Ö	lan	d plu	e fl	oat_	hold
				© vo			_ ' ر	<u>) </u>		•
				-						
							 -			
										
								_		
										
	Service Units	1990	32	27462	14359-1	4578				
	Driver Names		(Que	I Gydia	Slre	ver				

Customer Representative

Station Manager

Taylor Printing, Inc.