STERLING DRILLING CO.

BOX 129

STERLING, KANSAS 67579

Kansas

OWNER: F. G. Holl

ROTARY DRILLING CONTRACTOR: Sterling Drilling Company

COMMENCED: January 10, 1983 COMPLETED: January 16, 1983

TOTAL DEPTH: 4450'

L	0	G

0 - 90 Surface Soil and Sand

90 - 265 Shale

265 - 700 Shale and Sand

700 - 1117 Shale and Lime

1117 - 1133 Anhydrite

1133 - 4450 Lime and Shale

CASING RECORD

Ran 6 joints 8 5/8", 24# new casing. 249.14' pipe set at 276' K.B. Cemented with 210 sacks 60/40 Pozmix with 3% cc. Plug down at 11:30 AM, 1-10-83, by Howco.

* 7

Ran 131 joints 4 1/2", 10.5# used casing and 2 joints 4 1/2", 10.5# new casing. 4426.13' pipe set at 4435' K.B. Cemented with 100 sacks Lite and 125 sacks 50/50 Pozmix, plus regular additives. Plugged rat hole and water well (used Lite cement). Plug down at 8:30 AM, 1-16-83, by Howco.

Deviation Surveys: 1/2° at 2174° 1° at 4355°