

**LITHOLOGY STRIP LOG**  
**WellSight Systems**  
 Scale 1:240 (5" = 100') Imperial  
 Measured Depth Log

Well Name: **Beougher 8B #1**  
 Location: **80° N & 60° W of E2-W2-NW/4 Section 8 T12S-R29W**  
 License Number: **API: 15-063-22084-00-00** Region: **Gove Co, KS**  
 Spud Date: **Feb. 9, 2013** Drilling Completed: **Feb 19, 2013**  
 Surface Coordinates: **1400' FNL & 930' FEL Section 8 T12S-R29W**

**Bottom Hole Coordinates:**  
 Ground Elevation (ft): **2821'** K.B. Elevation (ft): **2826'**  
 Logged Interval (ft): **NTD** To: **TD** Total Depth (ft): **4620**  
 Type of Drilling Fluid: **Chemical**

**OPERATOR**

Company: **Ritchie Exploration, Inc.**  
 Address: **8100 E 22ND ST N #700**  
**Wichita, KS 67278-3188**


**GEOLOGIST**

Name: **Roger L. Fisher**  
 Company: **Consulting Geologist**  
 Address: **1928 N Garland**  
**Wichita Kansas, 67203**

**COMMENTS**

WW Drilling Rig #6  
 Surface Casing: 256' of 8" 7/8"  
 Mudco Mud Co  
 OH Logs: Nabors Wireline; DILL, CDL/CNL, Micro  
 Casing was run to produce this well.

ROCK TYPES			
	Anhy		Congl
	Bent		Shy dol
	Brec		Dol
	Cht		Gyp
	Cyl		Sdy lmst
	Coal		Lmst
			Mrlst
			Siltst
			Ss
	Black sh		Gry sh
	Shale		Shylst
	Stysh		



Log Tops	
Anh	+ 520
Stot	- 690
Hb Sh	-1032
Lans	-1094
Stark	-1313
BKC	-1362
Mn	-1385
Paw	-1488
Myric	-1538
FT S	-1566
Ck Sh	-1595
E Miss	-1670
Miss	-1714

DST #	Interval	Rec	Flow	Notes
DST #1	3978-4007	30-45-60	IF BOB 10 Min	No Blowback
DST #2	4042-4073	Rec: 20' SLOSM 1% Oil 99% Mud	IF BOB 10 Min	Weak Blow died in 20 Min.
DST #3	4078-4141	30-30-30-30	IF BOB 11 Min	No Blowback
DST #4	4136-95	30-45-45-60	IF 1 1/2"	FF BT to 11 1/2"
DST #5	4226-4292	30-45-45-60	IF 1 1/2"	FF No Blow
DST #6	4292-4375	30-45-45-60	IF BOB 11 Min	FF BOB 6 Min
DST #7	4390-4426	30-45-45-60	IF 1 1/2"	FF No Blowback
DST #8	4438-4508	30-45-45-60	Blow died in 22 Min.	

Printed by WellSight Log Viewer from WellSight Systems 1-800-447-1534 www.WellSight.com