

# QUALITY OILWELL CEMENTING, INC.

Federal Tax I.D.# 20-2886107

Phone 785-483-2025  
Cell 785-324-1041

Home Office P.O. Box 32 Russell, KS 67665

No. 6111

Date	12-7-12	Sec.	25	Twp.	15	Range	19	County	Ellis	State	KS	On Location		Finish	2:45 AM
Lease								Location		Hay's Mack - 15, 4W, 1/8 S w/into					
Bieker								Well No.		1-25					
Contractor								Owner		To Quality Oilwell Cementing, Inc. You are hereby requested to rent cementing equipment and furnish cementer and helper to assist owner or contractor to do work as listed.					
Discovery #4								Charge To		Acon oil					
Type Job								Street							
Production								City		State					
Hole Size								Depth		The above was done to satisfaction and supervision of owner agent or contractor.					
7 7/8"								T.D.		3700'					
Csg.								Depth		3696.49'					
5 1/2" 14# New								Cement Left in Csg.		42.92'					
Tbg. Size								Shoe Joint		42.92'					
Tool								Displace		89 BLS					
Cement Amount Ordered								Common		200					
200 Com 10% Salt								Poz. Mix							
Meas Line								Gel.							
500 gal Mud Clear 48								Calcium							
EQUIPMENT								Hulls							
Pumptrk								Salt		18					
16 No. Cementer Helper								Flowseal							
1 No. Driver								Kol-Seal							
1 No. Driver								Mud CLR 48		500 gal					
1 No. Driver								CFL-117 or CD110 CAF 38							
JOB SERVICES & REMARKS								Sand							
Remarks:								Handling		2/8					
Rat Hole								Mileage							
30 sx								FLOAT EQUIPMENT							
Mouse Hole								Guide Shoe							
15 sx								Centralizer		5 Reg					
Centralizers								Baskets		1					
2, 6, 8, 11, 13								AFU Inserts		1					
Baskets								Float Shoe		1					
5								Latch Down		1					
D/V or Port Collar								Pumptrk Charge		prod long string					
pipe on bottom, break								Mileage		14					
Circulation, pump 500 gal mud clear 48								Tax							
pump 5 Bis water spacer plug								Discount							
Rathole w/ 30sx, plug mousehole								Total Charge							
w/ 15sx, Hook to 5 1/2" casing +															
mix 1 1/2 sx Common 10% Salt.															
Shut down, wash pump + lines,															
Released plug + Displaced with 89															
Bis of water. Released + held.															
Lift pressure 700 #															
Land plug to 1300 #															
Signature															
Garry W. Piesker															