KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

1148414

Form ACO-1
June 2009
Form Must Be Typed
Form must be Signed
All blanks must be Filled

WELL COMPLETION FORM
WELL HISTORY - DESCRIPTION OF WELL & LEASE

OPERATOR: License # 30717
Name: Downing-Nelson Oil Co Inc
Address 1: PO BOX 1019
Address 2:
City: HAYS State: KS Zip: 67601 + __ __ __ __
Contact Person: Ron Nelson
Phone: (785) 621-2610
CONTRACTOR: License # 31548
Name: Discovery Drilling
Wellsite Geologist: Marc Downing
Purchaser: Coffeyville Resources

Designate Type of Completion:

- [x] New Well
- [ ] Re-Entry
- [ ] Workover

- [x] Oil
- [ ] WSW
- [ ] SWD
- [ ] SIOW
- [ ] Gas
- [ ] D&A
- [ ] ENHR
- [ ] SIGW
- [ ] OG
- [ ] GSW
- [ ] Temp. Abd.
- [ ] CM *(Coal Bed Methane)*
- [ ] Cathodic
- [ ] Other *(Core, Expl., etc.)*:

If Workover/Re-entry: Old Well Info as follows:

Operator:
Well Name:
Original Comp. Date: Original Total Depth:

- [ ] Deepening
- [ ] Re-perf.
- [ ] Conv. to ENHR
- [ ] Conv. to SWD
- [ ] Conv. to GSW
- [ ] Plug Back: Plug Back Total Depth
- [ ] Commingled Permit #:
- [ ] Dual Completion Permit #:
- [ ] SWD Permit #:
- [ ] ENHR Permit #:
- [ ] GSW Permit #:

05/22/2013	05/28/2013	05/29/2013
Spud Date or Recompletion Date	Date Reached TD	Completion Date or Recompletion Date

API No. 15 - 15-051-26525-00-00
Spot Description:
SW - NE - NE - SW Sec. 19 Twp. 14 S. R. 18 [ ] East [x] West
2005 Feet from [ ] North / [x] South Line of Section
2280 Feet from [ ] East / [x] West Line of Section
Footages Calculated from Nearest Outside Section Corner:
[ ] NE [ ] NW [ ] SE [x] SW
County: Ellis
Lease Name: Georgine Staab Well #: 1-19
Field Name:
Producing Formation: LKC
Elevation: Ground: 2104 Kelly Bushing: 2112
Total Depth: 3830 Plug Back Total Depth:
Amount of Surface Pipe Set and Cemented at: 638 Feet
Multiple Stage Cementing Collar Used? [x] Yes [ ] No
If yes, show depth set: 1352 Feet
If Alternate II completion, cement circulated from: 1352
feet depth to: 0 w/ 155 sx cmt.

Drilling Fluid Management Plan
(Data must be collected from the Reserve Pit)

Chloride content: 24000 ppm Fluid volume: 160 bbls
Dewatering method used: Haul Off Pit

Location of fluid disposal if hauled offsite:

Operator Name: Blackhawk Production Company
Lease Name: Brull(SWD) License #: 32504
Quarter NW Sec. 30 Twp. 14 S. R. 18 [ ] East [x] West
County: Ellis Permit #: D26232

AFFIDAVIT

I am the affiant and I hereby certify that all requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Submitted Electronically

KCC Office Use ONLY

- [ ] **Letter of Confidentiality Received**
  Date:
- [ ] **Confidential Release Date:**
- [x] **Wireline Log Received**
- [x] **Geologist Report Received**
- [ ] **UIC Distribution**

ALT [ ] I [x] II [ ] III **Approved by:** Deanna Garrison **Date:** 09/10/2013

Side Two

[redacted]

1148414

Operator Name: Downing-Nelson Oil Co Inc Lease Name: Georgine Staab Well #: 1-19

Sec. 19 Twp. 14 S. R. 18 ☐ East ☑ West County: Ellis

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach complete copy of all Electric Wire-line Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken ☑ Yes ☐ No
(Attach Additional Sheets)

Samples Sent to Geological Survey ☑ Yes ☐ No

Cores Taken ☐ Yes ☑ No

Electric Log Run ☑ Yes ☐ No

Electric Log Submitted Electronically ☑ Yes ☐ No
(If no, Submit Copy)

List All E. Logs Run:
Attached

☑ Log Formation (Top), Depth and Datum ☐ Sample

Name	Top	Datum
Attached	Attached	Attached

CASING RECORD ☑ New ☐ Used
Report all strings set-conductor, surface, intermediate, production, etc.

Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface Pipe	12.25	8.625	23	638	Common	275	2% Gel & 3% CC
Production Casing	7.875	5.5	14	3827.19	EA/2	150	

ADDITIONAL CEMENTING / SQUEEZE RECORD

Purpose:
☐ Perforate
☐ Protect Casing
☐ Plug Back TD
☐ Plug Off Zone

Depth Top Bottom	Type of Cement	# Sacks Used	Type and Percent Additives
-			
-			

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record *(Amount and Kind of Material Used)*	Depth
4	3597' to 3602'	250 gallons Mud Acid	3597' to 3602'
		750 gallons 15% NE	3597' to 3602'

TUBING RECORD: Size: 2.375 Set At: 3790 Packer At:

Liner Run: ☐ Yes ☐ No

Date of First, Resumed Production, SWD or ENHR. 07/02/2013

Producing Method: ☐ Flowing ☑ Pumping ☐ Gas Lift ☐ Other *(Explain)*

Estimated Production Per 24 Hours	Oil Bbls.	Gas Mcf	Water Bbls.	Gas-Oil Ratio	Gravity
	25	0	0		

DISPOSITION OF GAS:
☐ Vented ☐ Sold ☐ Used on Lease
(If vented, Submit ACO-18.)

METHOD OF COMPLETION:
☐ Open Hole ☑ Perf. ☐ Dually Comp. *(Submit ACO-5)* ☐ Commingled *(Submit ACO-4)*
☐ Other *(Specify)*

PRODUCTION INTERVAL:

Mail to: KCC - Conservation Division, 130 S. Market - Room 2078, Wichita, Kansas 67202

Form	ACO1 - Well Completion
Operator	Downing-Nelson Oil Co Inc
Well Name	Georgine Staab 1-19
Doc ID	1148414

All Electric Logs Run

Sonic
Micro
Dual Induction
Compensated Density/Neutron

Form	ACO1 - Well Completion
Operator	Downing-Nelson Oil Co Inc
Well Name	Georgine Staab 1-19
Doc ID	1148414

Tops

Name	Top	Datum
Top Anhydrite	1360'	+752
Base Anhydrite	1401'	+711
Topeka	3127'	-1015
Heebner	3382'	-1270
Toronto	3402'	-1290
LKC	3432'	-1320
BKC	3659'	-1547
Arbuckle	3774'	-1662

QUALITY OILWELL CEMENTING, INC.

Federal Tax I.D.# 20-2886107

Phone 785-483-2025 Home Office P.O. Box 32 Russell, KS 67665 No. 6953

Cell 785-324-1041

	Sec.	Twp.	Range	County	State	On Location	Finish
Date 5-23-13	19	14	18	ELLIS	KANSAS		3:00 AM

Location HAYS - 5 TO MUNSTER RD. - 2½W - N/INTO

Lease GOEDGINE STAAB Well No. #1-19

Owner DOWNING & NELSON

Contractor D.D #4

To Quality Oilwell Cementing, Inc.
You are hereby requested to rent cementing equipment and furnish cementer and helper to assist owner or contractor to do work as listed.

Type Job SURFACE

Hole Size 12¼" T.D. 638'

Csg. 8⅝-23LB-NEW Depth 638'

Charge To DOWNING & NELSON

Street P.O. BOX 1019

Tbg. Size Depth

City HAYS State KS, 67601

Tool Depth

The above was done to satisfaction and supervision of owner agent or contractor.

Cement Left in Csg. Shoe Joint 15'

Cement Amount Ordered 275 com 3% cc - 2% GEL

Meas Line Displace 39½ BBLS

EQUIPMENT

Pumptrk #9 No. Cementer Helper TRAVIS H.

Bulktrk #1 No. Driver Driver DAVID L.

Bulktrk P/U No. Driver Driver CISCO A.

JOB SERVICES & REMARKS

Remarks:

Rat Hole

Mouse Hole

Centralizers

Baskets

D/V or Port Collar

CEMENT DID CIRCULATE!

THANK YOU!

X Signature

Common	275
Poz. Mix	
Gel.	5
Calcium	10
Hulls	
Salt	
Flowseal	
Koi-Seal	
Mud CLR 48	
CFL-117 or CD110 CAF 38	
Sand	
Handling	290
Mileage	

FLOAT EQUIPMENT

Guide Shoe	
Centralizer	
Baskets	
AFU Inserts	
Float Shoe	
Latch Down	
Pumptrk Charge	Long Surface
Mileage	7
Tax	
Discount	
Total Charge	

JOB LOG — SWIFT Services, Inc.

DATE 5-28-13 | PAGE NO. 1

CUSTOMER	WELL NO.	LEASE	JOB TYPE	TICKET NO.
Downing & Nelson	1-19	Georgine Staab	Cement Longstring	24344

CHART NO.	TIME	RATE (BPM)	VOLUME (BBL) (GAL)	PUMPS T	PUMPS C	PRESSURE (PSI) TUBING	PRESSURE (PSI) CASING	DESCRIPTION OF OPERATION AND MATERIALS
								TD 3830'
5/28	2110					14#/ft	5½	On location - Float Equip
	2130							Start 5½" - 14#/ft. Casing 3827'
								Insert Float Shoe w/ fillup
								D.V. L.D. Baffle - 5J - 16' = 93 BBL
								Cent - 1-3-5-7-9-11-59
								Cent Basket #60
								D.V. Tool #60 collar @ 1352' = 33 BBL
								Drop ball - 5 Jts ant
5/28	2300							Fin run casing - Tag
	2315							Start circ / Rotate casing
								Fin circ
		6					250	1st Stage - Start 500 gal mud flush
		6	12/32				250	Pump 20 BBL KCL flush
		4½					200	Start 150 sks EA-2 cmt.
			36				Vac	Fin cmt - Wash pump & lines
		9					300	Drop D.V. L.D Plug - Start Displ
			60/70					60/H2O - 33 mud / 70 cmt to pit
5/29	0030		93				800/1400	Plug Down - Held Release & Held (SMD)
	0032		9/5			~		Drop D.V. open Tool - Plug RH 14 BBL
	0045	6	20				1050/1400	Open D.V - Fin flush & circulating
		5					250	2nd Stage - Start 155 sks SMD
			86					Fin cmt - Drop D.V. Closing Plug
							950	Start Displ
	0120		33				500/1400	Plug down - 30 sks cmt circ to pit
								Release & Held
	0130							Job Complete
								Washup & Rackup
								Thanks
								Don, Jon & Rob



TRILOBITE TESTING, INC.

DRILL STEM TEST REPORT

Prepared For: **Downing Nelson Oil Co Inc**

PO Box 1019
Hays KS 67601

ATTN: Marc Downing

Georgine Staab #1-19

19-14s-18w Ellis KS

Start Date: 2013.05.26 @ 23:23:00
End Date: 2013.05.27 @ 07:02:30
Job Ticket #: 52199 DST #: 1

Trilobite Testing, Inc
PO Box 362 Hays, KS 67601
ph: 785-625-4778 fax: 785-625-5620

Printed: 2013.05.31 @ 11:13:33

DRILL STEM TEST REPORT

Downing Nelson Oil Co Inc

PO Box 1019
Hays KS 67601

ATTN: Marc Downing

19-14s-18w Ellis KS

Georgine Staab #1-19

Job Ticket: 52199 **DST#: 1**

Test Start: 2013.05.26 @ 23:23:00

GENERAL INFORMATION:

Formation: **LKC H-J**
Deviated: No Whipstock: ft (KB)
Time Tool Opened: 02:04:15
Time Test Ended: 07:02:30

Test Type: Conventional Bottom Hole (Initial)
Tester: Cody Bloedorn
Unit No: 43

Interval: 3538.00 ft (KB) To 3614.00 ft (KB) (TVD)
Total Depth: 3614.00 ft (KB) (TVD)
Hole Diameter: 7.88 inches Hole Condition: Fair

Reference Elevations: 2105.00 ft (KB)
2097.00 ft (CF)
KB to GR/CF: 8.00 ft

Serial #: 6799 **Inside**

Press@RunDepth: 147.69 psig @ 3606.00 ft (KB)
Start Date: 2013.05.26 End Date: 2013.05.27
Start Time: 23:23:05 End Time: 07:02:29

Capacity: 8000.00 psig
Last Calib.: 2013.05.27
Time On Btm: 2013.05.27 @ 02:04:00
Time Off Btm: 2013.05.27 @ 05:07:45

TEST COMMENT: 45 - IF- B.O.B. in 13 Minutes.
45 - ISI- Surface return
45 - FF- B.O.B. in 4 Minutes
45 - FSI- 5" return



PRESSURE SUMMARY

Time (Min.)	Pressure (psig)	Temp (deg F)	Annotation
0	1777.98	104.52	Initial Hydro-static
1	42.78	103.78	Open To Flow (1)
45	102.53	104.80	Shut-In(1)
91	1184.06	106.09	End Shut-In(1)
91	102.93	105.85	Open To Flow (2)
135	147.69	106.54	Shut-In(2)
183	1148.93	107.61	End Shut-In(2)
184	1748.14	108.09	Final Hydro-static

Recovery

Length (ft)	Description	Volume (bbl)
62.00	HOCM, 40%O, 60%M	0.59
124.00	GHOCM, 20%M, 40%O, 40%G	1.74
124.00	GMCO, 5%G, 40%M, 55%O	1.74
0.00	248' of G.I.P.	0.00

Gas Rates

	Choke (inches)	Pressure (psig)	Gas Rate (Mcf/d)

DRILL STEM TEST REPORT

Downing Nelson Oil Co Inc

PO Box 1019
Hays KS 67601

ATTN: Marc Downing

19-14s-18w Ellis KS

Georgine Staab #1-19

Job Ticket: 52199 **DST#: 1**

Test Start: 2013.05.26 @ 23:23:00

GENERAL INFORMATION:

Formation: **LKC H-J**
Deviated: No Whipstock: ft (KB)
Time Tool Opened: 02:04:15
Time Test Ended: 07:02:30

Test Type: Conventional Bottom Hole (Initial)
Tester: Cody Bloedorn
Unit No: 43

Interval: 3538.00 ft (KB) To 3614.00 ft (KB) (TVD)
Total Depth: 3614.00 ft (KB) (TVD)
Hole Diameter: 7.88 inches Hole Condition: Fair

Reference Elevations: 2105.00 ft (KB)
2097.00 ft (CF)
KB to GR/CF: 8.00 ft

Serial #: 8648 **Inside**

Press@RunDepth: psig @ 3606.00 ft (KB)
Start Date: 2013.05.26 End Date: 2013.05.27
Start Time: 23:23:05 End Time: 07:01:14

Capacity: 8000.00 psig
Last Calib.: 2013.05.27
Time On Btm:
Time Off Btm:

TEST COMMENT: 45 - IF- B.O.B. in 13 Minutes.
45 - ISI- Surface return
45 - FF- B.O.B. in 4 Minutes
45 - FSI- 5" return



PRESSURE SUMMARY

Time (Min.)	Pressure (psig)	Temp (deg F)	Annotation

Recovery

Length (ft)	Description	Volume (bbl)
62.00	HOCM, 40%O, 60%M	0.59
124.00	GHOCM, 20%M, 40%O, 40%G	1.74
124.00	GMCO, 5%G, 40%M, 55%O	1.74
0.00	248' of G.I.P.	0.00

Gas Rates

	Choke (inches)	Pressure (psig)	Gas Rate (Mcf/d)

DRILL STEM TEST REPORT

TOOL DIAGRAM

Downing Nelson Oil Co Inc

PO Box 1019
Hays KS 67601

ATTN: Marc Downing

19-14s-18w Ellis KS

Georgine Staab #1-19

Job Ticket: 52199 **DST#: 1**

Test Start: 2013.05.26 @ 23:23:00

Tool Information

Drill Pipe:	Length:	3507.00 ft	Diameter:	3.80 inches	Volume:	49.19 bbl	Tool Weight:		2000.00 lb
Heavy Wt. Pipe:	Length:	0.00 ft	Diameter:	0.00 inches	Volume:	0.00 bbl	Weight set on Packer:		30000.00 lb
Drill Collar:	Length:	31.00 ft	Diameter:	2.25 inches	Volume:	0.15 bbl	Weight to Pull Loose:		56000.00 lb
					Total Volume:	49.34 bbl	Tool Chased		0.00 ft
Drill Pipe Above KB:		21.00 ft					String Weight:	Initial	50000.00 lb
Depth to Top Packer:		3538.00 ft						Final	53000.00 lb
Depth to Bottom Packer:		ft							
Interval between Packers:		76.00 ft							
Tool Length:		97.00 ft							
Number of Packers:		2	Diameter:	6.75 inches					

Tool Comments:

Tool Description	Length (ft)	Serial No.	Position	Depth (ft)	Accum. Lengths	
Change Over Sub	1.00			3518.00		
Shut In Tool	5.00			3523.00		
Hydraulic tool	5.00			3528.00		
Packer	5.00			3533.00	21.00	Bottom Of Top Packer
Packer	5.00			3538.00		
Stubb	1.00			3539.00		
Perforations	3.00			3542.00		
Change Over Sub	1.00			3543.00		
Drill Pipe	62.00			3605.00		
Change Over Sub	1.00			3606.00		
Recorder	0.00	6799	Inside	3606.00		
Recorder	0.00	8648	Inside	3606.00		
Perforations	5.00			3611.00		
Bullnose	3.00			3614.00	76.00	Bottom Packers & Anchor
Total Tool Length:	**97.00**					

DRILL STEM TEST REPORT

FLUID SUMMARY

Downing Nelson Oil Co Inc

PO Box 1019
Hays KS 67601

ATTN: Marc Downing

19-14s-18w Ellis KS

Georgine Staab #1-19

Job Ticket: 52199 **DST#: 1**

Test Start: 2013.05.26 @ 23:23:00

Mud and Cushion Information

Mud Type:	Gel Chem	Cushion Type:		Oil API:	deg API
Mud Weight:	9.00 lb/gal	Cushion Length:	ft	Water Salinity:	ppm
Viscosity:	60.00 sec/qt	Cushion Volume:	bbl		
Water Loss:	7.99 in³	Gas Cushion Type:			
Resistivity:	ohm.m	Gas Cushion Pressure:	psig		
Salinity:	4000.00 ppm				
Filter Cake:	inches				

Recovery Information

Recovery Table

Length ft	Description	Volume bbl
62.00	HOCM, 40%O, 60%M	0.587
124.00	GHOCM, 20%M, 40%O, 40%G	1.739
124.00	GMCO, 5%G, 40%M, 55%O	1.739
0.00	248' of G.I.P.	0.000

Total Length: 310.00 ft Total Volume: 4.065 bbl

Num Fluid Samples: 0 Num Gas Bombs: 0 Serial #:
Laboratory Name: Laboratory Location:
Recovery Comments:

Serial #: 6799 **Inside** Dow ning Nelson Oil Co Inc Georgine Staab #1-19 DST Test Number: 1



Trilobite Testing, Inc Ref. No: 52199 Printed: 2013.05.31 @ 11:13:36

Serial #: 8648 **Inside** Dow ning Nelson Oil Co Inc Georgine Staab #1-19 DST Test Number: 1



Trilobite Testing, Inc Ref. No: 52199 Printed: 2013.05.31 @ 11:13:37



TRILOBITE TESTING, INC.

DRILL STEM TEST REPORT

Prepared For: **Downing Nelson Oil Co Inc**

PO Box 1019
Hays KS 67601

ATTN: Marc Downing

Georgine Staab #1-19

19-14s-18w Ellis KS

Start Date: 2013.05.27 @ 13:34:00
End Date: 2013.05.27 @ 19:51:45
Job Ticket #: 52200 DST #: 2

Trilobite Testing, Inc
PO Box 362 Hays, KS 67601
ph: 785-625-4778 fax: 785-625-5620

Printed: 2013.05.31 @ 11:12:53

DRILL STEM TEST REPORT

Downing Nelson Oil Co Inc

PO Box 1019
Hays KS 67601

ATTN: Marc Downing

19-14s-18w Ellis KS

Georgine Staab #1-19

Job Ticket: 52200 **DST#: 2**

Test Start: 2013.05.27 @ 13:34:00

GENERAL INFORMATION:

Formation: **Sand**
Deviated: No Whipstock: ft (KB)
Time Tool Opened: 15:31:45
Time Test Ended: 19:51:45

Test Type: Conventional Bottom Hole (Reset)
Tester: Cody Bloedorn
Unit No: 43

Interval: 3610.00 ft (KB) To 3633.00 ft (KB) (TVD)
Total Depth: 3633.00 ft (KB) (TVD)
Hole Diameter: 7.88 inches Hole Condition: Fair

Reference Elevations: 2105.00 ft (KB)
2097.00 ft (CF)
KB to GR/CF: 8.00 ft

Serial #: 6799 **Inside**

Press@RunDepth: 15.83 psig @ 3615.00 ft (KB)
Start Date: 2013.05.27 End Date: 2013.05.27
Start Time: 13:34:05 End Time: 19:51:44

Capacity: 8000.00 psig
Last Calib.: 2013.05.27
Time On Btm: 2013.05.27 @ 15:31:30
Time Off Btm: 2013.05.27 @ 17:32:15

TEST COMMENT: 30 - IF- Surface blow , died in 18 min.
30 - ISI- No return
30 - FF- No blow for 5 minutes, flushed tool, surged and died
30 - FSI- No return



PRESSURE SUMMARY

Time (Min.)	Pressure (psig)	Temp (deg F)	Annotation
0	1777.64	100.51	Initial Hydro-static
1	8.06	99.86	Open To Flow (1)
27	11.81	100.63	Shut-In(1)
59	1087.04	102.19	End Shut-In(1)
60	12.30	101.92	Open To Flow (2)
90	15.83	103.21	Shut-In(2)
120	975.86	104.49	End Shut-In(2)
121	1732.57	104.90	Final Hydro-static

Recovery

Length (ft)	Description	Volume (bbl)
15.00	Mud w / show of oil 100%M	0.07

* Recovery from multiple tests

Gas Rates

	Choke (inches)	Pressure (psig)	Gas Rate (Mcf/d)

DRILL STEM TEST REPORT

Downing Nelson Oil Co Inc

PO Box 1019
Hays KS 67601

ATTN: Marc Downing

19-14s-18w Ellis KS

Georgine Staab #1-19

Job Ticket: 52200 **DST#: 2**

Test Start: 2013.05.27 @ 13:34:00

GENERAL INFORMATION:

Formation: **Sand**
Deviated: No Whipstock: ft (KB)
Time Tool Opened: 15:31:45
Time Test Ended: 19:51:45

Test Type: Conventional Bottom Hole (Reset)
Tester: Cody Bloedorn
Unit No: 43

Interval: 3610.00 ft (KB) To 3633.00 ft (KB) (TVD)
Total Depth: 3633.00 ft (KB) (TVD)
Hole Diameter: 7.88 inches Hole Condition: Fair

Reference Elevations: 2105.00 ft (KB)
2097.00 ft (CF)
KB to GR/CF: 8.00 ft

Serial #: 8648 **Inside**

Press@RunDepth: psig @ 3615.00 ft (KB)
Start Date: 2013.05.27 End Date: 2013.05.27
Start Time: 13:34:05 End Time: 19:50:29

Capacity: 8000.00 psig
Last Calib.: 2013.05.27
Time On Btm:
Time Off Btm:

TEST COMMENT: 30 - IF- Surface blow , died in 18 min.
30 - ISI- No return
30 - FF- No blow for 5 minutes, flushed tool, surged and died
30 - FSI- No return



PRESSURE SUMMARY

Time (Min.)	Pressure (psig)	Temp (deg F)	Annotation

Recovery

Length (ft)	Description	Volume (bbl)
15.00	Mud w / show of oil 100%M	0.07

* Recovery from multiple tests

Gas Rates

	Choke (inches)	Pressure (psig)	Gas Rate (Mcf/d)

DRILL STEM TEST REPORT

TOOL DIAGRAM

Downing Nelson Oil Co Inc

PO Box 1019
Hays KS 67601

ATTN: Marc Downing

19-14s-18w Ellis KS

Georgine Staab #1-19

Job Ticket: 52200 **DST#: 2**

Test Start: 2013.05.27 @ 13:34:00

Tool Information

Drill Pipe:	Length:	3568.00 ft	Diameter:	3.80 inches	Volume:	50.05 bbl	Tool Weight:		2000.00 lb
Heavy Wt. Pipe:	Length:	0.00 ft	Diameter:	0.00 inches	Volume:	0.00 bbl	Weight set on Packer:		30000.00 lb
Drill Collar:	Length:	31.00 ft	Diameter:	2.25 inches	Volume:	0.15 bbl	Weight to Pull Loose:		54000.00 lb
					Total Volume:	50.20 bbl	Tool Chased		0.00 ft
Drill Pipe Above KB:		10.00 ft					String Weight:	Initial	50000.00 lb
Depth to Top Packer:		3610.00 ft						Final	50000.00 lb
Depth to Bottom Packer:		ft							
Interval between Packers:		23.00 ft							
Tool Length:		44.00 ft							
Number of Packers:		2	Diameter:	6.75 inches					

Tool Comments:

Tool Description	Length (ft)	Serial No.	Position	Depth (ft)	Accum. Lengths	
Change Over Sub	1.00			3590.00		
Shut In Tool	5.00			3595.00		
Hydraulic tool	5.00			3600.00		
Packer	5.00			3605.00	21.00	Bottom Of Top Packer
Packer	5.00			3610.00		
Stubb	1.00			3611.00		
Perforations	4.00			3615.00		
Recorder	0.00	6799	Inside	3615.00		
Recorder	0.00	8648	Inside	3615.00		
Perforations	15.00			3630.00		
Bullnose	3.00			3633.00	23.00	Bottom Packers & Anchor
Total Tool Length:	**44.00**					

DRILL STEM TEST REPORT

FLUID SUMMARY

Downing Nelson Oil Co Inc

PO Box 1019
Hays KS 67601

ATTN: Marc Downing

19-14s-18w Ellis KS

Georgine Staab #1-19

Job Ticket: 52200 **DST#: 2**

Test Start: 2013.05.27 @ 13:34:00

Mud and Cushion Information

Mud Type:	Gel Chem	Cushion Type:		Oil API:	deg API
Mud Weight:	9.00 lb/gal	Cushion Length:	ft	Water Salinity:	ppm
Viscosity:	60.00 sec/qt	Cushion Volume:	bbl		
Water Loss:	7.98 in³	Gas Cushion Type:			
Resistivity:	ohm.m	Gas Cushion Pressure:	psig		
Salinity:	4000.00 ppm				
Filter Cake:	inches				

Recovery Information

Recovery Table

Length ft	Description	Volume bbl
15.00	Mud w / show of oil 100%M	0.074

Total Length: 15.00 ft Total Volume: 0.074 bbl

Num Fluid Samples: 0 Num Gas Bombs: 0 Serial #:
Laboratory Name: Laboratory Location:
Recovery Comments:

Serial #: 6799 **Inside** Downing Nelson Oil Co Inc Georgine Staab #1-19 DST Test Number: 2



Trilobite Testing, Inc Ref. No: 52200 Printed: 2013.05.31 @ 11:12:56

Serial #: 8648 **Inside** Dow ning Nelson Oil Co Inc Georgine Staab #1-19 DST Test Number: 2



Trilobite Testing, Inc Ref. No: 52200 Printed: 2013.05.31 @ 11:12:56

TRILOBITE TESTING INC.

1515 Commerce Parkway • Hays, Kansas 67601

4/10

Test Ticket

NO. 52199

Well Name & No. Georgine Staab #1-19 Test No. 1 Date 5-26-13

Company Downing-Nelson Oil Co Inc Elevation 2105 KB 2097 GL

Address Po Box 1019, Hays KS, 67601

Co. Rep / Geo. Marc Downing Rig Discovery #4

Location: Sec. 19 Twp. 14s Rge. 18w Co. Ellis State KS

Interval Tested 3538-3614 Zone Tested "H-J"

Anchor Length 76' Drill Pipe Run 3507' Mud Wt. 9.0

Top Packer Depth 3533 Drill Collars Run 31' Vis 60

Bottom Packer Depth 3538 Wt. Pipe Run — WL 8.0

Total Depth 3614 Chlorides 4,000 ppm System LCM —

Blow Description IF- B.O.B. in 13 Minutes

ISI- Surface return

FF- B.O.B. in 4 minutes

FSI- 5" return

Rec 62	Feet of HOCM	%gas	40 %oil	%water	60 %mud		
Rec 124	Feet of GHOCM	40 %gas	40 %oil	%water	20 %mud		
Rec 124	Feet of GMCO	5 %gas	55 %oil	%water	40 %mud		
Rec	Feet of	%gas	%oil	%water	%mud		
Rec	Feet of 248' of G.I.P.	%gas	%oil	%water	%mud		

Rec Total 310' BHT 107° Gravity — API RW — @ — °F Chlorides — ppm

(A) Initial Hydrostatic 1777	☒ Test 1150	T-On Location 9:58pm	
(B) First Initial Flow 42	☐ Jars	T-Started 11:23pm	
(C) First Final Flow 162	☐ Safety Joint	T-Open 2:05am	
(D) Initial Shut-In 1184	☐ Circ Sub	T-Pulled 5:05am	
(E) Second Initial Flow 102	☐ Hourly Standby	T-Out 7:03am	
(F) Second Final Flow 147	☒ Mileage 22 RT 34.10	Comments	
(G) Final Shut-In 1148	☐ Sampler		
(H) Final Hydrostatic 1748	☐ Straddle	☐ Ruined Shale Packer	
	☐ Shale Packer	☐ Ruined Packer	
Initial Open 45	☐ Extra Packer	☐ Extra Copies	
Initial Shut-In 45	☐ Extra Recorder	Sub Total 0	
Final Flow 45	☐ Day Standby	Total 1184.10	
Final Shut-In 45	☐ Accessibility	MP/DST Disc't	
	Sub Total 1184.10		

Approved By Our Representative Cody Bell

TRILOBITE TESTING INC.

1515 Commerce Parkway • Hays, Kansas 67601

4/10

Test Ticket

NO. 52200

Well Name & No. Georgine Staab #1-19 Test No. 2 Date 5-27-13

Company Downing-Nelson Oil Co Inc Elevation 2105 KB 2097 GL

Address Po Box 1019, Hays KS, 67601

Co. Rep / Geo. Marc Downing Rig Discovery #4

Location: Sec. 19 Twp. 14s Rge. 18w Co. Ellis State KS

Interval Tested 3610 - 3633 Zone Tested Sand

Anchor Length 23' Drill Pipe Run 3568 Mud Wt. 9.0

Top Packer Depth 3605 Drill Collars Run 31' Vis 60

Bottom Packer Depth 3610 Wt. Pipe Run — WL 8.0

Total Depth 3633 Chlorides 4,000 ppm System LCM —

Blow Description IF - Surface blow, died in 18 minutes

ISI - No return

FF - No blow for 5 min. flushed tool, surged & died

FSI - No return

Rec 15	Feet of Mud, show of oil	%gas	%oil	%water 100	%mud
Rec	Feet of	%gas	%oil	%water	%mud
Rec	Feet of	%gas	%oil	%water	%mud
Rec	Feet of	%gas	%oil	%water	%mud
Rec	Feet of	%gas	%oil	%water	%mud

Rec Total 15' BHT 104° Gravity — API RW — @ — °F Chlorides — ppm

(A) Initial Hydrostatic 1777	☒ Test 1150	T-On Location 1:18 pm
(B) First Initial Flow 8	☐ Jars	T-Started 1:34 pm
(C) First Final Flow 11	☐ Safety Joint	T-Open 3:31 pm
(D) Initial Shut-In 1087	☐ Circ Sub	T-Pulled 5:31 pm
(E) Second Initial Flow 12	☒ Hourly Standby ~~1.5 hours~~	T-Out 7:51 pm
(F) Second Final Flow 15	☒ Mileage 22RT X2 68.20	Comments Rig wouldn't start. Had to fix it.
(G) Final Shut-In 975	☐ Sampler	Done 5-28-13 loaded @ 8:30 am
(H) Final Hydrostatic 1732	☐ Straddle	☐ Ruined Shale Packer
	☐ Shale Packer	☐ Ruined Packer
Initial Open 30	☐ Extra Packer	☐ Extra Copies
Initial Shut-In 30	☐ Extra Recorder	Sub Total 0
Final Flow 30	☐ Day Standby	Total 1218.20
Final Shut-In 30	☐ Accessibility	MP/DST Disc't
	Sub Total 1218.20	

Approved By _____ Our Representative Cody B

Marc Downing
Consulting Petroleum Geologist
1441 Washington Circle
Phone: (620) 285-3165 • Fax: (620) 285-3286

GEOLOGIC REPORT LOG

COMPANY Ramsey-Hixon Oil Co., Inc.

WELL Georgine Shank #1-A

FIELD Wildcat

LOCATION 2065' FSL & 2260' FWL

SEC. 14 TWP. 14S RGE. 14W

COUNTY Ellis

STATE Kansas

OPERATOR Ramsey-Hixon Oil Co., Inc.

CONTRACTOR Discovery Drilling, Rig #1

SPUD 8-25-13 COMP. 9-3-13 TOTAL DEPTH 3634'

CASING RECORD 8 5/8" @ 227' w/ 150 sks

PRODUCTION OIL

ELEVATION GR 2112 KB 2120 DF — GL 2107

	Sample Samet	Elect. Log	Datum
Topeka	3162	3164	-1044
Heebner	3391	3391	-1271
Toronto	3414	3414	-1294
LKC	3431	3431	-1311
Arbuckle	3714	3714	-1594
RTD	3634		-1514
LTD		3634	-1514

Drilling Time Kept From 3000' To RTD
Samples Saved From 3200' To RTD
Geological Supervision From 3200' To RTD
Type Of Drilling Mud Chemical
Rotary Tools Were Used From Surface To RTD
Cable Tools Were Used From — To —

DRILL STEM TESTS

No.	Interval	Open	Shut-In	Recovery	Remarks
1	3410-3433	30-30-30-30	45-45-45-45	248' GIP 120' GMCO 5% g 65% o 120' GMO 40% g 60% o 60' HOCM 40% o	
2	3539-3634	30-30-30-30	45-45-45-45	248' GIP 120' GMCO 5% g 65% o 120' GMO 40% g 60% o 60' HOCM 40% o	

FORMATION TOPS AND STRUCTURAL POSITION

FORMATION	SAMPLE TOP	DATUM	ELECTRIC LOG TOP	DATUM
Topeka	3162	-1044	3164	-1044
Heebner	3391	-1271	3391	-1271
Toronto	3414	-1294	3414	-1294
LKC	3431	-1311	3431	-1311
Arbuckle	3714	-1594	3714	-1594
RTD	3634	-1514		
LTD			3634	-1514

REFERENCE WELL FOR STRUCTURE
Rose #1
NW-NW-SE
Location
Drilling
Sec. 14-14S-14W

Remarks "D" zone below abandonment.

LEGEND

Anhydrite | Salt | Sandstone | Shale | Carb sh | Limestone | Ool./Lime | Chert | Dolomite

DRILLING TIME IN MINUTES PER FOOT
Rate of Penetration Decreases
5" 10" 15"

DEPTH | LITHOLOGY | SAMPLE DESCRIPTIONS | OIL SHOWS | REMARKS

3050
3100
Topeka 3162(-1044)
50
3200
50
3300
Heebner 3391(-1271)
3400
Toronto 3414(-1294)
LKC 3431(-1311)
50
CFS
3500
50
CFS
3600
CFS
50
Arbuckle 3714(-1594)
3700
CFS
50
3800
50
RTD: 3634(-1514)
LTD: 3634(-1512)
CHMO
3850

Ls: white, md xln, stffly sbwt, sml shell frag frm
Trng: brn, vfxln, sbwt mtx w/ ltly foss.
No stng in ppt.

Sh: drk gry
Ls: white - lt tan. Scat spl ppr wl rare mtrx
Sh: Many chlky sx, mostly brn/wh, NA Od.

Sh: gy
Ls: tan - wht, fm md xln., ppr, NS.

Ls: w/wht - lt tan. Stffly sbwt, subdue mtrx stn, NSFo, NA Od.

Ls: wht - tan, md xln, stffly sbwt. Trng w chlky & wstd. Scat gy frss and a. All NS.

Sh: Black Carb

Sh: gy
Ls: cmst, vfxln-mic xln, sl ppr
Ls: AIA, stffly chlky.

Ls: wht-tan, fn xln, ppr, Scat foss. All NS.

Sh: gy
Ls: wht - tan - fm, fn md xln. tan foss chrts.

Sh: Black Carb

Sh: gy
Ls: wht - lt tan, fn xln. Scat chlky sx, mostly ppr + dns. Totally barren, No Od. Scat sml gy foss.

Sh: gy
Ls: wht, fm md xln, mostly chlky. 1-2 ex cst fr gry & grn sbwt clay. Scat spl Od.
Ls: wht, fn-md xln, Scat Foss. Trng stffly mtld & ppr, NS.

Sh: Black Carb

Sh: gy
Ls: loose, md xln. Mostly ppr & fcht. 1-2 ex wl lt tan, pr spttd Sfo, Fair NA Od.

Sh: lt gy to wh brn
Ls: cmst, fn xln. Subdue in ppt, NS.
Sh: Brn
Ls: cmst, fm md xln. ppr, NS.
Sh: gy
Ls: wht, fn xln, clky in ppt. pr fr evng, Scat mdse stn, NSFo, NA Od.

Sh: gy
Ls: fm wht, mdstn. Scat foss. 1-2 ex wl gry & grn sbwt clay. Scat dsc spl Od. Scat subdue chlky sx

Sh: gy
Ls: cst, fn xln, cal. Scat mdstone, mostly chlky. All NS, NA Od.
Ls: Mostly AIA. Some pck-ing fairly SFo, NSFo
Ls: wht, fn xln, subdue in ppt. All NS, fairly ppr.

Sh: Black Carb

Sh: gy
Ls: fm wht, ppr. 1-2 ex wl pr drgy stn, NSFo, NA Od.
Mostly ppr, sli gry shales.
Ls: tan, cmst-md. Pr wl w-AIA, pr fr evng fr ex cem SFo, NSFo, NA Od.
Ls: mostly AIA, ppr & chlk

Sh: gy
Ls: tan, fm-md xln, Scat foss & cal. No visg & NS.

Sh: gy
Ls: brn wl cmt, ppr

Sh: brn wl gry

Ls: tan, md xln, sndy in ppt, NS.

Sh: brn wl gry

Ls: AIA

Sh: red wl brn. v gummy & dry. washes red.
Scat tan - org chrts.

Sh: mostly AIA, v dry. Fr and tan - org chrts, washes red.

Scat wht dolo, mostly dns w/ wl mtrx rck SFo.
Dolo: wht, mdt-crs mass xln. Fr vsl stn & scat vsgy. All NS. Scat gilsonite.
Dolo: Mostly AIA. Fr vsgy, md rhom xln.
Totally barren.

Vis: 60 WL: 9.0

DST #1
3539-3634
45-45-45-45
I.F.- 68# 18 min / Surf 32#
F.F.- 84# 4 min / 8" 55#
ISIP: 972-1012
FFP: 142-149
SIP: 1149-1149
HP: 1777-1749
Rec:
248' GIP
120' GMCO 5% g 65% o
120' GMO 40% g 60% o
60' HOCM 40% o
BHT: 107°

DST #2
3410-3433
30-30-30-30
IFP: 5#
FFP: 12-15
SIP: 1087-978
HP: 1777-1722
Rec:
15' mud wl oil spks
BHT: 104°