STERLING DRILLING COMPANY

BOX 129 STERLING, KANSAS 67579

WELL LOG - - - - - - - - - - - LAMBERT #1-4

NE SW SE, Section 4-T30S-R13W, Barber County, Ks.

OWNER: F. G. Holl

ROTARY DRILLING CONTRACTOR: Sterling Drilling Company

COMMENCED: July 29, 1989 COMPLETED: August 9, 1989

TOTAL DEPTH 4720'

LOG

0' - 130' surface soil and sand 130' - 267' red bed

2671 6201 = 1=1=1= 6 ====

267' - 620' shale & redbed

620' - 1019' shale

1019' - 4720' lime & shale

CASING RECORD

Ran 6 joints 10 3/4" 32.30# new casing. 252.31' pipe set at 265' KB. Cemented with 235 sacks 60/40 Pozmix, 2% Gel, 3% cc. Plug down at 6:00PM 7-29-89 by Howco - good returns.

Note: lost circulation at 853', spotted 150 sacks at 853' and 100 sacks at 822'.

Ran 28 joints 8 5/8" 23# new casing. 989.39' pipe set at 1000' KB. Cemented with 230 sacks 60-40 Pozmix, 2% gel and 3% cc. Plug down at 5:30PM 7-31-89 by Howco - no returns.

Ran 131 joints 4½" 10.5# used casing. 4710.39' pipe set at 4718' KB. Cemented with 100 sacks Lite followed with 125 sacks 50/50 Pozmix W/ regulare F. G. Holl additives. Plug down at 4:30 PM 8-9-89 by Howco. Centralizers on jts. 1, 4, & 15. Scratchers 4480'-4520'; 4360' - 4470'. Shoe joint 15.58' long.

DEVIATIONS

597' 3/4° 4330' 3/4°