

DRILLERS LOG

Beldon-Chance #1

4-26-13W

SW-NW-SE

CASING RECORD:
8 5/8" set at 337'
with 275 sacks cement

OPERATOR: Robert E. Campbell

DESCRIPTION:

TOTAL DEPTH:
4265'

CONTRACTOR: Search Drilling

100' E & 100' N of
SW NW SE,
Section 4-26S-13W
Pratt County,
Kansas

COMMENCED: September 12, 1977

COMPLETED: September 19, 1977

FORMATION

FROM

TO

REMARKS

Clay and Sand	0	215
Red Bed	215	348
Red Bed and Shale	348	828
Anhydrite and Shale and Lime	828	1064
Shale and Lime	1064	1843
Shale and Lime	1843	2686
Lime and Shale	2686	3632
Lime and Shale	3632	4155
Lime and Shale Mississippi	4155	4222
Lime and Shale	4222	4265
Rotary Total Depth	4265	

Ran 111 joints new 4 1/2" set and cemented at 4264' with 225 sacks 50/50 posmix, salt saturated. Plug down at 2:00 P.M. September 19, 1977. By Sun Cementing Co.

ROBERT E. CAMPBELL
SUITE 110, 260 N. ROCK RD. #1 BELDEN-CHANCE 4-26-13W
WICHITA, KS. 100' N & 100' E,
CONTR SEARCH DRLG. CO. CTY PRATT SW NW SE

GEOL _____ FIELD FRISBIE NE

E 1946 KB CM 9/12/77 CARD ISSUED 6/29/78 1 PT TST 437 MCF GPD
+ 3 BFPD, 30% OIL
API 15-151-20,415 MISS 4146-87 OA

+	+	+
+	+	+

SMP	TOPS	DEPTH	DATUM
BR LM	3706	-1760	
MISS	4145	-2199	
MISN	4208	-2262	
VIOLA	4222	-2276	
RTD	4265	-2319	

8-5/8" 327/275sx, 4 1/2" 4264/275sx
DST (1) 4060-4155/30-45-60-60, GTS/40"
GA 5000/70", 7000/90", 40' M, SIP
963-1199#, FP 30-30#, 40-40#
DST (2) 4152-4175/30-60-60-75, GTS/10"
GA 48 MCF/15", 46 MCF/30" (2ND OP)
GA 137 MCF/5", 66 MCF/25", 49 MCF/
50" & STAB, 55' M, SIP 1188-1088#,
FP 33-33#, 33-33#
DST (3) 4182-4197/30-45-45-60, 600' GIP
40' SOCM, SIP 809-1230#, FP 40-40#
40-40#
DST (4) 4204-4222/20-30-30-30, 400' GIP
10' M w/so, SIP 33-33#, FP 33-33#
33-33#

INDEPENDENT OIL & GAS SERVICE
WICHITA, KANSAS

(OVER)

K. G. S. LIBRARY

