



**CONSOLIDATED**  
Oil Well Services, LLC

261399

TICKET NUMBER 42339

LOCATION Ottawa KS.

FOREMAN Fred Madar

PO Box 884, Chanute, KS 66720  
620-431-9210 or 800-467-8676

**FIELD TICKET & TREATMENT REPORT  
CEMENT**

DATE	CUSTOMER #	WELL NAME & NUMBER	SECTION	TOWNSHIP	RANGE	COUNTY
8-14-13	2579	Alexander #52 AL-21	SE 29	18	21	FR

CUSTOMER  
Enerjex Resources Inc.  
MAILING ADDRESS  
10975 Grandview Dr  
CITY  
Overland Park STATE KS ZIP CODE 66210

TRUCK #	DRIVER	TRUCK #	DRIVER
712	Fred Madar		
495	Harbor		
370	Ken Car		
548	Mik Han		

JOB TYPE Longstring HOLE SIZE 6 HOLE DEPTH 740' CASING SIZE & WEIGHT 2 7/8 EUE  
CASING DEPTH 726 DRILL PIPE \_\_\_\_\_ TUBING \_\_\_\_\_ OTHER \_\_\_\_\_  
SLURRY WEIGHT \_\_\_\_\_ SLURRY VOL \_\_\_\_\_ WATER gal/sk \_\_\_\_\_ CEMENT LEFT in CASING 2 1/2" Plug  
DISPLACEMENT 4.2 BBL DISPLACEMENT PSI \_\_\_\_\_ MIX PSI \_\_\_\_\_ RATE 4 BPM

REMARKS: Hold crew safety meeting. Establish pump rate: Mix Pump 100\*  
Gel Flush. Mix + Pump 107 sks 70/30 for mix Cement 290 Gal  
5% Salt 1/2\* Pheno Seal/5k. Cement to surface. Flush pump + lines  
clean. Displace 2 1/2" Rubber plug to casing TO. Pressure to 800\* PSL.  
Hold + Monitor pressure for 30 min. MIT. Release pressure to  
set float valve. Shut in casing.

JTC Drilling Fred Madar

ACCOUNT CODE	QUANTITY or UNITS	DESCRIPTION of SERVICES or PRODUCT	UNIT PRICE	TOTAL
5401	1	PUMP CHARGE		
5406		MILEAGE	495	1085.00
5402	726	Casing footage		N/C
5407	1/2 minimum	Ton Miles		N/C
5502C	1 1/2 hr	80 BBL Vac. Truck		164.00
				135.00
1127	107 sks	70/30 for Mix Cement		1428.45
1118B	289 #	Premium Gel		63.58
1111	217 #	Granulated Salt		84.63
1107A	54 #	Pheno Seal		72.90
4402	1	2 1/2" Rubber Plug		29.50
			2.65%	
			SALES TAX ESTIMATED TOTAL	128.45

AUTHORIZATION Jay TITLE \_\_\_\_\_ DATE \_\_\_\_\_

I acknowledge that the payment terms, unless specifically amended in writing on the front of the form or in the customer's account records, at our office, and conditions of service on the back of this form are in effect for services identified on this form