

FIELD DATA

Location: Holcomb, Ks
MP 45.59

Hole Depth: 2 @ 250' East Ground-bed & West Ground-bed
Hole Diameter: 10"
Anode Column: East 210' West 216'
Anode Spacing: 12'

Boring Record East Ground-bed M796B:2-2			
Geological Materials	Abbrev.	From	To
Top Soil / Clay	TS / CL	0'	20'
Sand / Clay	S / CL	20'	40'
Clay / Little Fine Sand	CL / LFS	40'	60'
Shale	SH	60'	100'
Shale / Sand Stone	SH / ST-SS	100'	180'
Shale	SH	180'	200'
Shale / Streak Rock	SH / ST Rock	200'	250'

Down-Hole Log East Ground Bed 12.86 V - 0.01 ohm Shunt							
Depth	mV	Depth	mV	Depth	mV	Depth	mV
30	22.8	130	14.10	230	26.70		
40	27.4	140	17.20	240	24.20		
50	21.1	150	21.00				
60	21.7	160	22.50				
70	19.7	170	21.20				
80	17.1	180	21.50				
90	17.2	190	22.50				
100	16.4	200	19.60				
110	13.2	210	21.30				
120	12.3	220	24.00				

Boring Record West Ground-bed M796B:2-1			
Geological Materials	Abbrev.	From	To
Top Soil/ Sand / Clay	TS/S/CL	0'	20'
Clay / Little Fine Sand	CL / LFS	20'	40'
Shale	SH	40'	60'
Shale / Streak Rock/Sand Stone	SH/ST SS	60'	100'
Shale / Streak Rock/Sand Stone	SH/ST-SS	100'	180'
Sand Stone / Shale	SS / SH	180'	220'
Shale / Streak Rock	SH	220'	250'