



11 Lewis Drive

Paola, KS 66071

Oil & Gas Well Drilling
Water Wells
Geo-Loop Installation

Phone: 913-557-9083

Fax: 913-557-9084

WELL LOG

Verde Oil Company
Campbell #I-75-65
API #15-001-30,737
July 22- July 23, 2013

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
6	soil & clay	6
51	lime	57
3	shale	60
3	lime	63
19	shale	82
18	lime	100
3	shale	103
30	lime	133 oil show
1	shale	134
21	lime	155 base of the Kansas City
99	shale	254
4	lime	258
32	shale	290
7	lime	297
14	shale	311
15	lime	326
3	shale	329
3	lime	332
17	shale	349
3	lime	352
25	shale	377
7	lime	384
29	shale	413
2	lime	415
8	shale	423
11	lime	434
3	shale	437
6	lime	443
39	shale	482
29	lime	511
53	shale	564
4	lime	568
41	shale	609
2	lime	611
51	shale	662
3	limy sand	665 brown, ok bleeding
58	shale	723
6	broken sand	729 black & grey, ok bleeding
49	shale	778

5	silty shale	783
7	broken sand	790 light brown & shale, light bleeding
8	silty shale	798
3	broken sand	801 80% brown sand, 20% silty shale gassy, good bleeding
1	sand	802 brown, no oil
17	shale	819
7	broken sand	826 soft brown sand, shale, good bleeding
16	oil sand	842 soft brown sand, good bleeding
1	coal	843
10	oil sand	853 light grey & brown, ok bleeding
14	oil sand	867 black & grey, ok bleeding
34	shale	901
1	lime	902 Mississippi TD

Drilled a 9 7/8" hole to 23.7'

Drilled a 5 5/8" hole to 902'

Set 23.7' of 7" threaded and coupled surface casing, cemented with 6 sacks cement.

Set 894.9' of 2 7/8" 8 round upset tubing with 4 centralizers, 1 float shoe, 1 clamp, 1 baffle