



11 Lewis Drive

Paola, KS 66071

**Oil & Gas Well Drilling
Water Wells
Geo-Loop Installation**

Phone: 913-557-9083

Fax: 913-557-9084

WELL LOG

Verde Oil Company
Campbell #I-8-8
API #15-001-30,739
July 19- July 22, 2013

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
5	soil & clay	5
35	lime	40
8	shale	48
10	lime	58
5	shale	63
3	lime	66
20	shale	86
15	lime	101
3	shale	104
52	lime	156 base of the Kansas City
98	shale	254
9	lime	263
30	shale	293
3	lime	296
16	shale	312
3	lime	315
3	shale	318
10	lime	328
2	shale	330
4	lime	334
15	shale	349
4	lime	353
25	shale	378
2	lime	380
36	shale	416
20	lime	436
1	shale	437
7	lime	444
5	shale	449
1	lime	450
33	shale	483
15	lime	498 oil show
10	shale	508
3	lime	511
98	shale	609
1	lime	610
109	shale	719
4	silty shale	723 grey black
3	shale	726

2	silty shale	728
1	coal	729
38	shale	767
4	broken sand	771 brown sand & shale, minimal bleeding
3	shale	774
2	broken sand	776 brown & shale, no show
27	shale	803
4	broken sand	807 brown sand & shale, good bleeding
6	oil sand	813 brown sand, good bleeding
8	broken sand	821 brown sand & shale, good bleeding
8	oil sand	829 soft brown sand, good bleeding
0.5	coal	829.5
7.5	oil sand	837 soft brown sand, good bleeding
2	broken sand	839 shale & 40% brown and, good bleeding
18	oil sand	857 brown sand, good bleeding
10	oil sand	867 grey, ok bleeding
34	shale	901
1	coal	902
1	shale	903
1	lime	904 Mississippi TD

Drilled a 9 7/8" hole to 21.2'

Drilled a 5 5/8" hole to 904'

Set 21.2' of 7" threaded and coupled surface casing, cemented with 6 sacks cement.

Set 896.2' of 2 7/8" 8 round upset tubing with 4 centralizers, 1 float shoe, 1 clamp, 1 baffle