



11 Lewis Drive

Paola, KS 66071

Oil & Gas Well Drilling
Water Wells
Geo-Loop Installation

Phone: 913-557-9083

Fax: 913-557-9084

WELL LOG

Verde Oil Company
Campbell #I-8-12
API #15-001-30,748
July 15- July 16, 2013

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
5	soil & clay	5
54	lime	59
4	shale	63
2	lime	65
19	shale	84
19	lime	103 oil show
1	shale	104
32	lime	136
1	shale	137
21	lime	158 base of the Kansas City
98	shale	256
6	lime	262
31	shale	293
4	lime	297
16	shale	313
15	lime	328
22	shale	350
2	lime	352
43	shale	395
11	lime	406
9	shale	415
2	lime	417
6	shale	423
10	lime	433
4	shale	437
8	lime	445
1	coal	446
38	shale	484
15	lime	499 oil show
66	shale	565
3	lime	568
38	shale	606
1	lime	607
86	shale	693
1	lime	694
10	shale	704
2	lime	706
10	shale	716
1	oil sand	717 brown sand, ok bleeding
3	broken sand	720 brown & grey, ok bleeding

1	shale	721
1	oil sand	722 brown sand, ok bleeding
2	broken sand	724 80% brown sand 20% shale, ok bleeding
4	oil sand	728 brown, good bleeding & saturation
1	coal	729
39	shale	768
7	limey sand	775 limey sand & shale, no oil
11	broken sand	786 light brown sand & shale, no oil
10	broken sand	796 light brown sand & shale light show
2	shale	798
7	broken sand	805 light brown & shale, no show
2	silty shale	807
1	broken sand	808 light brown & shale, no show
2	silty shale	810
1	broken sand	811 brown sand & shale, good bleeding
3	oil sand	814 soft brown sand, good bleeding
1	broken sand	815 black shale & sand, good bleeding
23	oil sand	838 soft brown sand, good bleeding
6	oil sand	844 brown & black sand, good bleeding
18	oil sand	862 black & grey, good bleeding
40	shale	902 Mississippi TD

Drilled a 9 7/8" hole to 21.9'

Drilled a 5 5/8" hole to 902'

Set 21.9' of 7" threaded and coupled surface casing, cemented with 6 sacks cement.

Set 893.65' of 2 7/8" 8 round upset tubing with 4 centralizers, 1 float shoe, 1 clamp, 1 baffle