



11 Lewis Drive

Paola, KS 66071

Oil & Gas Well Drilling  
Water Wells  
Geo-Loop Installation

Phone: 913-557-9083

Fax: 913-557-9084

**WELL LOG**

Verde Oil Company  
Campbell #I-85-75  
API #15-001-30,740  
June 28 - July 1, 2013

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
6	soil & clay	6
24	lime	30
2	shale	32
24	lime	56
4	shale	60 making water
1	lime	61
16	shale	77
20	lime	97
3	shale	100
6	lime	106
3	shale	109
21	lime	130
2	shale	132
20	lime	152 base of the Kansas City
100	shale	252
5	lime	257 light oil show
33	shale	290
2	lime	292
18	shale	310
3	lime	313
4	shale	317
9	lime	326
22	shale	348
1	lime	349
31	shale	380
1	lime	381
34	shale	415
2	lime	417
1	coal	418
5	shale	423
13	lime	436
1	shale	437
6	lime	443
5	shale	448
1	lime	449
36	shale	485
15	lime	500
9	shale	509

5	lime	514
46	shale	560
4	lime	564
41	shale	605
1	lime	606
3	shale	609
1	coal	610
35	shale	645
1	coal	646
14	shale	660
4	silty shale	664
55	shale	719
3	sand	722 black sand, no show
8	silty shale	730
1	coal	731
59	shale	790
1	sand	791 light brown, no oil
5	shale	796
1	broken sand	797 brown & shale, light bleeding
1	shale	798
2	oil sand	800 brown, good bleeding
17	silty shale	817
14	oil sand	831 brown sand, good bleeding
0.5	coal	831.5
4.5	oil sand	836 brown sand, good bleeding
3	broken sand	839 brown & grey, good bleeding
20	oil sand	859 grey, good saturaton & bleeding
43	silty shale	902
1	lime	903 Mississippi
		903 TD

Drilled a 9 7/8" hole to 22.4'

Drilled a 5 5/8" hole to 903'

Set 22.4' of 6 5/8" threaded and coupled surface casing, cemented with 6 sacks cement.

Set 888.4' of use 2 7/8" 8 round upset tubing including 4 centralizers, 1 float shoe, 1 baffle and 1 clamp.