



11 Lewis Drive

Paola, KS 66071

**Oil & Gas Well Drilling
Water Wells
Geo-Loop Installation**

Phone: 913-557-9083

Fax: 913-557-9084

WELL LOG

Verde Oil Company
Campbell #I-85-115
API #15-001-30,742
July 8-July 9, 2013

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
6	soil & clay	6
33	lime	39
1	shale	40
23	lime	63
3	shale	66
2	lime	68
17	shale	85
54	lime	139
1	shale	140
23	lime	163 base of the Kansas City, oil show
97	shale	260
3	lime	263
36	shale	299
6	lime	305
13	shale	318
3	lime	321
3	shale	324
11	lime	335
23	shale	358
3	lime	361
62	shale	423
4	lime	427
3	shale	430
20	lime	450
43	shale	493
7	lime	500
3	shale	503
4	lime	507
13	shale	520
1	lime	521
9	shale	530
1	lime	531
85	shale	616
1	coal	617
4	shale	621
3	lime	624
10	shale	634
1	coal	635
8	shale	643

1	coal	644
77	shale	721
2	broken sand	723 grey & brown, light bleeding
2	oil sand	725 brown sand, good saturation & bleeding
3	broken sand	728 brown & grey sand, ok bleeding
1	shale	729
3	oil sand	732 few thin grey sand seams, good bleeding
1	oil sand	733 black, good bleeding
3	broken sand	736 brown & black sand in shale, good bleeding
2	silty shale	738
1	coal	739
65	shale	804
16	broken sand	820 light brown sand & shale
1	shale	821
2	broken sand	823 brown sand & shale
18	oil sand	841 brown sand, good bleeding
8	oil sand	849 brown & black, good bleeding
7	shale	856
7	oil sand	863 grey & black
1	silty shale	864
12	oil sand	876 grey & black
27	shale	903
1	coal	904
4	shale	908 Mississippi TD

Drilled a 9 7/8" hole to 22.4'

Drilled a 5 5/8" hole to 908'

Set 22.4' of 7" threaded and coupled surface casing, cemented with 6 sacks cement.

Set 895.4' of use 2 7/8" 8 round upset tubing including 4 centralizers, 1 float shoe, 1 baffle, 1 clamp.