

Lease Name: Cantrell	Spud Date: 9/18/2013	Surface Pipe Size: 7"	Depth: 40'	TD: 1088
Operator: Ron-Bob Oil	Well #12	Bit Diameter: 5 7/8"		
Footage taken	Sample type			
0_3	soil			
3_146	shale			
146_220	lime			
220_243	shale			
243_435	lime			
435_505	shale			
505_639	lime			
639_801	shale			
801_807	lime			
807_822	shale			
822_840	lime			
840_895	shale			
895_902	lime			
902_912	shale			
912_917	lime			
917_960	soft lime			
960_965	black shale			
965_971	lime			
971_980	mulky			
980_986	broken upper sand oil show			
986_1018	shale			
1018_1019	cap			
1019_1021	broken oil sand			
1021_1027	good oil sand			
1027_1035	oil sand			
1035_1088	shale			
	1088 TD			

Hurricane Services, Inc.  
 3613 A Y Road  
 Madison, KS 66860  
 Office # 620-437-2661  
 Brad Cell # 620-437-6765



Ticket Number 100320  
 Location Madison  
 Foreman Brad Butler

Cement Service ticket

Date	Customer #	Well Name & Number	Sec./Township/Range	County
9-18-13		Cantrell # 12	11-24-16E	Woodson
Customer Ron-Bob Oil		Mailing Address	City State Zip	

Job Type:			Truck #	Driver
Hole Size: 5 7/8"	Casing Size:	Displacement: 6.27 Bbls	201	Kelly
Hole Depth:	Casing Weight:	Displacement PSI: 500	202	Jerry
Bridge Plug:	Tubing: 2 7/8"	Cement Left in Casing: 0'	103	Mark
Packer:	PBTD: 1083'		105	Charlie

Quantity Or Units	Description of Services or Product	Pump charge	
0	Mileage Truck on location	\$3.25/Mile	N/C
116 sacks	Quick Set Cement	17.90	2076.40
200 lbs.	Gel Flush	.30	60.00
4 Hrs.	WATER TRUCK	84.00	336.00
4 Hrs.	WATER TRUCK	84.00	336.00
5000 GAL	WATER	13.00 per 1000	65.00
30 miles	Truck # 290 Witchline Services	1.50 50.00	45.00 N/C
Tons	Bulk Truck > minimum charge	\$1.15/Mile	250.00
2	Plugs 2 7/8" Top Rubber	25.00	50.00
		Subtotal	4008.40
		Sales Tax 7.15%	160.98
		Estimated Total	4169.38

Remarks: Rig up to Tubing, Taped Float shoe at 1083' by wireline. Break circulation with 5 Bbls WATER  
 Pumped 10 Bbl. Gel Flush, circulated Gel around to condition Hole. Mixed SKS Quick Set Cement. Shutdown  
 WASH out Pump & Lines, Release 2-Top Rubber Plugs, Displaced Plugs with 6 1/4 Bbls WATER.  
 Final Pumping @ 500 PSI, Bumped Plugs to 1100 PSI, closed Tubing w/ 1100 PSI  
 Good cement returns with 5 1/2 Bbl. slurry

"Thank you"

Witnessed by Ron  
 Customer Signature





Hurricane Services, Inc.  
 3613 A Y Road  
 Madison, KS 66860  
 620-437-2661

Ticket Number 1132  
 Location \_\_\_\_\_  
 Foreman [Signature] #392

FRAC Service ticket

Date	Customer #	Well Name & Number	Sec./Township/Range	County
9/26/13		CANNON #12		W0
Customer		Mailing Address	City	State Zip
Row 4 BOB ORL				KS

Well Data		Truck #	Driver	Truck #	Driver
Casing Size 2 7/8	Total Depth	303	CLAYTON		
Casing Weight	Plug Depth	144/150	RECK		
Tubing Size	Packer Depth	143/151	MARK		
Tubing Weight	Open Hole	840	SEELY		
Perfs 1024-1034 21		312/311	DAVID		
Break PSI 1500	Max PSI 1500		JUSTIN		
Treat PSI 800-1400	ISIP 500		BRYAN		
Quantity	Acid	Additives Used	Charge		
1	303	Pump Charge			875.00
1000	156	Acid with inhibitor			195.00
1/2		NE-320			11.95
		FSW-4100			
		Iron Stay			
		Clay Stay			
4 3/4		KCL			124.93
2 1/2		Biocide			95.00
7	SP-903	Gel			315.00
1/2	LUB	Breaker			81.00
		Ball Sealers			
		Ball Gun			
9	303	Pump truck Mileage			29.25
		Acid Transport			
1	310	Acid Spotter			300.00
1	312/311	Sand Truck			200.00
9	392	Pickup Mileage			13.80
		80 Vac			
1 1/2		Transport			472.50
10		20/40 Sand			300.00
30		12/20 Sand			960.00
2 1/2		SR-445			67.25
# BOB PAID					Total 4040.88

Remarks: SPOT 100 GAL ON PERFS. RIG UP TEST LINE. LOADS & BREAK. EST RATE 10 BPM @ 800 PUMP 10 GAL PAD. START 10 SICK 20/40. PSE UP 1200 & BROKE 950. START 12/20 PSE 1000. 20 SICK IN PSE 850. 25 SICK IN PSE 1100. 30 SICK IN FLUSH 5 OVER ISIP 500. 145 TOTAL GAL

Customer Signature