



11 Lewis Drive

Paola, KS 66071

**Oil & Gas Well Drilling
Water Wells
Geo-Loop Installation**

Phone: 913-557-9083

Fax: 913-557-9084

WELL LOG

Verde Oil Company
Campbell #85-125
API #15-001-30,738
July 5 - July 8, 2013

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
5	soil & clay	5
28	lime	33
4	shale	37
22	lime	59
4	shale	63
2	lime	65
19	shale	84
27	lime	111
4	shale	115
44	lime	159 base of the Kansas City
95	shale	254
4	lime	258
36	shale	294
2	lime	296
18	shale	314
3	lime	317
3	shale	320
10	lime	330
23	shale	353
2	lime	355
63	shale	418
3	lime	421
1	coal	422
3	shale	425
13	lime	438
4	shale	442
5	lime	447
6	shale	453
1	lime	454
35	shale	489
16	lime	505
82	shale	587
1	coal	588
19	shale	607
1	lime	608
49	shale	657
2	lime	659
62	shale	721
4	broken sand	725 black & green, light bleeding
2	oil sand	727 brown sand, ok bleeding
7	oil sand	734 black sand, light bleeding

1	coal	735
5	silty shale	740
45	shale	785
11	broken sand	796 light brown sand, no oil
10	shale	806
4	broken sand	810 light brown sand, no oil
9	oil sand	819 brown sand, good bleeding
2	broken sand	821 70% brown sand 30% shale, good bleeding
6	oil sand	827 brown, good bleeding
1	broken sand	828 70% brown sand 30% shale, good bleeding
8	oil sand	836 brown sand, good bleeding
2	broken sand	838 80% brown sand 20% shale, good bleeding
1	oil sand	839 brown, good bleeding
15	oil sand	854 black sand, good bleeding
3	oil sand	857 grey & black, ok bleeding
9	shale	866
1	coal	867
32	shale	899
5	lime	904 Mississippi TD

Drilled a 9 7/8" hole to 22.4'

Drilled a 5 5/8" hole to 904'

Set 22.4' of 7" threaded and coupled surface casing, cemented with 6 sacks cement.

Set 882' of use 2 7/8" 8 round upset tubing including 4 centralizers, 1 float shoe, 1 baffle, 1 clamp, and 1 seating nipple.