Confidentiality Requested: Yes No

KANSAS CORPORATION COMMISSION **OIL & GAS CONSERVATION DIVISION**

1194296

Form ACO-1 August 2013 Form must be Typed Form must be Signed All blanks must be Filled

WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

OPERATOR: License #	API No. 15		
Name:	Spot Description:		
Address 1:			
Address 2:	Feet from Dorth / South Line of Section		
City: State: Zip:+	Feet from East / West Line of Section		
Contact Person:	Footages Calculated from Nearest Outside Section Corner:		
Phone: ()			
CONTRACTOR: License #	GPS Location: Lat:, Long:		
Name:	(e.g. xx.xxxx) (e.gxxx.xxxxx)		
Wellsite Geologist:	Datum: NAD27 NAD83 WGS84		
Purchaser:	County:		
Designate Type of Completion:	Lease Name: Well #:		
New Well Re-Entry Workover	Field Name:		
	Producing Formation:		
	Elevation: Ground: Kelly Bushing:		
Gas D&A ENHR SIGW	Total Vertical Depth: Plug Back Total Depth:		
GG GSW Temp. Abd.	Amount of Surface Pipe Set and Cemented at: Feet		
CM (Coal Bed Methane) Cathodic Other (Core, Expl., etc.):	Multiple Stage Cementing Collar Used?		
	If yes, show depth set: Feet		
If Workover/Re-entry: Old Well Info as follows:	If Alternate II completion, cement circulated from:		
Operator:			
Well Name:	feet depth to:w/sx cmt.		
Original Comp. Date: Original Total Depth:			
Deepening Re-perf. Conv. to ENHR Conv. to SWD	Drilling Fluid Management Plan		
Plug Back Conv. to GSW Conv. to Producer	(Data must be collected from the Reserve Pit)		
Commingled Permit #:	Chloride content: ppm Fluid volume: bbls		
Dual Completion Permit #:	Dewatering method used:		
SWD Permit #:	Location of fluid disposal if hauled offsite:		
ENHR Permit #:			
GSW Permit #:	Operator Name:		
	Lease Name: License #:		
Spud Date or Date Reached TD Completion Date or	QuarterSecTwpS. R East West		
Recompletion Date Recompletion Date	County: Permit #:		

AFFIDAVIT

I am the affiant and I hereby certify that all requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Submitted Electronically

KCC Office Use ONLY				
Confidentiality Requested				
Date:				
Confidential Release Date:				
Wireline Log Received				
Geologist Report Received				
UIC Distribution				
ALT I II III Approved by: Date:				

	Page Two	1194296
Operator Name:	Lease Name:	Well #:
Sec TwpS. R East _ West	County:	
INCTRINCTIONS. Changing particulations of formations parastrated	Antoil all agree Bapart all final	conice of drill stome tests giving interval tested, time test

INSTRUCTIONS: Show important tops of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed.

Final Radioactivity Log, Final Logs run to obtain Geophysical Data and Final Electric Logs must be emailed to kcc-well-logs@kcc.ks.gov. Digital electronic log files must be submitted in LAS version 2.0 or newer AND an image file (TIFF or PDF).

Drill Stem Tests Taken (Attach Additional She	eets)	Yes No		-	on (Top), Depth a		Sample
Samples Sent to Geolog	gical Survey	Yes No	Name	9		Тор	Datum
Cores Taken Electric Log Run		☐ Yes ☐ No ☐ Yes ☐ No					
List All E. Logs Run:							
			RECORD New		ion, etc.		
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
		ADDITIONAL	CEMENTING / SQU	EEZE RECORD			
Purpose:	Depth	Tupo of Comont	# Sooka Llood		Type and [Paraant Additivaa	

Purpose: Perforate	Top Bottom	Type of Cement	# Sacks Used	Type and Percent Additives
Protect Casing				
Plug Off Zone				

Did you perform a hydraulic fracturing treatment on this well?	Yes	
Does the volume of the total base fluid of the hydraulic fracturing treatment exceed 350,000	gallons? Yes	
Was the hydraulic fracturing treatment information submitted to the chemical disclosure regis	stry? Yes	

(If No, skip questions 2 and 3) (If No, skip question 3)

No

No No

(If No, fill out Page Three of the ACO-1)

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated				4		ement Squeeze Record d of Material Used)	Depth		
TUBING RECORD:	Size: Set At:			Packer	At:	Liner Ru	un:	No		
Date of First, Resumed	med Production, SWD or ENHR. Producing Method:									
Estimated Production Per 24 Hours		Oil Bbls.		Gas	Mcf	Wate	er	Bbls.	Gas-Oil Ratio	Gravity
DISPOSITI			METHOD OF COMPLETION:		_	PRODUCTION INT	ERVAL:			
Vented Solo	Vented Sold Used on Lease Open Hole Perf. Dually Comp. Commingled									
(If vented, Su	bmit ACO	-18.)	(Submit ACO-5) (Submit ACO-4)							

Form	ACO1 - Well Completion
Operator	SCZ Resources, LLC
Well Name	KENDALL DICE I-5
Doc ID	1194296

Casing

	Size Hole Drilled	Size Casing Set	Weight	Setting Depth	Type Of Cement		Type and Percent Additives
Surface	10	7	10	20	portland	5	
Production	6.25	2.875	8	838	portland	135	50/50 poz

DATED

TICKET NUMBER	
LOCATION_OHa	wa.KS
FOREMAN Carey	Kennedy

PO Box 884, Chanute, KS 66720 620-431-9210 or 800-467-8676

620-431-9210 or 800-467-867	6	CEMEN	Г			
DATE CUSTOMER #	WELL NAME & NUM	BER	SECTION	TOWNSHIP	RANGE	COUNTY
3/11/14 7752	Dice# I-S	5	SERA	26	18	AL
SCZ Resources	LLC	r r	TRUCK #			
MAILING ADDRESS	<u> </u>	-	729	DRIVER		
	De			Casken	12 sately	Heeting_
8614 Cedarspu	STATE ZIP CODE	4 }	<u>lelele</u>	GarMao	V	
		Í l	510	Settic	~	
Houston	1X 77055		JE 675	ATHCD	5	
JOB TYPE longstring	HOLE SIZE	HOLE DEPTH	80'	CASING SIZE &	WEIGHT 2718	EVE
CASING DEPTH	DRILL PIPE	_TUBING			OTHER	
SLURRY WEIGHT		WATER gal/sl	(CEMENT LEFT in		
DISPLACEMENT 4. 15 665	DISPLACEMENT PSI	MIX PSI		RATE 5 50	KA	
REMARKS: Leld safety	meeting establishe	d circular	tion min	dtound	ad 150#	Premium
	bbls fresh water				% Poz	mix
concert w/ 270	elper sk, æine	Let to su	ctace, flu	shed som	o dean	purpod
21/2" rubber duc to				ater, pres		800 PS1.
well hold pressure	for 30 min M	LIT, relea		e, shut i		
	- •	<i>(</i>				

ACCOUNT	QUANITY or UNITS	DESCRIPTION of SERVICES or PRODUCT		TOTAL
5401	1	PUMP CHARGE		100.00
5406	on lease	MILEAGE		
5402	838'	casing tootage		
5407A	348,30	tar mileage		491.10
5502C	ahrs	So lac		20,00
1124	135 Sks	5% 50 Pozurix ceneut		155 2.50
11183	377 #	Fremium Gel		82.94
		norials	subtotal	1635.44
			-30%	490.63
			Subtotal	1144.81
4402	1	2'/2" rubbar plug		29.50
			<u></u>	
				Deill ar
				35101,25
	$\overline{)}$		SALES TAX	86,90
Aavin 3737	- 1/ h.	/	ESTIMATED	
	1. Such		TOTAL	3037.31
AUTHORIZTION			DATE	

I acknowledge that the payment terms, unless specifically amended in writing on the front of the form or in the customer's account records, at our office, and conditions of service on the back of this form are in effect for services identified on this form.

-- --

TERMS

In consideration of the prices to be charged for Consolidated Oil Well Services, LLC (COWS) services, equipment and products and for the performance of services and supplying of materials. Customer agrees to the following terms and conditions.

Terms. Cash in advance unless satisfactory credit is established. On credit sales, invoices are payable within 30 days of the invoice date. On all invoices not paid within 30 days, Customer agrees to pay COWS interest at the rate of 18% per annum or the maximum rate allowed by law, whichever is higher. In the event COWS retains an attorney to pursue collection of any account. Customer agrees to pay all collection costs and attorney's fees incurred by COWS.

Any applicable federal, state or local sales, use occupation, consumer's or emergency taxes shall be added to the quoted price. All process license fees required to be paid to others will be added to the scheduled prices.

All COWS' prices are subject to change without notice.

SERVICE CONDITIONS

Customer warrants that the well is in proper condition to receive the services, equipment, products and materials to be supplied by COWS. The Customer shall at all time have complete care, custody, and control of the well, the drilling and production equipment at the well, and the premises about the well. A responsible representative of the Customer shall be present to specify depths, pressures, or materials used for any service which is to be performed.

(a) COWS shall not be responsible for any claim, cause of action or demand (hereinafter referred to as a 'claim') for damage to property, or injury to or death of employees and representatives, of Customer or the well owner (if different from Customer), unless such damage, injury or death is caused by the willful misconduct or gross negligence of COWS, including but not limited to sub-surface damage and surface damage arising from sub-surface damage.

(b) Unless a claim is the result of the sole willful misconduct or gross negligence of COWS, Customer shall be responsible for and indemnify and hold COWS harmless from any claim for: (1) reservoir loss or damage, or property damage resulting from sub-surface pressure, losing control of the well and/or a well blowout; (2) damages as a result of a subsurface trespass, or an action in the nature thereof, arising from a service operation performed by COWS; (3) injury to or death of persons, other than employees of COWS, or damage to property (including, but not limited to, injury to the well), or any damages whatsoever, irrespective of cause, growing out of or in any way connected with the use of radioactive material in the well hole; and (4) well damage or reservoir damage caused by (i) loss of circulation, cement invasion, cement misplacement, pumping cement or cement plugs on wells with loss of circulation. including the failure to displace plug to proper depth, (ii) subsurface pressure and resulting failure to complete pumping of cement or cement plug, including dehydration of cement slurry or flashing, plugged float shoe, annulus bridging or plugging, or (iii) down hole tools being lost or left in the well, or becoming stuck in the well for any reason and by any cause. COWS may furnish down hole tools and may supply supervision for the running and placement of such tools but will not be liable for any damage, loss or result caused by the use of such tools.

Furthermore. Customer will be responsible for the cost to replace such tools if they are lost or left in the well.

(c) COWS makes no guarantee of the effectiveness of any COWS products, supplies or materials, or the results of any COWS' treatment or services.

(d) Because of the uncertainty of variable well conditions and the necessity of relying on facts and supporting services furnished by others, COWS is unable to guarantee the accuracy of any chart interpretation, research analysis, job recommendation or other data furnished by COWS. COWS' personnel will use their best efforts in gathering such information and their best judgement in interpreting it, but Customer agrees that COWS shall not be responsible for any damage arising from the use of such information except where due to COWS' gross negligence or willful misconduct in the preparation or furnishing of it.

(c) COWS may buy and re-sell to Customer down hole equipment, including but not limited to float equipment, DV tools, port collars, type A & B packers, and Customer agrees that COWS is not an agent or dealer for the companies who manufacture such items, and further agrees that Customer shall be solely responsible for and indemnify COWS against any claim with regard to the effectiveness, malfunction of, or functionality of such items.

WARRANTIES - LIMITATION OF LIABILITY

COWS warrants title to the products, supplies and materials, and that the same are free from defects in workmanship and materials. THERE ARE NO OTHER WARRANTIES, EXPRESS OR IMPLIED, NOR ANY WARRANTY OF MERCHANTABILITY OR FUNESS FOR PURPOSE. WHICH EXTEND BEYOND THOSE STATED IN THE IMMEDIATELY PRECEDING SENTENCE. COWS's liability and Customer's exclusive remedy in any claim (whether in contract, tort, breach of warranty or otherwise.) arising out of athe sale or use of any COWS' products, supplies, materials or services is expressly limited to the replacement of such products, supplies, materials or services or their return to COWS or, at COWS' option, an allowance to Customer of credit for the leost of such items.

Customer waives and releases all claims against COWS for any special, incidental, indirect, consequential or punitive damages.

1.0. or pipe 848 Surface pipe dept 20' Count Well Type Injection Driller's Log Thickness Strata From To 7 dirt 0 7 33 lime 7 40 21 shale 40 61 14 lime 61 75 46 shale 75 121 74 lime 121 195 5 shale 195 200 21 lime 200 221 5 shale 251 256 17 lime 256 273 142 shale 273 415 5 lime/shale mix 415 420 10 shale 430 435 4 shale 433 488 5 lime 430 435 4 shale 433 488 5 top sand 458 460 2 top sand		Operator License # Operator Address City Contractor Contractor License # T.D.	34897 SCZ Resources 8614 Cedarspur Drive Houston, TX 77055 JTC Oil, Inc. 32834 880		API # Lease Well # Spud Ceme Locat
Driller's Log Thickness Strata From To 7 dirt 0 7 33 lime 7 40 21 shale 40 61 14 lime 61 75 46 shale 75 121 74 lime 121 195 5 shale 195 200 21 lime 200 221 5 shale 251 256 17 lime 256 273 142 shale 273 415 5 lime/shale mix 415 420 10 shale 430 435 4 shale 435 439 9 lime 439 448 5 top sand 453 458 2 top sand 453 458 10 sand/shale 463 473		Surface pipe depth	20'		Count
ThicknessStrataFromTo7dirt0733lime74021shale406114lime617546shale7512174lime1211955shale19520021lime2262515shale25125617lime256273142shale2734155lime/shale mix41542010shale4204305lime4304354shale4354399lime4394485shale4484535top sand453458ok2top sand4604621end4624631end46246310sand/shale46347377shale55056338shale56360116lime6016178shale625628148shale6287762top sand7787802top sand7787802top sand7787802top sand7787802top sand7787802top sand7767783lime628776 <td></td> <td></td> <td></td> <td></td> <td></td>					
7 dirt 0 7 33 lime 7 40 21 shale 40 61 14 lime 61 75 46 shale 75 121 74 lime 121 195 5 shale 195 200 21 lime 200 221 5 shale 221 226 25 lime 226 251 5 shale 273 415 5 shale 273 415 5 lime/shale mix 415 420 10 shale 420 430 5 lime 430 435 4 shale 435 439 9 lime 439 448 5 shale 448 453 5 top sand 453 458 6 top sand 453 460 1 end 462 463 10 s	Thickness		-	То	
33 lime 7 40 21 shale 40 61 14 lime 61 75 46 shale 75 121 74 lime 121 195 5 shale 195 200 21 lime 200 221 5 shale 251 226 25 lime 226 251 5 shale 273 415 5 lime/shale mix 415 420 10 shale 273 445 5 lime/shale mix 415 420 10 shale 430 435 4 shale 433 439 9 lime 439 448 5 shale 448 453 5 top sand 458 460 2 top sand 453 473 55 top sand 453 453 1 end 462 463 <td< td=""><td></td><td></td><td></td><td></td><td></td></td<>					
21 shale 40 61 14 lime 61 75 46 shale 75 121 74 lime 121 195 5 shale 195 200 21 lime 200 221 5 shale 221 226 25 lime 226 251 5 shale 251 256 17 lime 256 273 142 shale 430 435 5 lime/shale mix 415 420 10 shale 430 435 4 shale 435 439 9 lime 430 448 5 shale 448 453 5 top sand 453 458 ok 2 top sand 453 453 ok 2 top sand 463 473 550 13 lime 553 601 1617 8 shale<					
14 lime 61 75 46 shale 75 121 74 lime 121 195 5 shale 195 200 21 lime 200 221 5 shale 221 226 25 lime 226 251 5 shale 251 256 17 lime 256 273 142 shale 415 420 10 shale 420 430 5 lime/shale mix 415 420 10 shale 433 435 4 shale 433 448 5 shale 448 453 5 top sand 453 458 ok 2 top sand 453 458 ok 2 top sand 453 453 55 13 lime 550 563 601 14 end 462 463 473 550		-			
46 shale 75 121 74 lime 121 195 5 shale 195 200 21 lime 200 221 5 shale 221 226 25 lime 226 251 5 shale 251 256 17 lime 256 273 142 shale 415 420 10 shale 420 430 5 lime/shale mix 415 420 10 shale 433 435 4 shale 435 439 9 lime 439 448 5 shale 448 453 5 top sand 453 458 2 top sand 453 451 1 end 462 463 10 sand/shale 473 550 13 lime 550 563 38 shale 617 625 148					
74 lime 121 195 5 shale 195 200 21 lime 200 221 5 shale 221 226 25 lime 226 251 5 shale 251 256 17 lime 256 273 142 shale 273 415 5 lime/shale mix 415 420 10 shale 420 430 5 lime 430 435 4 shale 435 439 9 lime 439 448 5 shale 448 453 5 top sand 453 458 ok 2 top sand 460 462 1 end 462 463 10 sand/shale 463 473 77 shale 550 563 3 lime 625 628 148 shale 617 625		-			
5 shale 195 200 21 lime 200 221 5 shale 221 226 25 lime 226 251 5 shale 251 256 17 lime 256 273 142 shale 273 415 5 lime/shale mix 415 420 10 shale 420 430 5 lime 430 435 4 shale 435 439 9 lime 439 448 5 shale 448 453 5 top sand 458 460 2 top sand 458 460 1 end 462 463 10 sand/shale 463 473 77 shale 473 550 13 lime 553 601 16 lime 601 617 17 shale 625 628 <t< td=""><td>-</td><td></td><td></td><td></td><td></td></t<>	-				
21 lime 200 221 5 shale 221 226 25 lime 226 251 5 shale 251 256 17 lime 256 273 142 shale 273 415 5 lime/shale mix 415 420 10 shale 420 430 5 lime 430 435 4 shale 435 439 9 lime 439 448 5 shale 448 453 5 top sand 453 458 ok 2 top sand 453 453 453 10 sand/shale 463 473 550 11 end 462 463 473 177 shale 550 563 601 13 lime 550 563 601 16 lime 601 617 625 3 lime 625 <td< td=""><td></td><td></td><td></td><td></td><td></td></td<>					
5 shale 221 226 25 lime 226 251 5 shale 251 256 17 lime 256 273 142 shale 273 415 5 lime/shale mix 415 420 10 shale 420 430 5 lime 430 435 4 shale 435 439 9 lime 439 448 5 shale 448 453 5 top sand 458 460 2 top sand 463 473 10 sand/shale 463 473 11 end 462 463 12 top sand 463 473 13 lime 550 563 13 lime 550 563 148 shale 617 625 3 lime 625 628 148 shale 628 776					
25 lime 226 251 5 shale 251 256 17 lime 256 273 142 shale 273 415 5 lime/shale mix 415 420 10 shale 420 430 5 lime 430 435 4 shale 435 439 9 lime 439 448 5 shale 448 453 5 top sand 453 458 ok 2 top sand 460 462 463 10 sand/shale 463 473 550 13 lime 550 563 601 14 end 462 463 473 77 shale 570 563 601 13 lime 550 563 601 16 lime 601 617 625 3 lime 625 628 776 2 to					
5 shale 251 256 17 lime 256 273 142 shale 273 415 5 lime/shale mix 415 420 10 shale 420 430 5 lime 430 435 4 shale 435 439 9 lime 439 448 5 shale 448 453 5 top sand 453 458 ok 2 top sand 460 462 463 10 sand/shale 463 473 550 13 lime 550 563 601 14 end 462 463 473 777 shale 473 550 563 13 lime 563 601 601 16 lime 601 617 625 3 lime 625 628 776 2 top sand 776 778 ok <					
17 lime 256 273 142 shale 273 415 5 lime/shale mix 415 420 10 shale 420 430 5 lime 430 435 4 shale 435 439 9 lime 439 448 5 shale 448 453 5 top sand 453 458 ok 2 top sand 453 460 462 1 end 462 463 473 10 sand/shale 463 473 550 11 end 462 463 473 77 shale 473 550 563 13 lime 553 601 601 16 lime 601 617 625 3 lime 625 628 776 2 top sand 776 778 ok 2 top sand 780 780 780 <td></td> <td></td> <td></td> <td></td> <td></td>					
142 shale 273 415 5 lime/shale mix 415 420 10 shale 420 430 5 lime 430 435 4 shale 435 439 9 lime 439 448 5 shale 448 453 5 top sand 453 458 2 top sand 458 460 2 top sand 463 473 10 sand/shale 463 473 11 end 462 463 10 sand/shale 463 473 77 shale 473 550 13 lime 563 601 16 lime 601 617 2 top sand 776 778 3 lime 625 628 148 shale 617 625 3 lime 628 776 2 top sand 778 780					
5 lime/shale mix 415 420 10 shale 420 430 5 lime 430 435 4 shale 435 439 9 lime 439 448 5 shale 448 453 5 top sand 458 460 2 top sand 463 473 10 sand/shale 463 473 10 sand/shale 463 473 10 sand/shale 463 473 77 shale 550 563 13 lime 550 563 13 lime 625 628 148 shale 617 625 3 lime 625 628 148 shale 628 776 2 top sand 776 778 ok 2 top sand 780 782 783					
10 shale 420 430 5 lime 430 435 4 shale 435 439 9 lime 439 448 5 shale 448 453 5 top sand 453 458 ok 2 top sand 458 460 462 1 end 462 463 473 10 sand/shale 463 473 550 13 lime 550 563 601 16 lime 601 617 625 3 lime 625 628 148 148 shale 625 628 148 148 shale 628 776 2 2 top sand 776 778 ok 2 top sand 780 782 1 2 top sand 780 782 1 end/shale 783 803 3 shale/sand 803 806 875					
5 lime 430 435 4 shale 435 439 9 lime 439 448 5 shale 448 453 5 top sand 453 458 ok 2 top sand 458 460 462 1 end 462 463 473 10 sand/shale 463 473 550 13 lime 550 563 563 38 shale 563 601 617 8 shale 617 625 628 148 shale 625 628 776 2 top sand 776 778 ok 2 top sand 776 778 ok 148 shale 628 776 78 2 top sand 780 780 2 2 top sand 780 780 783 2 top sand 783 803 33 3 s		-			
4 shale 435 439 9 lime 439 448 5 shale 448 453 5 top sand 453 458 ok 2 top sand 458 460 462 1 end 462 463 473 10 sand/shale 463 473 550 13 lime 550 563 563 13 lime 601 617 625 3 shale 617 625 628 148 shale 628 776 778 ok 2 top sand 776 778 ok 780 781 2 top sand 776 778 ok 782 783 0k 2 top sand 780 782 783 783 782 783 783 783 783 783 783 783 783 783 783 783 783 783 783 783 783 783 783 </td <td></td> <td></td> <td></td> <td></td> <td></td>					
9 lime 439 448 5 shale 448 453 5 top sand 453 458 ok 2 top sand 458 460 462 1 end 462 463 473 10 sand/shale 463 473 550 13 lime 550 563 563 16 lime 601 617 625 3 lime 625 628 776 2 top sand 776 778 ok 16 lime 625 628 776 3 lime 625 628 776 2 top sand 778 780 782 2 top sand 776 778 ok 2 top sand 780 782 783 20 shale 783 803 303 306 little 69 <td< td=""><td></td><td>-</td><td></td><td></td><td></td></td<>		-			
5 shale 448 453 5 top sand 453 458 ok 2 top sand 458 460 462 2 top sand 460 462 463 1 end 462 463 473 10 sand/shale 463 473 550 13 lime 550 563 563 16 lime 601 617 625 3 shale 617 625 628 148 shale 628 776 778 ok 2 top sand 776 778 ok 776 778 ok 2 top sand 778 780 782 783 780 782 783 784					
5 top sand 453 458 ok 2 top sand 458 460 462 1 end 460 462 463 10 sand/shale 463 473 50 10 sand/shale 463 473 550 13 lime 550 563 601 16 lime 601 617 625 3 lime 625 628 76 2 top sand 776 778 ok 16 lime 625 628 76 3 lime 625 628 776 2 top sand 776 778 ok 2 top sand 780 782 1 2 top sand 783 803 3 20 shale 783 803 3 3 shale/sand 803 806 litttle 69					
2 top sand 458 460 2 top sand 460 462 1 end 462 463 10 sand/shale 463 473 77 shale 473 550 13 lime 550 563 38 shale 563 601 16 lime 601 617 8 shale 625 628 148 shale 628 776 2 top sand 778 0k 2 top sand 778 780 2 top sand 780 782 1 end/shale 783 803 20 shale 783 803 3 shale/sand 803 806 69 shale 806 875					ok
2 top sand 460 462 1 end 462 463 10 sand/shale 463 473 10 sand/shale 463 473 10 sand/shale 463 473 11 end 463 473 10 sand/shale 463 473 11 lime 550 563 13 lime 553 601 16 lime 601 617 16 lime 625 628 148 shale 628 776 2 top sand 776 778 ok 2 top sand 778 780 780 2 top sand 780 782 783 20 shale 783 803 803 3 shale/sand 803 806 little 69 shale 806 875 1		·			
1 end 462 463 10 sand/shale 463 473 77 shale 473 550 13 lime 550 563 38 shale 563 601 16 lime 601 617 8 shale 617 625 3 lime 625 628 148 shale 628 776 2 top sand 776 778 ok 2 top sand 778 780 780 2 top sand 778 783 383 3 shale 783 803 803 3 shale/sand 803 806 little 69 shale 806 875 114		-			
10 sand/shale 463 473 77 shale 473 550 13 lime 550 563 38 shale 563 601 16 lime 601 617 8 shale 617 625 3 lime 625 628 148 shale 628 776 2 top sand 776 778 ok 2 top sand 780 782 1 2 top sand 780 782 1 2 top sand 783 803 803 3 shale/sand 803 806 little 69 shale 806 875 1					
77shale47355013lime55056338shale56360116lime6016178shale6176253lime625628148shale6287762top sand776778ok2top sand7787802top sand7807821end/shale7838033shale/sand803806little69shale80687511	10	sand/shale			
38 shale 563 601 16 lime 601 617 8 shale 617 625 3 lime 625 628 148 shale 628 776 2 top sand 776 778 ok 2 top sand 778 780 782 1 end/shale 783 803 803 3 shale/sand 803 806 little 69 shale 806 875 little	77	shale	473	550	
16 lime 601 617 8 shale 617 625 3 lime 625 628 148 shale 628 776 2 top sand 776 778 ok 2 top sand 780 780 782 1 end/shale 782 783 783 20 shale 783 803 803 3 shale/sand 803 806 little 69 shale 806 875 11	13	lime	550	563	
8 shale 617 625 3 lime 625 628 148 shale 628 776 2 top sand 776 778 ok 2 top sand 776 780 780 2 top sand 780 782 783 1 end/shale 782 783 803 20 shale 783 803 806 little 69 shale 806 875 111 </td <td>38</td> <td>shale</td> <td>563</td> <td>601</td> <td></td>	38	shale	563	601	
3 lime 625 628 148 shale 628 776 2 top sand 776 778 ok 2 top sand 776 778 ok 2 top sand 778 780 782 1 end/shale 782 783 20 shale 783 803 3 shale/sand 803 806 little 69 shale 806 875 111	16	lime	601	617	
148shale6287762top sand776778ok2top sand7787807802top sand7807827831end/shale78278380320shale7838038063shale/sand803806little69shale806875100	8	shale	617	625	
2 top sand 776 778 ok 2 top sand 778 780 2 top sand 780 782 1 end/shale 782 783 20 shale 783 803 3 shale/sand 803 806 little 69 shale 806 875	3	lime	625	628	
2 top sand 778 780 2 top sand 780 782 1 end/shale 782 783 20 shale 783 803 3 shale/sand 803 806 little 69 shale 806 875	148	shale	628	776	
2 top sand 780 782 1 end/shale 782 783 20 shale 783 803 3 shale/sand 803 806 little 69 shale 806 875	2	top sand	776	778	ok
1 end/shale 782 783 20 shale 783 803 3 shale/sand 803 806 little 69 shale 806 875	2	top sand	778	780	
20 shale 783 803 3 shale/sand 803 806 little 69 shale 806 875	2	top sand	780	782	
3 shale/sand 803 806 little 69 shale 806 875				783	
69 shale 806 875					
		shale/sand		806	little
3 sand 875 878					
	3	sand	875	878	

API # Lease Name Well #		15-001-3085 Kendall Dice I-5	4-00-00	
Spud Date Cement Da		3/6/14		
Location		Sec 27	T 26	R 18
	330	feet from	Ν	line
	2310	feet from	W	line
County		Allen		