



Oil & Gas Well Drilling  
Water Wells  
Geo-Loop Installation

Phone: 913-557-9083

Fax: 913-557-9084

11 Lewis Drive

Paola, KS 66071

**WELL LOG**

SCZ Resources, LLC

Cannon #C-4

API #15-001-30906

March 5 - March 6, 2014

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
6	soil & clay	6
37	lime	43
25	shale	68
20	lime	88
23	shale	111 oil show
75	lime	186 with a few shale seams
7	shale	193
20	lime	213
5	shale	218
27	lime	245
4	shale	249
26	lime	275 base of Kansas City
150	shale	425
8	lime	433
8	shale	441
4	broken sand	445 brown & green ok bleeding
4	silty shale	449
4	sand	453 green no oil
34	shale	487
8	sand	495 grey no oil
30	shale	525
1	coal	526
3	shale	529
10	lime	539 brown
4	shale	543
5	lime	548
1	coal	549
36	shale	585
15	lime	600 oil show
9	shale	609
3	lime	612
4	shale	616
4	sand	620 green no oil
79	shale	699
3	lime	702
50	shale	752
5	broken sand	757 brown & green, ok bleeding
1	shale	758

7	broken sand	765 brown & green, ok bleeding
14	shale	779
6	oil sand	785 brown ok bleeding
3	broken sand	788 brown & grey ok bleeding
26	shale	814
4	broken sand	818 brown & white, ok bleeding
2	oil sand	820
3	broken sand	823 brown & white, good bleeding
2	oil sand	825 brown good bleeding
1	coal	826
29	shale	855
6	broken sand	861 brown & grey
3	oil sand	864 brown ok bleeding
1	broken sand	865 brown & grey good bleeding
8	oil sand	873 brown good bleeding
67	sand	940 brown no oil show making water 940 TD

Drilled a 9 7/8" hole to 22.4'

Drilled a 6 1/8" hole to 940'

Set 22.4' of 7" surface casing, cemented with 5 sacks cement.

Set 914' of 2 7/8" 8 round upset tubing including 2 centralizers, 1 float shoe, and 1 clamp.