



11 Lewis Drive

Paola, KS 66071

Oil & Gas Well Drilling
Water Wells
Geo-Loop Installation

Phone: 913-557-9083

Fax: 913-557-9084

WELL LOG

SCZ Resources, LLC

Cannon #C-5

API #15-001-30902

March 4 - March 5, 2014

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
2	soil & clay	2
35	lime	37
29	shale	66
18	lime	84
19	shale	103 oil show
10	lime	113
10	shale	123
4	lime	127
4	shale	131
55	lime	186
9	shale	195
19	lime	214
4	shale	218
27	lime	245
5	shale	250
18	lime	268 base of Kansas City
162	shale	430
5	lime	435
1	shale	436
1	coal	437
12	lime	449
30	shale	479
10	sand	489 grey, no oil
43	shale	532
1	coal	533
3	shale	536
13	lime	549
2	shale	551
5	lime	556
2	shale	558
1	coal	559
34	shale	593
16	lime	609
102	shale	711
2	lime	713
30	shale	743
1	coal	744
15	shale	759

10	broken sand	769	brown & green, light bleeding
6	shale	775	
4	broken sand	779	brown & grey, light bleeding
10	shale	789	
1	coal	790	
8	shale	798	
4	broken sand	802	
2	shale	804	
3	broken sand	807	brown & grey, good bleeding
4	shale	811	
3	oil sand	814	brown, good bleeding
1	broken sand	815	brown & grey good bleeding
8	oil sand	823	brown, good bleeding
1	limey sand	824	
2	oil sand	826	brown, good bleeding
3	silty shale	829	
1	broken sand	830	brown & grey, ok bleeding
12	oil sand	842	brown, good bleeding
1	coal	843	
38	shale	881	
4	broken oil sand	885	brown & grey, ok bleeding
3	oil sand	888	brown, ok bleeding
29	sand	917	light brown
3	silty shale	920	
20	sand	940	grey & brown, no oil
			940 TD

Drilled a 9 7/8" hole to 20.1'

Drilled a 6 1/8" hole to 940'

Set 20.1' of 7" surface casing, cemented with 5 sacks cement.

Set 912.4' of 2 7/8" 8 round upset tubing including 2 centralizers, 1 float shoe, 1 baffle, and 1 clamp.