Glassman Consulting

API 15-163-24167-00-00

GEOLOGIST'S REPORT
DRILLING TIME AND SAMPLE LOG

OPERATOR: BOWMAN OIL COMPANY
LEASE: BHB WELL NO. #1
FIELD: TODD SOUTHEAST
LOCATION: 2970' FSL & 1315' FWL
SEC. 5 TWP. 7S RGE. 20W
COUNTY: ROOKS STATE: KANSAS

ELEVATION
KB: 2211
DF:
GL: 2206
Measurements Are All From: KELLY BUSHING

CONTRACTOR: WHITE KNIGHT DRILLING LLC
COMM: COMP: 12-23-2013
RTD: 3690 LOG TD: 3691
SAMPLES SAVED FROM 3100 TO T.D.
DRILLING TIME KEPT FROM 3000 TO T.D.
SAMPLES EXAMINED FROM 3100 TO T.D
GEOLOGICAL SUPERVISION FROM 3000 TO T.D.
MUD UP 3050 TYPE MUD CHEMICAL-DRISPAC

CASING RECORD
SURFACE 8 5/8" @ 221'
150 sxs, 3% CC, 2% Gel
PRODUCTION 5 1/2" @ 3684'
DV Tool @ 2204'
150 sxs EA2 / 370 sxs SMD

ELECTRICAL SURVEYS
DUAL INDUCTION
DENSITY NEUTRON
MICRO

FORMATION	LOG TOP	LOG DATUM	SAMPLE TOP	SAMPLE DATUM	STRUCT. COMP.
ANHYDRITE	1798	(413)	1797	(414)	
B/ANHYDRITE	1831	(380)	1842	(369)	
TOPEKA	3188	(-977)	3184	(-973)	
HEEBNER	3395	(-1184)	3394	(-1183)	
LANSING	3431	(-1220)	3428	(-1217)	
B/KANSAS CITY	3620	(-1409)	3619	(-1408)	
ARBUCKLE	3656	(-1445)	3657	(-1446)	



REFERENCE WELL FOR STRUCTURAL COMPARISON: BOWMAN OIL COMPANY LUNNEY / SCHUCK SE #1, SEC. 31-6S-20W; 400' FSL & 1925' FEL. ROOKS COUNTY KANSAS

DATE	DEPTH
12-17-13	225
12-18-13	297
12-19-13	1181
12-20-13	2285
12-21-13	2974
12-22-13	3687
12-23-13	3690

NO	SIZE	MAKE	TYPE	DEPTH OUT	FEET	HOURS
1	12 1/4	HTC	RR	225	225	5 1/2
2	7 7/8	VBM116	0160803	2315	2090	27
3	7 7/8	HTC GX23	5206912	3690	1375	26

FORMATION	INTERVAL	DESCRIPTION OF SHOW	LOG ANALYSIS

DRILL STEM TESTS

No.	Interval	IFP/Time	ISIP/Time	FFP/Time	FSIP/Time	BHT-FHH	RECOVERY

REMARKS AND RECOMMENDATIONS

LEGEND

Anhydrite, Salt, Sandstone, Shale, Carb sh, Limestone, Ool.Lime, Chert, Dolomite

DRILLING TIME IN MINUTES PER FOOT — Rate of Penetration Decreases — 5" 10" 15" 20" 25"

DEPTH	FORMATION TOPS	SAMPLE DESCRIPTIONS	OIL SHOWS	REMARKS
1780				
1790	ANHYDRITE 1797 (414)			
1800–1840	B/ANHYDRITE 1842 (369)			
3000				Start 1' drlg time
3050				DISPLACE MUD system
3100		SH: gry, med, blky.		start 10' wet/dry smpls.
3120	HOWARD LS	LS: tan, f-med xln, inter xln Ø, NS.		
3140		SH: gry-dk gry, med plty.		
3150		LS: tan, f-med xln, fos, inter xln-frag Ø, NS.		GEO on loc. @ 3:45 pm 12-21-2013
3160		SH: gry, rough		
3170	SEVERY SHALE	SH: gry, f, med, plty.		
3180	TOPEKA 3184 (-973)	LS: tan-lt gry, f-med xln, mottld, fos, inter xln-frag Ø, NS.		
3200		LS: lt gry, f-med xln, inter xln Ø, NS.		
3210		SH: gry, med, plty.		
3220		LS: tan-lt gry, f-med xln, inter xln Ø, NS.		
3240		SH: dk gry, med, rough, blky.		
3250		LS: tan-lt gry, f-med xln, inter xln Ø, NS.		
3260		SH: gry		VIS 51 Wt 8.9 LCM 2#
3260		LS: lt gry-dk gry, oolitic, inter xln-ool Ø, NS.		
3280		SH: brn		
3290	KING HILL	SH: blk, carb		
3290		SH: dk brn-blk, f, med, blky.		
3310		LS: gry-dk gry, f-med xln, inter xln Ø, NS.		
3330		SH: gry, sme vari clrd, pyrite xls, plty		
3340	QUEEN HILL	SH: blk carb		
3340		LS: lt gry-gry, f-med xln, inter xln Ø, NS		VIS 52 Wt 9.0 LCM 2#
3370		LS: tan, f-med xln, inter xln Ø, SSFO, sli odor, dk spty stn.	•	
3380		LS: tan-lt gry, f-med xln, inter xln Ø, FSFO, Fr odor, dk spty stn, oolitic.	•	
3390	HEEBNER 3394 (-1183)	SH: blk, carb		
3400		SH: gry-dk gry, f, med, plty.		
3410	TORONTO 3413 (-1202)	LS: tan, f-med xln, inter xln Ø, sli chlky. NS.		
3420	LANSING 3428 (-1217)	SH: gry-dk brn.		
3430		LS: tan, f-med xln, sli chlky, sme chert, f-med, inter xln Ø, VSSFO, Fr odor, mostn.	•	
3440		LS: tan, f-med xln, inter xln Ø, chlky, NS.		
3460		SH: lt brn-brn, f, med plty.		
3480		LS: tan, f-med xln, oolitic, gd inter xln-vuggy Ø, FSFO, sli odor, lt brn spty stn-uneven.	•	
3490		LS: tan-lt brn, f-med xln, inter xln Ø, SSFO, sli odor, dk even stn.	•	VIS 54 Wt 9.1
3500		SH: vari clrd		
3510		LS: tan, f-med xln, NS.		
3510		SH: vari clrd		
3520		LS: tan, f-med xln, inter xln Ø, NS.		
3540		SH: blk carb.		
3540		SH: vari clrd mstly brn.		
3550		LS: tan, f-med xln, inter xln Ø NS		VIS 55 Wt 9.2
3570		SH: gry, f-med, plty-blky.		
3580		LS: tan, sme clr qtz xls, f-med xln, inter xln Ø, SSFO, sli odor, lt uneven-spty stn.	•	
3590		LS: tan, f-med xln, sli oolitic, inter xln-ool-vuggy Ø, FSFO, sli odor, dk-even-uneven stn.	•	
3600		SH: vari clrd, gry, brn, reddish brn, plty-blky		
3610		SH: gry		
3610	B/KANSAS CITY 3619 (-1408)	LS: tan, NS.		
3620		SH: vari clrd.		
3650		SS: clr, f-med gr, poor sort, calc cmt, clstrs, GSFO, fair odor, sli odor.	•	
3650		SH: vari clrd.		
3657	ARBUCKLE 3657 (-1446)	DOL: tan, f-med xln, rhombic xls, inter xln Ø, sli FSFO, GSFO, sli odor, dk-even stn.	•	
3670		DOL: tan-lt gry, f-med xln, sucrosic, inter xln Ø, FSFO, No odor, dk scttrd stn.	•	
3690	TOTAL DEPTH			
3700				

CFL

DRILLING TIME Minutes/Foot — Rate of Penetration Decreases | DEPTH | LITHOLOGY | SAMPLE DESCRIPTIONS | OIL SHOWS | REMARKS

CONTRACTOR: WHITE KNIGHT DRILLING
LEASE: BHB IP:
ELEVATION: 2206, KB 2211 RTD 3690
LOCATION: 2970' FSL & 1315' FWL
SEC. 5 TWP 7S RNG 20 W
COUNTY: ROOK STATE: KANSAS