

LEASE NAME Bartlett OPERATOR KRED
 WELL # KR-18 LOCATION: Miami
 SURFACE PIPE: 20' H: 7" Cement (#bags) 5
 PRODUCTION: 2 3/8 PIPE: SIZE: " FEET 533.1' Baffle 30.6' set at 502.5

START DATE: 4/1/14
 API:

Driller Brad

1 core

Thickness	Formation	Comment	Depth	Thickness	Formation	Comment	Depth
		soil - clay	0-8'			Shale	466-470
		Shale	8-19			lime	470-471
		lime	19-24			bleed limy sand	471-472
		Shale	24-59			core 472-490	
		lime	59-60			lime	472-472
		Shale	60-68			Heavy bleed oil sand	472.3-473
		lime	68-83			95% shale	473.3-474
		lime Shale	83-93			bleed 40% oil sand	474.9-475
		lime	93-120			light bleed 15% oil sand	476-477
		Shale	120-128			shale	477-478
		lime	128-151			bleed 20% sand	478-480
		Shale	151-156			Shale	480.5-481
		lime	156-166			thin oil seams mostly shale	482-483
		Shale	166-184			shale	483-484
		Gray Sand	184-187			shale	488-500
		Shale	187-272			lime	540-541
		broken sand	272-280				
		Shale	280-308				
		lime	308-316				
	Hard	sandy shale	316-323				
		Shale	323-333				
		lime	333-356				
		Shale	356-359				
		Gray Sand	359-361				
	bleed	Oil Sand	361-362				
		sandy Gray Shale	362-364				
		Shale	364-373				
		Blk Shale	373-390				
		lime	390-399				
		Shale	399-410				
		lime	410-439				
		Shale	439-454				
		lime	454-457				
		coal	457-459				
	oil	lime	459-464				

TD 541