

Beckman #1-18
 Daily Drilling Report
 Page Two

4/4/14 Depth 4580'. Cut 260'. DT: None. CT: 4¼ hrs. Dev.: None. HC @ 5:00AM 4/4.
 CF Log

4/5/14 RTD: 4580'. CT: 19½ hrs. Pioneer logged 10:30AM -3:45PM 4/4. LTD: 4578'.
 Allied plugged from 7:30PM – 10:30PM 4/4, using 60/40 Poz, 4%Gel, ¼#Flo seal,
 25sxs @ 2650', 100sxs @ 1710', 40sxs @ 350', 10sxs @ 40', 30sxs RH, 15sxs
 MH. Orders by Pat Staab KCC Hays. RR@ 2:30AM 4/5/14. FINAL REPORT.

Beckman #1-18 2150' FNL 2310' FEL Sec. 18-7S-29W 2886' KB							Beckman 'A' #1-16 1903' FSL 1340' FWL Sec. 16-7S-29W 2876' KB	
Formation	Sample top	Datum	Ref	Log tops	Datum	Ref	Log tops	Datum
Anhydrite	2550	+336	Flat	2551	+335	-1	2540	+336
B/Anhydrite	2587	+299	-1	2580	+306	+6	2576	+300
Topeka	3748	-862	-4	3741	-855	+3	3734	-858
Heebner	3934	-1048	+6	3934	-1048	+6	3930	-1054
Lansing	3977	-1091	+7	3974	-1088	+10	3974	-1098
Stark	4146	-1260	+13	4148	-1262	+11	4149	-1273
BKC	4194	-1308	+10	4196	-1310	+8	4194	-1318
Pawnee	4307	-1421	+9	4308	-1422	+8	4306	-1430
Ft Scott	4386	-1500	+14	4387	-1501	+13	4390	-1514
Cherokee	4403	-1517	+16	4405	-1519	+14	4409	-1533
Mississippi	4504	-1618	+9	4506	-1620	+7	4503	-1627
RTD	4580						4580	
LTD				4578			4580	