



Operator:
Grand Mesa Operating Co.
Wichita, KS

Nickel 6-15
Coffey Co., KS
10-22S-16E
API: 031-23885

Spud Date: 6/4/2014
Surface Casing: 7.0"
Surface Length: 44.0'
Surface Cement: Consolidated
Longstring:

Surface Bit: 11.0"
Drill Bit: 6.25"
Longstring: P&A
Longstring Date:
Seat Nipple:

Driller's Log

Top	Bottom	Formation	Comments
0	17	Soil & clay	
17	23	Gravel & Sand	
23	27	Lime	
27	32	Shale	
32	40	Lime	
40	69	Shale	
69	80	Lime	
80	215	Shale	
215	217	Lime	
217	229	Shale	
229	248	Lime	
248	256	Shale	
256	271	Lime	
271	353	Shale	
353	380	Lime	
380	428	Shale	
428	460	Lime	
460	478	Shale	
478	489	Lime	
489	549	Shale	
549	584	Lime	
584	596	Shale	
596	600	Lime	
600	607	Shale	

Nickel #6-15
Coffey Co., KS

607	610	Lime	
610	619	Shale	
619	631	Lime	
631	640	Shale	
640	658	Lime	
658	675	Shale	
675	679	Lime	
679	819	Shale	
819	822	Lime	
822	839	Shale	
839	855	Lime	
855	925	Shale	
925	929	Lime	
929	934	Shale	
934	939	Lime	
939	969	Shale	
969	984	Lime	
984	989	Shale	
989	996	Lime	
996	1016	Shale	
1016	1017	Lime	
1017	1020	Shale	
1020	1021	Lime	
1021	1022	Sand	Good oil show, wells saturated
1022	1023	Sand	Laminated, worse sand quality, rainbow
1023	1025	Sand	No show
1025	1037	Shale	
1037		TD	

	Coring	
Run	Footage	Rec.
1	1017-1037	18'

P&A through drill pipe with 10 sx plug at TD, 10 sx at base of KC,
fill from 250-surface