

Operator License # 35069
 Operator Kansas City Oil, LLC
 Address 9525 Lime Stone Road
 City Parkville, MO 64152
 Contractor JTC Oil, Inc.
 Contractor License # 32834
 T.D. 420
 T.D. of pipe 400
 Surface pipe size 7"
 Surface pipe depth 20'
 Well Type Production

API # 15-121-30412-00-00
 Lease Name KU
 Well # 2
 Spud Date 6/2/2014
 Cement Date
 Location Sec 23 T 18 R 22
 165 feet from S line
 1095 feet from W line
 County Miami

Driller's Log

Thickness	Strata	From	To
9	dirt	0	9
22	lime	9	31
27	shale	31	58
8	lime	58	66
39	shale	66	105
11	lime	105	116
8	shale	116	124
32	lime	124	156
5	shale	156	161
25	lime	161	186
3	shale	186	189
5	lime	189	194
3	shale	194	197
9	lime	197	206
137	shale	206	343
2	top sand	343	345
2	ok	345	347
2	lime	347	349
2	ok	349	351
2	ok	351	353
2	good	353	355
3	very good	355	358
2	very good	358	360
18	lime	360	378
6	lime oil	378	384
36	shale	384	420

Hurricane Services, Inc.
 3613 A Y Road
 Madison, KS 66860
 Office # 620-437-2661
 Brad Cell # 620-437-6765



Ticket Number 100457
 Location _____
 Foreman DeWayne / Joe

Cement Service ticket

Date	Customer #	Well Name & Number	Sec./Township/Range	County
6-4-14		KU Lease # 2	23-18-22	Miami
Customer	Mailing Address	City	State	Zip
Kansas City Oil	9525 Limestone Rd	Parkville	MO	64152

Job Type:

Truck #	Driver
230	Tom / Alex
242	Amos / Dray
110	Scott
111	Tyler
25	DeWayne

Quantity Or Units	Description of Services or Product	Pump charge	
23	Mileage Cement Pump 230	\$3.25/Mile	74.75
23	Foreman Pickup 25	1.5 mi	34.50
65 Sacks	60-40 Poz mix	12 ⁰⁰ SK	780 ⁰⁰
112 Lbs	Prem Gel 2% ^o	.30 Lb	33 ⁶⁰
100 Lbs	PREM GEL Flush	.30 Lb	30 ⁰⁰
16,25 Lbs	cello Flake	2.15 Lb	34.94
3000 Gal	Water	1.3 gal	39 ⁰⁰
2 LT	Water TRUCK 110	84 hr	168 ⁰⁰
2 LT	Water TRUCK 111	94 hr	168 ⁰⁰
2.8 Tons	Bulk Truck Minimum Charge 242	\$1.15/Mile	300 ⁰⁰
1	Plugs 2 1/2 Rubber Plug	25 ⁰⁰	25 ⁰⁰
	Subtotal		2362.29
	8.65	Sales Tax	81.53
	Estimated Total		2444.32

Remarks: Hooked onto casing pump to establish circulation pump
 5 Bbl Gel followed by 15 Bbl pad and start cement
 pump 65 Sacks stop and flush pump then pump plug to
 bottom and shut in 800 PSI