

Operator License # 35069
 Operator Kansas City Oil, LLC
 Address 9525 Lime Stone Road
 City Parkville, MO 64152
 Contractor JTC Oil, Inc.
 Contractor License # 32834
 T.D. 420
 T.D. of pipe 409
 Surface pipe size 7"
 Surface pipe depth 20'
 Well Type Production

API # 15-121-30410-00-00
 Lease Name KU
 Well # 4
 Spud Date 6/12/2014
 Cement Date
 Location Sec 23 T 18 R 22
 500 feet from S line
 165 feet from W line
 County Miami

Driller's Log

Thickness	Strata	From	To
7	dirt	0	7
18	lime	7	25
26	shale	25	51
5	lime	51	56
41	shale	56	97
11	lime	97	108
9	shale	108	117
31	lime	117	148
4	shale	148	152
26	lime	152	178
3	shale	178	181
14	lime	181	195
5	shale mix	195	200
136	shale	200	336
2	top sand	336	338
2	top sand	338	340
2	top sand	340	342
2	top sand	342	344
2	limey	344	346
2	good	346	348
2	good	348	350
2	ok	350	352
2	limey	352	354
2	ok	354	356
2	good	356	358
2	ok	358	360
2	ok	360	362
3	shale	362	365
18	lime	365	383
37	shale	383	420

ok

Hurricane Services, Inc.
 3513 A Y Road
 Madison, KS 66860
 Office # 620-437-2661
 Brad Cell # 620-437-6765



Ticket Number 100429
 Location _____
 Foreman Dwayne

Cement Service ticket

Date	Customer #	Well Name & Number	Sec./Township/Range	County
6/18/14		KU Lease # 4	23-18-22	Miami
Customer		Mailing Address	City	State Zip
Kansas City Oil		9525 Limestone Rd	Parkville	MO 64152

Job Type:	Truck #	Driver
Long String	231	TOM
Hole Size: 6 1/2"	242	Danny D.
Hole Depth:	110	SCOTT
Bridge Plug:	108	TYLOR
Packer:	25	DWAYNE

Quantity Or Units	Description of Services or Product	Pump charge	
23	Mileage Cement Pump 231	\$3.25/Mile	N/C
23	Fedman Pickup 25	1.5	N/C
63 Sacks	60/40 Poz Mix	12.00 SK	756.00
106 Lbs	Prem Gal In Cement	.30 Lb	31.80
100 Lbs	Prem Gal Flush	.30 Lb	30.00
15.75 Lbs	FloSeal 1/4 Lb - Sack	2.15 \$8	33.86
3000 Gal	Water	1.3 \$gal	39.00
1.25 hr	Water TRUCK 110	84.00 hr	105.00
1.25 hr	Water TRUCK 108	84.00 hr	105.00
2.7 Tons	Bulk Truck AllReady on location 242	\$1.15/Mile	N/C
1	Plugs 2 1/2 Rubber Plug	25.00	25.00
	Subtotal		1900.66
	Sales Tax		79.20
	Estimated Total		1979.86

Remarks: Hooked on to casing and Established Circulation. Pump 6 Bbl Gal Flush Followed By 15 Bbl Pad and Start Cement. Pump 63 Sacks of Cement. Stop and Flush Pump Then Pump wiper Plug to Bottom and Shut In 700 PSI.

Customer Signature _____