

Operator License # 35069
 Operator Kansas City Oil, LLC
 Address 9525 Lime Stone Road
 City Parkville, MO 64152
 Contractor JTC Oil, Inc.
 Contractor License # 32834
 T.D. 420
 T.D. of pipe 413
 Surface pipe size 7"
 Surface pipe depth 20'
 Well Type Production

API # 15-121-30411-00-00
 Lease Name KU
 Well # 6
 Spud Date 6/6/2014
 Cement Date
 Location Sec 23 T 18 R 22
 830 feet from S line
 495 feet from W line
 County Miami

Driller's Log

Thickness	Strata	From	To
9	dirt	0	9
22	lime	9	31
26	shale	31	57
40	lime	57	97
13	shale	97	110
8	lime	110	118
5	shale	118	123
27	lime	123	150
5	shale	150	155
24	lime	155	179
4	shale	179	183
14	lime	183	197
6	shale mix	197	203
135	shale	203	338
2	top sand	338	340
2	ok	340	342
2	ok	342	344
2	ok	344	346
2	ok	346	348
2	ok	348	350
2	ok	350	352
2	ok	352	354
2	v-good	354	356
2	v-good	356	358
2	ok	358	360
3	shale	360	363
16	lime	363	379
41	shale	379	420

Hurricane Services, Inc.
 3613 A Y Road
 Madison, KS 66860
 Office # 620-437-2661
 Brad Cell # 620-437-6765



Ticket Number 100433
 Location _____
 Foreman Dwayne

Cement Service ticket

Date	Customer #	Well Name & Number	Sec./Township/Range	County
6/18/14		KU Lease # 6	23 18 22	Miami
Customer	Mailing Address	City	State	Zip
Kansas City Oil	9525 Limestone Rd	Parkville	MO	64152

Job Type:	Truck #	Driver
Long String	231	Tom
Hole Size: 6"	240	Amos/Alex
Hole Depth: 420'	110	Scott
Bridge Plug:	108	Tyler
Packer:	25	Dwayne

Quantity Or Units	Description of Services or Product	Pump charge	
32 mi	Mileage Cement Pump 231	\$3.25/Mile	N/A
32 mi	Foreman Pickup 25	1.5 mi	N/A
63 Sacks	60/40 Poz Max	12.00	756.00
106 LBS	Prem Gel In Cement 2%	.30 LB	31.80
100 LBS	Prem Gel Flush	.30 LB	30.00
15.75 LBS	FloSeal	2.15 LB	33.86
3000 Gal	Water	1.3 \$ gal	39.00
1.25 hr	Water Truck 110	84.00 hr	105.00
1.25 hr	Water Truck 108	84.00 hr	105.00
2.7 Tons	Bulk Truck AllReady on Location		N/A
1	Plugs 2 1/2 Rubber Plug	25.00	25.00
	Subtotal		1800.66
	Sales Tax		79.30
	Estimated Total		1879.86

Remarks: Hooked onto casing and Establish Circulation
 Pump 6 BBL Prem gel Flush Followed By 15 BBL Pad
 and Start Cement Pump 63 Sacks OF Cement Stop and
 Flush Pump Then Pump wiper Plug to Bottom and
 Shut IN 700 PSI

Customer Signature _____