

Operator License # 35069
 Operator Kansas City Oil, LLC
 Address 9525 Lime Stone Road
 City Parkville, MO 64152
 Contractor JTC Oil, Inc.
 Contractor License # 32834
 T.D. 420
 T.D. of pipe 413
 Surface pipe size 7'
 Surface pipe depth 20'
 Well Type Production

API # 15-121-30448-00-00
 Lease Name KU
 Well # 13
 Spud Date 6/4/2014
 Cement Date
 Location Sec 23 T 18 R 22
 1160 feet from S line
 825 feet from W line
 County Miami

Driller's Log

Thickness	Strata	From	To
9	dirt	0	9
18	lime	9	27
27	shale	27	54
6	lime	54	60
40	shale	60	100
12	lime	100	112
8	shale	112	120
30	lime	120	150
8	shale	150	158
22	lime	158	180
4	shale	180	184
16	lime	184	200
138	shale	200	338
2	top	338	340
2	top	340	342
2	top	342	344
2	top	344	346
2	top	346	348
2	top	348	350
2	top	350	352
2	end	352	354
2	lime	354	356
2	sand	356	358
4	shale	358	362
2	lime oil	362	364
2	lime oil	364	366
2	lime oil	366	368
6	lime	368	374
1	lime oil	374	375
3	lime oil	375	378
42	shale	378	420

ok

Hurricane Services, Inc.
 3613 A Y Road
 Madison, KS 66860
 Office # 620-437-2661
 Brad Cell # 620-437-6765



Ticket Number 100431
 Location _____
 Foreman Dwayne

Cement Service ticket

Date	Customer #	Well Name & Number	Sec./Township/Range	County
G/18/14		KU Lease # 13	23-18-22	Miami
Customer	Mailing Address	City	State	Zip
Kansas City Oil	9525 Limestone Rd	Parkville	MO	64152

Job Type:	Truck #	Driver
Long String	231	Tom
Hole Size: 6"	240	Amos/Alex
Hole Depth: 420'	110	Scott
Bridge Plug:	108	Tyler
Packer:	25	Dwayne

Quantity Or Units	Description of Services or Product	Pump charge	
32	Mileage Cement Pump 231	\$3.25/Mile	N/K
32	Forman Pickup 25	1.5	N/K
63 Sacks	60/40 Poz Mix	12 ⁰⁰ SK	756 ⁰⁰
106 Lbs	Prem Gal In Cement 2%	1.30 Lb	31 ⁸⁰
100 Lbs	Prem Gal Flush	1.30 Lb	30 ⁰⁰
15.75 Lbs	Flt Seal	2.15 Lb	33 ⁸⁶
3000 Gal	Water	1.3 L gal	39 ⁰⁰
1.25 hr	Water Truck 110	84 ⁰⁰ hr	105 ⁰⁰
1.25 hr	Water Truck 108	84 ⁰⁰ hr	105 ⁰⁰
2.7 Tons	Bulk Truck Minimum Delivery 240		300 ⁰⁰
1	Plugs 2 1/2 Rubber Plug	25 ⁰⁰	25 ⁰⁰
		Subtotal	2100 ⁶⁶
		Sales Tax	79 ²⁰
		Estimated Total	2179 ⁸⁶

Remarks: Hooked onto casing and Establish circulation
 Pump 6 Sacks Prem gel Flush followed by 15 BRP
 Pad and start cement pump 63 Sacks of cement. Stop
 and flush pump. Then pump wiper plug to bottom and
 shot in 700 PSI.

Customer Signature _____