


LEIS OIL SERVICES



1410 150th Rd. • Yates Center, Kansas 66783 • (620) 212-0752

Operator License #: 35034	API #: 15-003-26224-00-00
Operator: Hunt Oil, LLC.	Lease: Banks
Address: 259 Park Rd Garnett, KS 66032	Well #: 50
Phone: (913) 208-8183	Spud Date: 7/15/14 Completed: 7/16/14
Contractor License: 32079	Location: SW/NE/SE/NE of 22-20S-20E
T.D. : 661 T.D. of Pipe: 657 Size: 2.875"	3527 Feet From South
Surface Pipe Size: 7" Depth: 36'	623 Feet From East
Kind of Well: Enh. Rec.	County: Anderson

LOG

Thickness	Strata	From	To	Thickness	Strata	From	To
15	Soil/Clay	0	15	2	Light Sand	596	598
6	Gravel	15	21	30	Shale	598	628
15	Shale	21	36	7	Sand/No Bleed	628	635
29	Lime	36	65	26	Shale	635	661
15	Shale	65	80				
2	Lime	80	82				
47	Shale	82	129				
83	Lime	129	212				
3	Shale/Black Shale	212	215				
21	Lime	215	236				
175	Shale	236	411				
3	Lime	411	414				
9	Shale	414	423				
6	Lime	423	429				
54	Shale	429	483				
6	Lime	483	489		T.D.		661
6	Shale	489	495		T.D. of Pipe		657
1	Lime	495	496				
11	Shale	496	507				
3	Lime	507	510				
20	Shale	510	530				
32	Sandy Lime	530	562				
2	Lime	562	564				
12	Shale/Black Shale	564	576				
8	Lime	576	584				
4	Shale	584	588				
2	Lime	588	590				
1	White Muck	590	591				
5	Oil Sand	591	596				



CONSOLIDATED
Oil Well Services, LLC

269750

TICKET NUMBER 47449
LOCATION Ottawa KS
FOREMAN Fred Maden

PO Box 884, Chanute, KS 66720
620-431-9210 or 800-467-8676

FIELD TICKET & TREATMENT REPORT
CEMENT

DATE	CUSTOMER #	WELL NAME & NUMBER	SECTION	TOWNSHIP	RANGE	COUNTY
7-17-14	H21	Banks # 50	NW 23	20	20	AN
CUSTOMER Hunt Oil LLC			TRUCK #			
MAILING ADDRESS 259 W. Park Rd			DRIVER			
CITY Garnett			TRUCK #			
STATE KS			DRIVER			
ZIP CODE 66032			TRUCK #			
			DRIVER			

JOB TYPE Longstring HOLE SIZE 5 7/8 HOLE DEPTH 661 CASING SIZE & WEIGHT 2 7/8 EVE
 CASING DEPTH 657 DRILL PIPE _____ TUBING _____ OTHER _____
 SLURRY WEIGHT _____ SLURRY VOL _____ WATER gal/sk _____ CEMENT LEFT In CASING 2 1/2" Plug
 DISPLACEMENT 3.82 BBL DISPLACEMENT PSI _____ MIX PSI _____ RATE 5 BPM

REMARKS: Hold crew safety meeting. Establish circulation. Mix Pump 100#
Gel Flusk. Mix Pump 75 sks OWC Cement 1/4" Flo Seal/sk.
Cement to surface. Flush pump & lines clean. Displace 2 1/2"
Rubber plug to casing TD. Pressure to 800# PSI. Monitor
pressure for 30 min MIT. Release pressure to set float valve
Shut in casing.

J. Leis Drilling

Fred Maden

ACCOUNT CODE	QUANTITY or UNITS	DESCRIPTION of SERVICES or PRODUCT	UNIT PRICE	TOTAL
5401	1	PUMP CHARGE	495	1085 ⁰⁰
5404	25 mi	MILEAGE	495	105 ⁰⁰
5402	657'	Casing Footage		N/C
5407	Minimum	Ton Miles	548	368 ⁰⁰
5502C	1 1/2 hr	80 BBL Vac Truck	675	150 ⁰⁰
1126	75 sks	owc Cement	1481 ³⁵	
1118B	100#	Premium Gel	22 ⁰⁰	
1107	19#	Flo Seal	46 ⁹³	
		Material	1550 ¹⁸	
		Less 30%	-465 ⁰⁵	
		Total		1085 ¹³
4402	1	2 1/2" Rubber Plug		29 ⁵⁰
			3408.53	
			7.65%	SALES TAX 85 ²¹
				ESTIMATED TOTAL 2997 ⁹⁰
				DATE 7/17/14

Revin 3737

AUTHORIZATION

TITLE

DATE

I acknowledge that the payment terms, unless specifically amended in writing on the front of the form or in the customer's account records, at our office, and conditions of service on the back of this form are in effect for services identified on this form.