



11 Lewis Drive

Paola, KS 66071

Oil & Gas Well Drilling
Water Wells
Geo-Loop Installation

Phone: 913-557-9083
Fax: 913-557-9084

WELL LOG

L & P Enterprises, LLC
Donner #D21
API#15-121-29,597
July 25 - July 28, 2014

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
3	soil & clay	3
7	lime	10
2	shale	12
13	lime	25
11	shale	36
36	lime	72
2	shale	74
19	lime	93
87	shale	180
16	lime	196
31	shale	227
7	lime	234
36	shale	270
14	lime	284
14	shale	298
27	lime	325 oil show
8	shale	333
23	lime	356
4	shale	360
14	lime	374 base of the Kansas City
29	shale	403
11	broken sand	414 brown & grey light bleeding
72	shale	486
7	oil sand	493 green ok bleeding
54	shale	547
8	lime	555
7	shale	562
3	lime	565
16	shale	581
1	coal	582
6	shale	588
5	lime	593
15	shale	608
3	lime	611
32	shale	643
3	lime	646
21	shale	667
4	broken sand	671 brown & green 50% bleeding
2.5	oil sand	673.5 brown 90% bleeding

Donner #D21

Page 2

1	broken sand	674.5 brown & green few bleeding seams
1.5	shale	676
1.5	broken sand	677.5 brown & green 70% bleeding
43.5	shale	721 TD

Drilled a 9 7/8" hole to 22'

Drilled a 5 5/8" hole to 721'

Set 22' of 7" surface casing threaded and coupled cemented with 5 sacks of cement

Set 711.1' of 2 7/8" 8 round upset tubing with 3 centralizers, 1 float shoe, 1 clamp



CONSOLIDATED
Oil Well Services, LLC

269993

TICKET NUMBER 47517

LOCATION Ottawa KS

FOREMAN Fred Maden

PO Box 884, Chanute, KS 66720
620-431-9210 or 800-467-8676

FIELD TICKET & TREATMENT REPORT
CEMENT

DATE	CUSTOMER #	WELL NAME & NUMBER	SECTION	TOWNSHIP	RANGE	COUNTY
7-29-14	4828	Danner # D-21	NW 5	17	22	MI
CUSTOMER L&P Enterprises LLC			TRUCK #			
MAILING ADDRESS 29975 Indianapolis Rd			DRIVER			
CITY Paola			TRUCK #			
STATE KS			DRIVER			
ZIP CODE 66071			TRUCK #			
Wettsville			DRIVER			

JOB TYPE Longstring HOLE SIZE 5 7/8 HOLE DEPTH 721 CASING SIZE & WEIGHT 2 3/8 EUE
 CASING DEPTH 711 DRILL PIPE _____ TUBING _____ OTHER _____
 SLURRY WEIGHT _____ SLURRY VOL _____ WATER gal/sk _____ CEMENT LEFT in CASING 2 1/2" Plug
 DISPLACEMENT 4.13 BBL DISPLACEMENT PSI _____ MIX PSI _____ RATE 58 BPM

REMARKS: Hold crew safety meeting. Establish pump rates. Mix + Pump 100# Gal Flush. Mix + Pump 95 sks 50/50 Poz Mix Cement 290 Gal 1/2# Pheno Seal/sk. Cement to surface. Flush pump + lines clean. Displace 2 1/2" Rubber plug to casing. TD. Pressure to 800# PSI. Release pressure to set float valve. Shut in casing.

Evans Energy Dev. Inc. Travis

Fred Maden

ACCOUNT CODE	QUANTITY or UNITS	DESCRIPTION of SERVICES or PRODUCT	UNIT PRICE	TOTAL
5401	1	PUMP CHARGE	495	1085.00
5406	20 mi	MILEAGE	495	84.00
5402	711	Casing footage		N/C
5407	1/2 Minimum	Ten Miles	510	184.00
5502C	1 1/2 hr	80 BBL Vac Truck	675	150.00
1124	95 sks	50/50 Poz Mix Cement	1092.50	
115B	260#	Premium Gel	57.20	
1107A	48#	Pheno Seal	64.80	
		Material	1214.50	
		Less 30%	-364.35	
		Total		850.15
4402	1	2 1/2" Rubber Plug		29.50
			7.6570	
			SALES TAX	67.31
			ESTIMATED	
			TOTAL	2449.96

Ravin 3737

AUTHORIZATION

TITLE _____

DATE _____

I acknowledge that the payment terms, unless specifically amended in writing on the front of the form or in the customer's account records, at our office, and conditions of service on the back of this form are in effect for services identified on this for