

Confidentiality Requested:

KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

1227039

Form ACO-1 August 2013 Form must be Typed Form must be Signed All blanks must be Filled

WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

OPERATOR: License #	API No. 15				
Name:	Spot Description:				
Address 1:					
Address 2:	Feet from Dorth / South Line of Section				
City: State: Zip:+	Feet from East / West Line of Section				
Contact Person:	Footages Calculated from Nearest Outside Section Corner:				
Phone: ()					
CONTRACTOR: License #	GPS Location: Lat:, Long:				
Name:	(e.g. xx.xxxx) (e.gxxx.xxxx)				
Wellsite Geologist:	Datum: NAD27 NAD83 WGS84				
Purchaser:	County:				
Designate Type of Completion:	Lease Name: Well #:				
New Well Re-Entry Workover	Field Name:				
	Producing Formation:				
	Elevation: Ground: Kelly Bushing:				
Gas D&A ENHR SIGW	Total Vertical Depth: Plug Back Total Depth:				
OG GSW Temp. Abd. CM (Coal Bed Methane)	Amount of Surface Pipe Set and Cemented at: Feet				
Cathodic Other (Core, Expl., etc.):	Multiple Stage Cementing Collar Used?				
If Workover/Re-entry: Old Well Info as follows:	If yes, show depth set: Feet				
Operator:	If Alternate II completion, cement circulated from:				
Well Name:	feet depth to:w/sx cmt.				
Original Comp. Date: Original Total Depth:					
Deepening Re-perf. Conv. to ENHR Conv. to SWD	Drilling Fluid Management Plan				
Plug Back Conv. to GSW Conv. to Producer	(Data must be collected from the Reserve Pit)				
	Chloride content: ppm Fluid volume: bbls				
Commingled Permit #: Dual Completion Permit #:	Dewatering method used:				
SWD Permit #:	Location of fluid disposal if hauled offsite:				
ENHR Permit #:					
GSW Permit #:	Operator Name:				
	Lease Name: License #:				
Spud Date or Date Reached TD Completion Date or	Quarter Sec TwpS. R East West				
Recompletion Date Recompletion Date	County: Permit #:				

AFFIDAVIT

I am the affiant and I hereby certify that all requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Submitted Electronically

KCC Office Use ONLY						
Confidentiality Requested						
Date:						
Confidential Release Date:						
Wireline Log Received						
Geologist Report Received						
UIC Distribution						
ALT I II III Approved by: Date:						

	Page Two	1227039
Operator Name:	Lease Name:	Well #:
Sec TwpS. R □ East □ West	County:	
INCTRUCTIONS. Chow important tang of formations panatrated	Dotail all cores Report all fine	al copies of drill stoms tasts giving interval tasted, time tool

INSTRUCTIONS: Show important tops of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed.

Final Radioactivity Log, Final Logs run to obtain Geophysical Data and Final Electric Logs must be emailed to kcc-well-logs@kcc.ks.gov. Digital electronic log files must be submitted in LAS version 2.0 or newer AND an image file (TIFF or PDF).

Drill Stem Tests Taken (Attach Additional Sh	neets)	Yes No		-	on (Top), Depth a		Sample
Samples Sent to Geolog	gical Survey	Yes No	Nam	e		Тор	Datum
Cores Taken Electric Log Run		☐ Yes ☐ No ☐ Yes ☐ No					
List All E. Logs Run:							
			RECORD Ne		ion, etc.		
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
		ADDITIONAL	CEMENTING / SQL	EEZE RECORD			
Purpose:	Depth Top Bottom	Type of Cement	# Sacks Used		Type and F	Percent Additives	

Purpose: Perforate	Top Bottom	Type of Cement	# Sacks Used	Type and Percent Additives
Protect Casing				
Plug Off Zone				

Did you perform a hydraulic fracturing treatment on this well?	
Does the volume of the total base fluid of the hydraulic fracturing treatment exceed 350,000 gallons?	
Was the hydraulic fracturing treatment information submitted to the chemical disclosure registry?	Γ

Yes	No
Yes	No
Yes	No

(If No, skip questions 2 and 3) (If No, skip question 3)

(If No, fill out Page Three of the ACO-1)

Shots Per Foot		PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated							ement Squeeze Record d of Material Used)	Depth
TUBING RECORD:	Siz	ze:	Set At:		Packer	r At:	Liner R		No	
Date of First, Resumed	l Product	ion, SWD or ENHI	٦.	Producing Me	ethod:	ping	Gas Lift	Other (Explain)		
Estimated Production Per 24 Hours		Oil Bb	ols.	Gas	Mcf	Wate	er	Bbls.	Gas-Oil Ratio	Gravity
DISPOSITION OF GAS:							_	PRODUCTION INTER	RVAL:	
Vented Sole	d 🗌 I	Used on Lease		Open Hole	Perf.	Uually (Submit)	Comp.	Commingled (Submit ACO-4)		
(If vented, Su	ıbmit ACC	D-18.)		Other (Specify) _		(2001111)		(000/1)		

Form	ACO1 - Well Completion
Operator	Bauer Oil Investment, LLC
Well Name	Chrisjohn 4
Doc ID	1227039

Casing

Purpose Of String		Size Casing Set	Weight	Setting Depth	Type Of Cement		Type and Percent Additives
Surface	9.875	7	10	20	Portland	5	
Completio n	5.625	2.875	8	377	Portland	55	



www.pennysconcrete.com An Equal Opportunity Employer

1.00

ea

FUELINV

PENNY'S CONCRETE, INC.



MODO

Certifications

KANSAS

Certifications

\$7.40

15 2

\$7.40

American Concrete Institute Certifications

23400 W. 82ND STREET SHAWNEE MISSION, KANSAS 66227-2705 DISPATCH: (913) 441-4197 OFFICE (913) 441-8781 (800) 322-9710 (800) 524-6474

PLANT	DATE	ACCOUNT	TRUCK	DRIVER 1	TAME	TIC	KET #
08	08/27/2014	COD8	0158	Joe Nighswo	onger	8	044881
CUSTOME	r name	A	DDITIONAL DIRE	CTIONS AND/OR SPE	CIAL INSTRUCTIO	ONS	
COD - H	BAUER OIL	*	**PAID***	69 SOUTH -	- 68 WEST	-169 SO	UTH -
JOE AD	DRESS	17	HWY/PLUM	IB CREEK RD B	EXIT NORTH	I - 1ST	ST
7 HWY & 363RD ST/SUNSHINE RD 363RD ST/SUNSHINE RD WEST TO JOB							
and a second sec	A MARK	N	OTE:				
		0 7	LL DRIVERS	MUST WEAR A HA	RD HAT, SAF	ETY GLASS	SES,
And		S	TEEL TOE BO	OTS, AND SAFET	Y VEST ON E	VERY JOB	
ORDER #	PO#	PROJECT CODE	JOB#	APPLICATI	ON PREVI	OUS TRUCK	SLUMP
20	CREI	DITCARD					10
QTY.	UNIT PRODUCT	DESCRIPTION		ORDERED	DELIVERED UN	NIT PRICE	AMOUNT
5.00 (CYDS SLURRY20-2	20 SACK SLURF	RY - 7 GAI	LONS 5.00	5.00 \$3	338.001,	690.00
1.00	ea SLC S	SHORT LOAD CH	HARGE	1.00	1.00 \$1	8.00	\$18.00

				SUBTOTAL	\$1,715.40
LEAVE PLANT	ARRIVE JOB	START UNLOAD	FINISH UNLOAD	TAX	\$14 1.09 \$1,859.49
LEAVE JOB	ARRIVE PLANT	TEST CYLINDERS TAKEN (BEFORE H20 ADDED I Y			
		/E ACCEPTS RECEIPT OF THIS LOAD O galydsgalydsgal		GRAND TOTAL	\$1,859.49

0.00

FUEL SURCHARGE - PER LOAD

CAUTION! Cement powder or freshly mixed concrete, grout or mortar may cause skin injury. Avoid contact with skin and wash exposed areas promptly with water. If any cement powder or mixture gets into the eyes, rinse

immediately and repeatedly with water, and get prompt medical attention. Keep children away from all freshly mixed cement products. MSDS on reverse side. ANY WATER ADDED TO MIX ON THE JOB WILL BE AT THE PURCHASER'S RISK DELIVERY AGREEMENT: This purchase agreement is for delivery to the curb line. In the event Purchaser requests delivery beyond the curb line, the Purchaser hereby assumes liability for damages to sidewalks, driveways all other property, and personal injury. Purchaser hereby agrees to indemnify and hold the Seller harmless against all liability, loss or expense incurred as the result of such delivery. If ground conditions beyond the curb line are inadequate for heavy truck travel, and as a result of this condition the truck requires towing, towing will be at the customer's expense.

PRODUCT PERFORMANCE: All concrete sold on a basis of compressive strength, air-entrainment, slump, temperature, density and or yield must be sampled at the mixer truck discharge in accordance to ASTM C172 and tested according to the applicable ASTM testing standards. Compressive strength: ASTM C31 & ASTM C39, air content: ASTM C213 or ASTM C173; Slump: ASTM C143; Temperature; ASTM C1064; density and or yield: ASTM C138. Slump and air-entrainment variances in accordance to ASTM C94 are applicable. Unless identified in writing, no other condition of sale shall apply. Customer assumes all responsibility for the placement, consolidation, curing, and protection of all concrete after delivery to the curb line. The placement, consolidation, curing, and protection of all concrete can greatly affect its performance. The seller is not responsible for any product performance after placement is made by the customer. ADDITIONAL INFORMATION: Ambient conditions may produce rapid evaporation of moisture from the concrete surface. As a result, plastic shrinkage cracking may occur. Precautions should be taken. Drying shrinkage is

an inherent, unavoidable property of concrete and precautions should be taken to minimize random cracking. Control joints must be properly constructed with reference to location, spacing, depth and timing. Materials hereby sold become property of purchaser at point of origin. The purchaser shall in no event accept deliveries of materials not in accord with the agreement of the parties, but such materials shall be refused by the purchaser and returned to the seller with a written statement of the reason for the refusal thereof. No cancellation accepted after concrete has been batched.

and the second		A Berthe	CUSTOMER SIGNATURE
PRINTED NAME	TITLE	Jr	NO WARRANTY IMPLIED OR EXPRESSED ON PRODUCT

Chrisjohn 2:3