

SandRidge Energy Anthony #3306 1-15H Harper County, KS.

## 1.0 Executive Summary

Allied Oil & Gas Services would like to thank you, for the award of the provision of cementing products and services on the well Anthony #3306 1-15H Surface Casing.

A pre-job meeting was held to discuss job details, review the safety hazards, potential environmental impact and established emergency procedures.

Allied started the job testing lines to 2000 psi. After a successful test we began the job by pumping 10 bbls of preflush spacer. We then mixed and pumped the following cements:

63 Bbls (190 sacks) of 12.7 ppg Lead slurry: Class A poz Blend Yeild 1.87 6% Gel 2% CC 1/4# Floseal

32 Bbls (150 sacks) of 15.6 ppg Tail slurry Class A Yeild 1.20 2% CC 1/4 # Floseal

The top plug was then released and displaced with 44 Bbls of fresh water. The plug bumped and pressured up to 900 psi. Pressure was released and floats held.

All real time data is shown on the graph in the attachment section.

Allied Oil & Gas Services remains committed to provide operational excellence and superior product performance. All comments and suggestions are greatly appreciated and help us to continue to provide this level of service.

Again we want to thank you for the opportunity to perform these and your future cementing & acidizing service needs.



SandRidge Energy Anthony #3306 1-15H Harper County, KS.

## 1.0 Executive Summary

Allied Oil & Gas Services would like to thank you for the award of the provision of cementing products and services on the well Anthony#3306 1-15H Intermediate Casing.

A pre-job meeting was held to discuss job details, review the safety hazards, potential environmental impact and established emergency procedures.

Allied started the job testing lines to 3200 psi. After a successful test we began the job by pumping 30 bbls of preflush spacer. We then mixed and pumped the following cements:

60 Bbls (240 sacks) of 13.6 ppg Lead slurry: 50:50 Class A:Poz Blend - 1.4 Yield 2.0% Gel 0.4% FL-160 0.1% SA-51

21Bbls (100 sacks) of 15.6 ppg Tail slurry: Class A - 1.18 Yield 0.8% FL-160 0.2% CD-31

The top plug was then released and displaced with 196 of fresh water. The plug bumped and pressured up to 1800 psi. Pressure was released and floats held.

All real time data is shown on the graph in the attachment section.

Allied Oil & Gas Services remains committed to provide operational excellence and superior product performance. All comments and suggestions are greatly appreciated and help us to continue to provide this level of service.

Again we want to thank you for the opportunity to perform these and your future cementing & acidizing service needs.

## **INVOICE**



DATE	INVOICE #	
6/22/2014	4874	

BILL TO

SANDRIDGE ENERGY, INC. ATTN: PURCHASING MANAGER 123 ROBERT S. KERR AVENUE OKLAHOMA CITY, OK 73102 **REMIT TO** 

EDGE SERVICES, INC. PO BOX 609 WOODWARD, OK 73802

COUNTY	STARTING D	WORK ORDER	RIG NUMBER	LEASE NAME	Terms
HARPER, KS	6/22/2014	3675	LARIAT 20	ANTHONY 3306 1-15H	Due on rec

## Description

DRILLED 80' OF 30" CONDUCTOR HOLE

DRILLED 6' OF 76" HOLE

FURNISHED AND SET 6' X 6' TINHORN CELLAR

FURNISHED 80 ' OF 20" CONDUCTOR PIPE

FURNISHED WELDER AND MATERIALS

FURNISHED 8 YARDS OF 10 SACK GROUT FOR CONDUCTOR HOLE

FURNISHED 4 YARDS OF 10 SACK GROUT FOR MOUSE HOLE

DRILL MOUSE HOLE

FURNISHED 80 ' OF 16" CONDUCTOR PIPE

TOTAL BID \$17,000.00

**Sales Tax (6.15%)** 

\$158.79

**TOTAL** 

\$17,158.79