

JOB NO: (31612)
 GPS: N: 37.305803°
 W: -100.86948°

COMPANY: ONEOK
 COMPANY REP.: WILEY MARTENS
 INSTALLATION DATE: 10/23/14
 RECTIFIER LOCATION: LINE O-23.5

CP MASTERS
 CORROSION PREVENTION INC.
 1700 E. SEWARD RD.
 GUTHRIE, OK 73044
 PH: (405)293-9777 F: (405)293-9779

STATE: KANSAS
 COUNTY: SEWARD

INSTALLED BY: J. WINTERS
 CASING TYPE: SCH 40 PVC
 DIAMETER: 8"
 CASING DEPTH: 20'
 NO. OF ANODES: 15
 ANODE TYPE: ANOTEC
 ANODE LEAD TYPE: #8 HMPWE

DIA. HOLE: 8"
 DEPTH: 300'
 COKE TYPE: SWS
 LBS INST'D: 3750
 HOLE PLUG: BENTONITE
 LOG VOLT: 13.84
 SOURCE: TRUCK

DEPTH FT.	DRILLERS LOG	ANODE NO. CASING	ELECTRIC LOG		DEPTH FT.	DRILLERS LOG	ANODE NO.	ELECTRIC LOG	
			NATIVE	W/O COKE				W/COKE	W/COKE
0	TOP SOIL				210	SAND & CLAY MIX			
10					220		9	0.1	3.2
20					230		8	0	3.2
30	BROWN CLAY	CASING			240	CLAY	7	0.1	3.3
40					250		6	0.1	3.4
50					260		5	0.1	3.5
60					270		4	0	3.4
70					280		3	0.1	3.1
80	SANDY LOMA				290		2	0	2.7
90					300	CLAY	1	0.4	2.2
100					310				
110					320				
120					330				
130					340				
140	SAND & CLAY MIX				350				
150					360				
160		15		0.0	370				
170		14		0.1	380				
180		13		0.1	390				
190		12		0.1	400				
200		11		0.1	410				
	SAND & CLAY MIX	10		0.0					