

JOB NO: (31612)
 GPS: N: 37.126606°
 W: -100.86925°

COMPANY: ONEOK
 COMPANY REP.: WILEY MARTENS
 INSTALLATION DATE: 10/25/14
 RECTIFIER LOCATION: LIBERAL JCT LINE



STATE: KANSAS
 COUNTY: SEWARD

INSTALLED BY: J. WINTERS
 CASING TYPE: SCH 40 PVC
 DIAMETER: 8"
 CASING DEPTH: 20'
 NO. OF ANODES: 15
 ANODE TYPE: ANOTEC
 ANODE LEAD TYPE: #8 HMPWE

DIA. HOLE: 8"
 DEPTH: 300'
 COKE TYPE: SWS
 LBS INST'D: 3750
 HOLE PLUG: BENTONITE
 LOG VOLT: 14.5
 SOURCE: TRUCK

DEPTH FT.	DRILLERS LOG	ANODE NO.	ELECTRIC LOG		DEPTH FT.	DRILLERS LOG	ANODE NO.	ELECTRIC LOG	
			NATIVE	W/O COKE				NATIVE	W/O COKE
0	TOP SOIL	CASING			210	SANDY LOMA			
10					220		9	1.0	32.2
20		CASING	0.0		230		8	1.3	35.7
30			0.0		240		7	1.0	36.7
40			0.0		250		6	1.6	38.0
50			0.0		260		5	1.4	38.9
60	SANDY LOMA		0.0		270		4	0.9	39.2
70			0.0		280		3	1.6	37
80			0.0		290		2	1.1	34.7
90			0.0		300	SANDY LOMA	1	1.1	35.8
100			0.0		310				
110			0.0		320				
120	SANDY LOMA		0.0		330				
130			0.0		340				
140			0.2		350				
150			0.9		360				
160	SAND & CLAY	15	0.8	15.3	370				
170		14	0.3	17.6	380				
180		13	0.3	19.7	390				
190		12	0.3	21.8	400				
200		11	0.7	26.1	410				
	SANDY LOMA	10	0.7	28.4					