

JOB NO: (31612)
GPS: N: 37.692849°
W: -101.10125°

COMPANY: ONEOK
COMPANY REP.: WILEY MARTENS
INSTALLATION DATE: 10/18/14
RECTIFIER LOCATION: KGS-15



STATE: KANSAS
COUNTY: GRANT

INSTALLED BY: J. WINTERS
CASING TYPE: SCH 40 PVC
DIAMETER: 8"
CASING DEPTH: 20'
NO. OF ANODES: 15
ANODE TYPE: ANOTEC
ANODE LEAD TYPE: #8 HMPWE

DIA. HOLE: 8"
DEPTH: 300'
COKE TYPE: SWS
LBS INST'D: 3750
HOLE PLUG: BENTONITE
LOG VOLT: 14.06
SOURCE: TRUCK

DEPTH FT.	DRILLERS LOG	ANODE NO.	ELECTRIC LOG		DEPTH FT.	DRILLERS LOG	ANODE NO.	ELECTRIC LOG	
			NATIVE	W/O COKE				NATIVE	W/O COKE
0	TOP SOIL	CASING			210	SAND & CLAY MIX	9		
10				0.0	220		8		0.3
20		CASING		0.0	230		7		0.2
30				0.1	240		6		0.3
40				0.0	250		5		0.2
50				0.0	260		4		0.3
60				0.0	270		3		2.3
70				0.0	280		2		0.4
80				0.1	290		1		1.0
90				0.1	300	SAND & CLAY MIX			1.1
100	SAND & CLAY MIX			1.4	310				
110				0.7	320				
120				0.3	330				
130				0.2	340				
140				0.3	350				
150				0.3	360				
160		15		0.4	370				
170		14		0.3	380				
180		13		0.3	390				
190		12		0.2	400				
200		11		0.3	410				
	SAND & CLAY MIX	10		0.2					