



11 Lewis Drive

Paola, KS 66071

**Oil & Gas Well Drilling
Water Wells
Geo-Loop Installation**

Phone: 913-557-9083

Fax: 913-557-9084

WELL LOG

Verde Oil Company
Campbell # I-10-10
API #15-001-31,152

September 23 - September 24, 2014

Thickness of Strata

Formation

Total

8	soil & clay	8
52	limestone	60
3	shale	63
2	lime	65
18	shale	83
78	lime	161
155	shale	316
3	lime	319
3	shale	322
10	lime	332
88	shale	420
1	lime	421
8	shale	429
21	lime	450
43	shale	493
15	lime	508
8	shale	516
6	lime	522
44	shale	566
2	lime	568
155	shale	723
2	limy sand	725 oil show
3	oil sand	728
3	broken sand	731
47	shale	778
2	brown sand	780
18	silty shale	798
20	shale	818
45	oil sand	863 brown bleeding
5	black	868 oil bleeding
10	black sand	878 no show
31.5	shale	909.5
0.5	lime	910 Mississippian, TD

Drilled a 9 7/8" hole to 21.5'

Drilled a 5 5/8" hole to 910'

Set 21.5' of new 7" threaded and coupled surface casing, cemented with 5 sacks cement.

Set 903.55' of used 2 7/8" 8 round upset tubing including, 4 centralizers, 1 float shoe, 1 clamp, 1 cement pup joint