

LEASE NAME: Larry Spratt OPERATOR: Utah Oil

START DATE: 7-14-14

WELL #: KO-6 LOCATION: Franklin

API #: 15-059-26494

SURFACE PIPE: 7' Ft 20.05 Cement (#bags) 6

PRODUCTION: used PIPE: 2 7/8 SIZE: 720.60 =FT Baffle 29.10

Thickness	Formation	Comment	Depth	Thickness	Formation	Comment	Depth
3	Soil		3	11	Shale		489
2	Sand Stone		5	3	Lime		492
3	Grey Sand		8	2	Coal		494
65	Shale		73	10	Shale		504
2	Lime		75	5	Shale	Some Lime	509
1	Shale		76	4	Lime		513
15	Lime		91	1	Lime	Oil Small No Bleed	514
8	Shale		99	3	Lime Soft	Sandy Heavy Bleed	517
5	Grey Sand	No Oil Show	104	1	Lime Soft	Good Bleed	518
2	Lime		106	2	Lime		520
7	Shale		113	2	Shale		522
2	Lime		115	1	Shale	Broken Sand No Show	523
3	Shale		118	3	Sand Solid	Oil Small No Bleed	526
4	Lime		122	1	Broken Sand	Heavy Bleed CP	527
37	Shale		159	0.5	Broken Sand	40% Good Bleed	527.5
12	Lime		171	1	Shale		528.5
2	Shale		173	0.25	Broken Sand	50% Good Bleed	528.75
4	Lime		177	1.25	Sand Solid	Good Bleed	530
10	Shale		187	3	Broken Sand	50% Good Bleed	533
27	Lime		214	48	Shale		581
8	Shale		222	2	Broken Sand	40% Oil Light No Bleed	583
23	Lime		245	4	Sand Solid	Small No Bleed	587
3	Shale		248	2	Broken Sand	50% Small No Bleed	589
2	Coal		250	40	Shale		629
12	Lime		262	3	Coal		632
3	Shale		265	1	Lime		633
1	Lime	KC	266	8	Shale		641
102	Shale		368	2	Shale Very Broken Sand	Light Bleed CP	643
4	Lime		372	7	Broken Sand	50% Light Bleed	650
26	Shale		398	8	Sand Solid	Good Bleed	658
8	Lime	Soft	406	77	Shale		735
5	Shale		411				
18	Lime		429			Waylon	
41	Shale		470			1st Core 527-546	
8	Lime		478			2nd Core 643-661	