



11 Lewis Drive

Paola, KS 66071

**Oil & Gas Well Drilling  
Water Wells  
Geo-Loop Installation**

Phone: 913-557-9083

Fax: 913-557-9084

**WELL LOG**

Verde Oil Company

Campbell # I-95-65

API #15-001-31,143

August 26 - August 27, 2014

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
3	soil & clay	3
13	broken lime	16
27	lime	43
5	shale	48
2	lime	50
18	shale	68
75	lime	143 base of the Kansas City
77	shale	220
6	lime	226
52	shale	278
3	lime	281
11	shale	292
1	lime	293
5	shale	298
14	lime	312
89	shale	401
2	lime	403
6	shale	409
12	lime	421 oil show
1	shale	422
7	lime	429
4	shale	433
1	lime	434
35	shale	469
17	lime	486
2	shale	488
1	lime	489
1	shale	490
1	coal	491
6	shale	497
3	lime	500
50	shale	550
2	lime	552
41	shale	593
1	lime	594
49	shale	643
6	broken sand	649 brown/green sand & shale light oil show
57	shale	706
4	oil sand	710 black & dark brown light bleeding

9	shale	719
1	coal	720
26	shale	746
3	broken sand	749 black/white sand no show
15	shale	764
2	broken sand	766 brown & grey ok bleeding
7	broken sand	773 hard light brown sand & shale no show
20	silty shale	793
1	broken sand	794 hard brown sand & shale light bleeding
9	silty shale	803
11	oil sand	814 soft brown good bleeding
2	shale	816
2	sand	818 grey sandy shale no show
2	broken sand	820 brown sand & shale good bleeding
4	oil sand	824 soft brown sand good bleeding
2	oil sand	826 brown & grey good bleeding
1	coal	827
27	sand	854 grey & black no show
27	shale	881
5	sand	886 hard white sand no oil
3	shale	889 TD Mississippi

Drilled a 9 7/8" hole to 21.8'

Drilled a 5 5/8" hole to 889'

Set 21.8' of 7" surface casing, cemented with 5 sacks cement.

Set 885' of 2 7/8" 8 round upset tubing with 4 centralizers, 1 float shoe, 1 clamp, 1 baffle