



11 Lewis Drive

Paola, KS 66071

**Oil & Gas Well Drilling
Water Wells
Geo-Loop Installation**

Phone: 913-557-9083

Fax: 913-557-9084

WELL LOG

Verde Oil Company

Campbell #95-75

API #15-001-31,144

August 25 - August 26, 2014

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
3	soil & clay	3
12	broken lime	15
33	lime	48
4	shale	52
2	lime	54
19	shale	73
18	lime	91
3	shale	94
30	lime	124
1	shale	125
20	lime	145 base of the Kansas City
98	shale	243
8	lime	251
30	shale	281
3	lime	284
18	shale	302
2	lime	304
4	shale	308
8	lime	316
2	shale	318
5	lime	323
17	shale	340
1	lime	341
27	shale	368
8	lime	376
28	shale	404
3	lime	407
5	shale	412
12	lime	424
4	shale	428
6	lime	434
41	shale	475
17	lime	492 oil show
1	shale	493
3	lime	496
3	shale	499
6	lime	505
90	shale	595
3	lime	598

111	shale	709
4	broken sand	713 90% black sand 10% limey sand ok bleeding
5	silty shale	718
5	shale	723
1	coal	724
42	shale	766
12	broken sand	778 shale with light brown sand minimal oil show
8	shale	786
5	broken sand	791 light brown hard sand & shale light bleeding
6	silty shale	797
1	broken sand	798 hard brown sand & shale light bleeding
2	broken sand	800 40% brown sand 60% shale good bleeding
27	oil sand	827 soft brown sand very good bleeding
4	oil sand	831 brown & dark grey sand good bleeding
15	oil sand	846 grey good oil show
6	grey sand	852 minimal show
1	coal	853
36	shale	889 Mississippi 889 TD

Drilled a 9 7/8" hole to 21.8'

Drilled a 5 5/8" hole to 899'

Set 21.8' of 7" surface casing, cemented with 5 sacks cement.

Set 886.2' of 2 7/8" 8 round upset tubing with 4 centralizers, 1 float shoe, 1 clamp, 1 seating nipple, 1 baffle