



11 Lewis Drive

Paola, KS 66071

**Oil & Gas Well Drilling
Water Wells
Geo-Loop Installation**

Phone: 913-557-9083

Fax: 913-557-9084

WELL LOG

Verde Oil Company
Campbell #1-95-85
API #15-001-31,145

August 29 - September 3, 2014

<u>Thickness of Strata</u>	<u>Formation</u>	<u>Total</u>
5	soil & clay	5
10	broken lime	15
42	lime	57
3	shale	60
5	lime	65
18	shale	83
72	lime	155
136	shale	291
3	lime	294
16	shale	310
5	lime	315
2	shale	317
10	lime	327
88	shale	415
2	lime	417
6	shale	423
12	lime	435
1	shale	436
8	lime	444
42	shale	486
17	lime	503
7	shale	510
5	lime	515
89	shale	604
1	lime	605
152	shale	757
10	broken sand	767 brown sand, dark shale no show
22	sand	789 brown, no show
7	silty sandy shale	796 darl
13	shale	809
14	broken sand	823 brown bleeding sand and shale
6	oil sand	829 good bleeding, brown
6	shale	835
20	oil sand	855 brown, bleeding
5	sand	860 grey to brown
6	sand	866 grey to black
34	shale	900
1	lime	901 Mississippi TD

Campbell #I-95-85

Page 2

Drilled a 9 7/8" hole to 21.7'

Drilled a 5 5/8" hole to 901'

Set 21.7' of 7" surface casing, cemented with 5 sacks cement.

Set 896' of used 2 7/8" including a cement pup joint, 4 centralizers, 1 float shoe, 1 clamp